


VRF highlighted features

Panasonic provides an extensive range of solutions for medium and large sized buildings, combining the best options to satisfy all needs and site restrictions.



		ECOi. Electrical VRF	:		ECO G. Gas F	Powered VRF
R32	R410A	R32	R410A	R410A	R410A	R410A
Mini ECOi LZ2	Mini EC0i LE2/LE1	ECOi EX MZ1	ECOi EX ME2	ECOi EX MF3	ECO G GE3	ECO G GF3
			181	-		
-	6 =					
0 0					-	-
			Capacity range			
4 - 10 HP	4 - 10 HP	8 - 48 HP	8 - 80 HP	8 - 48 HP	16 - 60 HP	16 - 25 HP
		Extrer	me temperatures ope	eration		
-20 °C (heating) /	-20 °C (heating) /	-25 °C (heating) /	-25 °C (heating) /	-20 °C (heating) /	-21 °C (heating) /	-21 °C (heating)
52 °C (cooling)	46 °C (cooling)	52 °C (cooling)	52 °C (cooling)	52 °C (cooling)	43 °C (cooling)	43 °C (cooling)
		Maximum nu	mber of connectable	indoor units		
16 ¹⁾	15	64	64	52	64	24
		Indoor	to outdoor connection	on ratio		
50 ~ 150%	50 ~ 130%	50 ~ 200%	50 ~ 200%	50 ~ 150%	50 ~ 200% ²⁾	50 ~ 200%
			Indoor units			
		A	All (check restrictions	;}		
			Controls			
			All			
		Ot	her ranges integrati	on		
	PACi rar	nge full control integ	ration + Domestic ra	nge integration by ac	ressorv	

Panasonic EC0i is Eurovent certified. Panasonic's VRF systems - EC0i range is now certified by Eurovent*.



The Eurovent certification verifies the performance ratings of heating and cooling systems following European standards. Those data provides products efficiency with full transparency for the benefit of customers and professionals.

* Reference website: https://www.eurovent-certification.com/en.

Energy saving



Refrigerant R32.

Our heat pumps containing R32 refrigerant show a drastic reduction in the value of Global Warming Potential (GWP).



Inverter Plus system.

Inverter Plus system classification highlights Panasonic's highest performing systems.



Panasonic R2 rotary compressor.

Designed to withstand extreme conditions, it delivers high performance and efficiency.



All Inverter compressors.

Multiple large-capacity all Inverter compressors (more than 14 HP). Two independently controlled Inverter compressors achieve high efficiency. Redesigned components in the body provide performance improvement especially in the rated cooling condition and EER performance.



High COP.

High efficiency models performs higher COP than standard units and standard combinations.



Gas powered.

ECO G technology offers the best in energy efficiency. ECO G gas VRF is specially designed for buildings where the electricity is restricted or CO, emissions must be reduced.



Econavi.

Intelligent human activity sensor and sunlight sensor technologies that can detect and reduces the waste of energy by optimising air conditioner operation according to room conditions. With just one touch of a button, you can save energy.



ERP 2018.

Compliant following COMMISSION REGULATION (EU) No2016/2281.

High performance and indoor air quality





Panasonic has extended the life of its condensers with an original anti-rust coating.



Down to -10 °C in cooling mode.

The air conditioner works in cooling mode when the outdoor temperature of -10 °C.



Down to -25 °C in heating mode.

The air conditioner works in heat pump mode when the outdoor



temperature is as low as -25 °C.

Cooling with outdoor temperature up

to 52 °C. The ECOi EX system works in cooling mode with performance data at outdoor temperature up to 52 °C.



Automatic restart.

Automatic restart function for power failure. Even when power failure occurs, preset programmed operation can be reactivated once power is resumed.



r R22 renewal.

™ One Panasonic renewal system allows good quality existing R22 pipe work to be re-used whilst installing high efficiency R410A systems.



nanoe™ X.

Technology with the benefits of hydroxyl radicals has the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise.



Self-diagnosing function.

By using electronic control valves past warnings are stored. This makes it easier to diagnose malfunctions, reducing service labour and therefore



Automatic fan operation.

Convenient microprocessor control automatically adjusts fan speed to High, Medium or Low, corresponding to room sensor and maintains comfortable air flow throughout the room.



Mild Dry.

By intermittent control of compressor and indoor unit's fan, "Mild Dry" gives you comfort. It realizes efficient dehumidification according to room temperature.



Comfortable auto-flap control.

When the unit is first turned on, flap position is automatically adjusted in accordance with the cooling or heating operation.



Air Sweep.

The air sweep function moves the flap up and down in the air outlet, directing air in a "sweeping" motion around the room and providing comfort in every corner.



Built-in drain pump.

Maximum head 50 cm (or 75 cm for U type) from the bottom of the unit.



Filter included.

Hide-away with filter included.



5 Years compressor warranty.

We guarantee the outdoor unit compressors in the entire range for five years.

High connectivity



Domestic integration to S-Link - CZ-CAPRA1.

Can connect RAC range to S-Link. Full control is now possible.



Internet control.

A next generation system providing user-friendly control of air conditioning or heat pump units from everywhere, using a simple Android™ or iOS smartphone or tablet via Wi-Fi.



The communication port can be integrated into the indoor unit and provides easy connection to, and control of, your Panasonic air conditioner to your home or Building Management System.



Panasonic AC Smart Cloud.

The AC Smart Cloud from Panasonic allows you to have complete PANASONIC ACSMARTCLOUD control of all your installations. In a simple click, receive status updates from all your units in real-time, preventing breakdowns and optimising costs.

Bringing nature's balance indoors



nanoe™ X, technology with the benefits of hydroxyl radicals.

Abundant in nature, hydroxyl radicals (also known as OH radicals) have the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise. nanoe™ X technology can bring these incredible benefits indoors so that hard surfaces, soft furnishings, and the indoor environment can be a cleaner and more pleasant place to be, whether at home, work, or visiting hotels, shops and restaurants etc.



What is unique about nanoe™ X?

Effective on fabrics and surfaces.



1 | At one billionth of a metre, nanoe TM X is much smaller than steam and can deeply penetrate cloth fabrics to

Longer lifespan.



2 | Contained in tiny water particles, nanoe™ X has a long lifespan, which is about 600 seconds, to spread easily around the room.

Huge quantity.



3 | nanoe X Generator Mark 3 produces 48 trillion hydroxyl radicals per second. Greater amounts of hydroxyl radicals contained in nanoe™ X lead to higher performance on inhibition of pollutants

Maintenance-free.



4 | No service and maintenance required. nange™ X is a filter free solution that does not require maintenance, as its atomisation electrode is enveloped with water during its generation process and it is made with Titatium.

7 effects of nanoe™ X – Panasonic unique technology

Deodorises

Capacity to inhibit 5 types of pollutants

Moisturises







Mould





Generator: nanoe™ X

Mark 2 - 2019





Hazardous substances

* Refer to https://aircon.panasonic.eu for more details and validation data.

First nanoe™ device was developed by Panasonic in 2003


Generator: nanoe™

480 billion hydroxyl radicals/sec

Ion particle structure

Hydroxyl radicals





times

Mark 1 - 2016





48 trillion hydroxyl radicals/sec

Mark 3 - 2022

100x times Panasonic ECOi is Eurovent certified. Panasonic's VRF systems - ECOi range is now certified by Eurovent*.



The Eurovent certification verifies the performance ratings of heating and cooling systems following European standards. Those data provides products efficiency with full transparency for the benefit of customers and professionals.

* Reference website: https://www.eurovent-certification.com/en.

Energy saving



Refrigerant R32.

Our heat pumps containing R32 refrigerant show a drastic reduction in the value of Global Warming Potential (GWP).



Inverter Plus system.

Inverter Plus system classification highlights Panasonic's highest performing systems.



Panasonic R2 rotary compressor.

Designed to withstand extreme conditions, it delivers high performance and efficiency.



All Inverter compressors.

Multiple large-capacity all Inverter compressors (more than 14 HP). Two independently controlled Inverter compressors achieve high efficiency. Redesigned components in the body provide performance improvement especially in the rated cooling condition and EER performance.



High COP.

High efficiency models performs higher COP than standard units and standard combinations.



Gas powered.

ECO G technology offers the best in energy efficiency. ECO G gas VRF is specially designed for buildings where the electricity is restricted or CO, emissions must be reduced.



Econavi.

Intelligent human activity sensor and sunlight sensor technologies that can detect and reduces the waste of energy by optimising air conditioner operation according to room conditions. With just one touch of a button, you can save energy.



ERP 2018.

Compliant following COMMISSION REGULATION (EU) No2016/2281.

High performance and indoor air quality





Panasonic has extended the life of its condensers with an original anti-rust coating.



Down to -10 °C in cooling mode.

The air conditioner works in cooling mode when the outdoor temperature of -10 °C.



Down to -25 °C in heating mode.

The air conditioner works in heat pump mode when the outdoor temperature is as low as -25 °C.



Cooling with outdoor temperature up

to 52 °C. The ECOi EX system works in cooling mode with performance data at outdoor temperature up to 52 °C.



Automatic restart.

Automatic restart function for power failure. Even when power failure occurs, preset programmed operation can be reactivated once power is resumed.



r R22 renewal.

™ One Panasonic renewal system allows good quality existing R22 pipe work to be re-used whilst installing high efficiency R410A systems.



nanoe™ X.

Technology with the benefits of hydroxyl radicals has the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise.



Self-diagnosing function.

By using electronic control valves past warnings are stored. This makes it easier to diagnose malfunctions, reducing service labour and therefore



Automatic fan operation.

Convenient microprocessor control automatically adjusts fan speed to High, Medium or Low, corresponding to room sensor and maintains comfortable air flow throughout the room.



Mild Dry.

By intermittent control of compressor and indoor unit's fan, "Mild Dry" gives you comfort. It realizes efficient dehumidification according to room temperature.



Comfortable auto-flap control.

When the unit is first turned on, flap position is automatically adjusted in accordance with the cooling or heating operation.



Air Sweep.

The air sweep function moves the flap up and down in the air outlet, directing air in a "sweeping" motion around the room and providing comfort in every corner.



Built-in drain pump.

Maximum head 50 cm (or 75 cm for U type) from the bottom of the unit.



Filter included.

Hide-away with filter included.



5 Years compressor warranty.

We guarantee the outdoor unit compressors in the entire range for five years.

High connectivity



Domestic integration to S-Link - CZ-CAPRA1.

Can connect RAC range to S-Link. Full control is now possible.



Internet control.

A next generation system providing user-friendly control of air conditioning or heat pump units from everywhere, using a simple Android™ or iOS smartphone or tablet via Wi-Fi.



The communication port can be integrated into the indoor unit and provides easy connection to, and control of, your Panasonic air conditioner to your home or Building Management System.



Panasonic AC Smart Cloud.

The AC Smart Cloud from Panasonic allows you to have complete control of all your installations. In a simple click, receive status updates from all your units in real-time, preventing breakdowns and optimising costs.

VRF outdoor units range

Outdoor units	4 HP	5 HP	6 HP	8 HP	10 HP	12 HP
R32						
11.02	Present BITTER	Proceeds BECOM	Proceeds STOTAL	E E E E E E E E E E E E E E E E E E E	Time to the time t	
Mini ECOi LZ2 Series - R32	- 832	- 00				
Jei les - R32	U-4LZ2E5 / U-4LZ2E8	U-5LZ2E5 / U-5LZ2E8	U-6LZ2E5 / U-6LZ2E8	U-8LZ2E8	U-10LZ2E8	
Mini ECOi LE2 / LE1 Series · R410A		1000 mg 1000 m	THE STATE OF THE S			
			-			
	U-4LE2E5 / U-4LE2E8	U-5LE2E5 / U-5LE2E8	U-6LE2E5 / U-6LE2E8	U-8LE1E8	U-10LE1E8	
R32					Assess	
				-	-	70
NEW 2-Pipe ECOi EX MZ1				4		
Series - R32				U-8MZ1E8	U-10MZ1E8	U-12MZ1E8
				7	in the second se	100
2-Pipe ECOi EX					=	- No.
ME2 Series - R410A					-	
				U-8ME2E8	U-10ME2E8	U-12ME2E8
				8		=
3-Pipe ECOi EX MF3 Series - R410A						
rii o series - Karoa						
				U-8MF3E8	U-10MF3E8	U-12MF3E8
2 Bi FCO C CF2						
2-Pipe ECO G GE3 Series · R410A						
3-Pipe ECO G GF3						
Series - R410A						

GHP/EHP Hybrid System - R410A

30 HP

U-14ME2E8 U-16ME2E8 U-18ME2E8 U-20ME2E8 U-14MF3E8 U-16MF3E8 U-16GE3E5 U-20GE3E5 U-25GE3E5 U-30GE3E5 U-16GF3E5 U-20GF3E5 U-25GF3E5

20 HP

25 HP

14 HP

16 HP

18 HP



Best efficiency EC0i Series from Panasonic

The ECOi Series is designed for energy savings, easy installation, and high efficiency. Always continuing to evolve, Panasonic uses advanced technologies to meet the requirements of diverse situations and contribute to the creation of comfortable living spaces.



Mini EC0i LZ2 Series - R32.

From 4 to 10 HP.

The Mini ECOi LZ2 Series utilizes environmentally friendly R32 refrigerant, reducing the total amount of refrig erant by 20% and more, resulting in lower GWP, reduced by 75%*.

* As a result of applying R32 while at the same time reducing the total refrigerant amount.



New 2-Pipe ECOi EX MZ1 Series . R32

From 8 to 48 HP.

The next generation in energy efficiency and versatility for commercial applications.



Mini EC0i LE Series R410A.

From 4 to 10 HP.

The 2-Pipe heat pump small VRF system specifically designed for the European market.



2-Pipe EC0i EX ME2 Series · R410A.

From 8 to 80 HP.

The VRF system delivering energysaving performance, powerful operation, reliability and comfort surpassing anything previously possible.



3-Pipe ECOi EX MF3 Series R410A.

From 8 to 48 HP.

The VRF system that offers high-efficiency and performance for simultaneous heating and cooling.



ECOi R32 - Extended decarbonised solution. Minimize environmental impact.





The ECOi Series with R32 refrigerant has been expanded to minimise the environmental impact of VRF systems for the decarbonised buildings. Advanced R32 technology and optimised design make it a more sustainable alternative to R410A. With lower GWP and superior efficiency, it ensures sustainability throughout its lifetime.

1) GWP of R32 refrigerant is 675, while the GWP of R410A is 2088, 2) Panasonic's internal research. Refrigerant amount reduction compared to the R410A equivalent system. 12 HP model with 30 m piping installation.







Benefit from a substantial 68% ¹⁾ reduction in Global Warming Potential (GWP) and up to 82% ³⁾ total CO₂ Eq reduction thanks to decreased refrigerant volume, all while boosting overall efficiency.





Reliability - R32 standard-compliant.

Panasonic offers safety measures such as a leak detector, alarm, and safety valve kit, compliant with the latest standards. These are designed to meet requirements based on R32 refrigerant density under specific project conditions.





Design flexibility.

Maximum piping length of up to 1000 m.

Extreme operating range, with heating down to -25 °C.

Wide selection of indoor units, including premium nanoe™ X for improved indoor air quality.

Seamless connectivity with a variety of standalone, central, cloud and BMS integration options.

1) GWP of R32 refrigerant is 675, while the GWP of R410A is 2088, 2) Panasonic's internal research. Refrigerant amount reduction compared to the R410A equivalent system. 12 HP model with 30 m piping installation, 3) Total CO₂ Eq= GWP x charge. Panasonic's internal research conducted under consistent system conditions.

High performance of Panasonic's ECOi Series is verified by Eurovent now!





Outstanding efficiency in a compact body and continuous operation even at extreme ambient temperatures. VRF with outstanding energy-saving performance and





8,50 1)

5,05 1)

R32



R32

REFRIGERANT



Extraordinary savings.

Reliable quality - R32 standard-compliant 2). **Panasonic DNA** compressors.

Low height 996 mm.

HIGH **ESP**

pressure 35 Pa.





Quiet mode operation with low capacity drop.



Continuous operation at extreme ambient temperatures.



Increased indoor / outdoor capacity ratio up to 150%.


1) for 4 HP model, 2) Panasonic's R32 safety measures comply with IEC 60335-2-40 (ed. 7.0) and EN 378 (ISO 5149).

Mini ECOi LZ2 provides the optimal performance in any climatic condition.

Extended design operation conditions

LZ2 mini VRF is extremely reliable even under the most difficult conditions. The units can operate in cooling mode at extreme temperatures, 52 °C in cooling and -20 °C in heating mode.

Compatible with a large range of indoor units and controls




An expansion of Panasonic VRF line up, the Mini ECOi R32 is compatible with a large range of indoor units, either supporting Panasonic's optional R32 refrigerant leak detector alarm or having built-in detectors provide a great flexibility for all types of installation, and can utilize all Panasonic's scalable control and monitoring solutions.



Panasonic R32 refrigerant leak detector/alarm (optional)

The optional R32 refrigerant leak detector (CZ-CGLSC2) is available for compatible indoor units, allowing customers to determine if the detector is required for safety compliance or if the indoor unit can be installed without it. This sensor includes an integrated alarm buzzer and can connect to a central alarm system. It links to the indoor unit's remote control terminals and is compatible with any VRF remote controllers, wired or wireless.





Only one remote controller can be connected with the Panasonic R32 refrigerant leak detector.




Non-voltage contact external output, maximum allowable voltage DC 24 V (for central monitoring,

R32 Pump Down solution

R32 Pump Down solution offers the assurance of additional safety protection, whilst expanding the potential installation cases, allowing for installation within smaller rooms.

Suitable for the Mini ECOi LZ2 range up to 10 HP, compatible indoor units connected to CZ-CGLSC2 or integrated Panasonic R32 refrigerant leak detector.




Operation steps: 1 | A leak is detected by the leak detection sensor, 2A | Leak alarm signal is sent to the outdoor unit. 2B | Indoor unit fan activated and runs at maximum speed, 3 | Pump Down procedure is activated. 4 | Solenoid valves are closed preventing refrigerant returning to indoor units. 5 | Outdoor unit is operating in Pump Down mode and check valve only allows flow to the outdoor unit. 6 | Low pressure switch threshold is reached, Error signal isolates the outdoor unit, preventing restart.

Technical focus

- · Simplified design and installation
- Complies with IEC 60335-2-40 ed.6.0
- · Recovers base charge within outdoor unit
- · Expands potential installation cases
- · IP rated connections for outdoor installation

Model reference	Description
PAW-PUD2WB-1	Basic Pump Down system (2 way) for one R32 Mini EC0i outdoor unit



Mini EC0i LZ2 Series 4 to 6 HP - R32

Outstanding efficiency in a compact body and continuous operation even at extreme ambient temperatures.

- · SEER levels up to 8,5 and SCOP levels up to 5,0 (for 4 HP model)
- Continuous operation at extreme ambient temperatures: -20 °C (heating) to 52 °C (cooling)
- · Unique indoors with nanoe™ X, hydroxyl radicals contained in water



HP			4 HP	5 HP	6 HP	4 HP	5 HP	6 HP
Outdoor unit			U-4LZ2E5	U-5LZ2E5	U-6LZ2E5	U-4LZ2E8	U-5LZ2E8	U-6LZ2E8
	Voltage	٧	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Single phase	Single phase	Single phase	Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50	50	50	50
Cooling capacity		kW	12,1	14,0	15,5	12,1	14,0	15,5
EER 1)		W/W	4,53	4,12	3,88	4,53	4,12	3,88
Current		Α	13,30-12,80-12,20	16,90-16,20-15,50	19,60 - 18,70 - 18,00	4,37 - 4,15 - 4,00	5,50 - 5,23 - 5,04	6,44-6,12-5,89
Input power		kW	2,67	3,40	4,00	2,67	3,40	4,00
Heating capacity		kW	12,5	16,0	16,5	12,5	16,0	16,5
COP 1)		W/W	5,27	4,71	4,42	5,27	4,71	4,42
Current		Α	12,00-11,40-11,00	16,90-16,20-15,50	18,50 - 17,70 - 17,00	3,91-3,71-3,58	5,50-5,22-5,03	6,02 - 5,72 - 5,51
Input power		kW	2,37	3,40	3,73	2,37	3,40	3,73
Starting current		Α	1,0	1,0	1,0	1,0	1,0	1,0
Maximum current		Α	19,6	23,7	26,5	7,2	9,2	9,9
Maximum input pov	ver	kW	3,92-4,10-4,28	4,76 - 4,98 - 5,19	5,41 - 5,66 - 5,90	4,40-4,63-4,80	5,69 - 5,99 - 6,22	6,15-6,47-6,72
Maximum number of	of connectable indoor un	its ²⁾	7 (10)	8 (12)	9 (12)	7 (10)	8(12)	9 (12)
External static pres	sure	Pa	0~35	0~35	0~35	0~35	0~35	0~35
Air flow		m³/min	69	72	74	69	72	74
	Cool	dB(A)	52	53	54	52	53	54
Sound pressure	Cool (Silent1/2/3/4)	dB(A)	49/47/45/45	50/48/46/45	51/49/47/45	49/47/45/45	50/48/46/45	51/49/47/45
	Heat	dB(A)	54	56	56	54	56	56
Sound power	Cool / Heat	dB(A)	69/72	70/74	72/75	69/72	70/74	72/75
Dimension	HxWxD	mm	996 x 980 x 370	996 x 980 x 370	996×980×370	996 x 980 x 370	996 x 980 x 370	996×980×370
Net weight		kg	94	94	94	94	94	94
D:=: d:k	Liquid	Inch (mm)	3/8(9,52)	3/8(9,52)	3/8 (9,52)	3/8(9,52)	3/8(9,52)	3/8 (9,52)
Piping diameter	Gas	Inch (mm)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)	5/8(15,88)	5/8 (15,88)	5/8 (15,88)
Maximum piping ler	ngth (total)	m	90 (180)	90 (180)	90 (180)	90 (180)	90 (180)	90 (180)
Elevation difference	(in / out)	m	50 (OU above)/ 40 (OU below)					
Refrigerant (R32)		kg	2,7	2,7	2,7	2,7	2,7	2,7
Maximum allowable capacity ratio 31	indoor / outdoor	%	50~150(130)	50~150(130)	50 ~ 150 (130)	50~150(130)	50~150(130)	50~150(130)
0	Cool Min ~ Max	°C	-10~52	-10~52	-10~52	-10~52	-10~52	-10~52
Operating range	Heat Min ~ Max	°C	-20~18	-20~18	-20~18	- 20 ~ 18	-20~18	-20~18
-								

ErP data 4)						
SEER 5)	8,50	8,12	7,71	8,50	8,12	7,71
η _{s,c}	337,0%	321,8%	305,4%	337,0%	321,8%	305,4%
SCOP 5)	5,05	4,61	4,59	5,05	4,61	4,59
n .	199 በ%	181 4%	180.6%	199 በ%	181 4%	180.6%

1) EER and COP calculation is based in accordance to EN 14511. 2) The number in parenthesis indicates maximum number of connectable indoor unit in case of 1,5 kW indoor units connection. 3) The number in parenthesis indicates maximum allowed indoor / outdoor capacity ratio in case of 1,5 kW indoor units connection. 4) SEER / SCOP and η_{sc} / η_{sh} are in accordance with ErP test data for U2 type 4 way 90x90 cassette indoor units. 5) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency " η " values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = $(\eta + \text{Correction}) \times \text{PEF}$.

Minimum environmental impact

Panasonic has designed the LZ2 series in order to minimize the environmental impact of the system. Low GWP refrigerant R32 and highest efficiency levels ensure this through the total operational lifetime.

For the most challenging spaces

The Mini ECOi LZ2 R32 VRF system is the ideal solution to fit into any application thanks to its compact design and long piping lengths.

Technical focus

- · Widest range of connectable units in R32 VRF
- \cdot Allowing wide range of installations with and without mitigation measures
- Flexible mitigation measures, with Panasonic R32 refrigerant leak detector / alarm to be installed only when required





















INTERNET CONTROL: Optional.

Mini ECOi LZ2 Series 8 and 10 HP · R32

Introducing widest range of R32 Mini VRF.

- \cdot SEER levels up to 7,6 and SCOP levels up to 4,6 (for 8 HP model)
- Continuous operation at extreme ambient temperatures: -20 °C (heating) to 52 °C (cooling)
- Unique indoors with nanoe™ X, hydroxyl radicals contained in water

Industry 1st 8 HP and 10 HP Mini VRF units with R32



НР			8 HP	10 HP
Outdoor unit			U-8LZ2E8	U-10LZ2E8
	Voltage	٧	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase
	Frequency	Hz	50	50
Cooling capacity		kW	22,4	28,0
EER 1)		W/W	3,84	3,47
Current		Α	9,73 - 9,25 - 8,91	13,2 - 12,5 - 12,1
Input power		kW	5,83	8,07
Heating capacity		kW	25,0	28,0
COP 1)		W/W	4,30	4,47
Current		Α	9,81 - 9,32 - 8,98	10,5 - 9,93 - 9,57
Input power		kW	5,81	6,26
Starting current		Α	1,0	1,0
Maximum current		Α	13,7	19,5
Maximum input power		kW	8,21 - 8,64 - 8,96	11,9 - 12,6 - 13,0
Maximum number of connectab	le indoor units ²⁾		16	16
External static pressure		Pa	0~35	0~35
Air flow		m³/min	158	167
C	Cool	dB(A)	59,0	60,0
Sound pressure	Cool (Silent 1/2/3/4)	dB(A)	56/54/52/50	57/55/53/50
Sound power	Cool	dB(A)	72	74
Dimension	HxWxD	mm	1500 x 980 x 370	1500 x 980 x 370
Net weight		kg	125	126
Dining diameter	Liquid	Inch (mm)	3/8(9,52)	3/8(9,52)
Piping diameter	Gas	Inch (mm)	3/4(19,05)	7/8(22,22)
Maximum piping length (total)		m	100 (300)	100 (300)
Elevation difference (in / out)		m	50 (OU above) / 40 (OU below)	50 (OU above) /40 (OU below)
Refrigerant (R32)		kg	4,9	5,1
Maximum allowable indoor / ou	tdoor capacity ratio 3)	%	50 ~ 150 (130)	50~150(130)
0	Cool Min ~ Max	°C	-10~52	-10~52
Operating range	Heat Min ~ Max	°C	-20~18	-20~18

R32

ErP data 4)		
SEER 5)	7,56	7,08
$\eta_{s,c}$	299,4%	280,2%
SCOP 5	4,59	4,60
$\eta_{s,h}$	180,6%	181,0%

1) EER and COP calculation is based in accordance to EN 14511. 2) The number in parenthesis indicates maximum number of connectable indoor unit in case of 1,5 kW indoor units connection. 3) The number in parenthesis indicates maximum allowed indoor / outdoor capacity ratio in case of 1,5 kW indoor units connection. 4) SEER / SCOP and $\eta_{sc}/\eta_{s,h}$ are in accordance with ErP test data for F2 type variable static pressure hide-away indoor units. 5) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency "ŋ" values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = (η + Correction) × PEF.

Perfect fit for small to medium size projects

8 and 10 HP LZ2 Mini VRF units bring in the total benefits of a VRF system in a smaller application. You can enjoy advanced individual and central VRF control options including the revolutionary Panasonic AC Smart Cloud and AC Service Cloud.

For the most difficult conditions

The Mini ECOi LZ2 series are able to operate at the hardest conditions from -20 °C up to +52 °C providing continuous and efficient, heating and cooling for your space all year long.

Technical focus

- · Widest range of connectable units in R32 VRF
- · Allowing wide range of installations with and without refrigerant mitigation
- Flexible mitigation measures, with Panasonic R32 refrigerant leak detector / alarm to be installed only when required






















INTERNET CONTROL: Optional.



1) for 4 HP model, 2) For model 4-6 HP.

pressure 35 Pa.

extreme ambient

temperatures.

capacity ratio up to 130%.

Mini ECOi LE2 Series high efficiency 4 to 6 HP · R410A

Panasonic Mini ECOi. Extraordinary energy-saving.

The most compact ECOi system ever.

- · Outstanding SEER and SCOP
- · Better efficiency even compared to 2 fan outdoor units



HP			4 HP	5 HP	6 HP	4 HP	5 HP	6 HP
Outdoor unit			U-4LE2E5	U-5LE2E5	U-6LE2E5	U-4LE2E8	U-5LE2E8	U-6LE2E8
	Voltage	٧	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	380 - 400 - 415	380 - 400 - 415	380-400-415
Power supply	Phase		Single phase	Single phase	Single phase	Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50	50	50	50
Cooling capacity		kW	12,1	14,0	15,5	12,1	14,0	15,5
EER 1)		W/W	4,50	4,06	3,73	4,50	4,06	3,73
Current		Α	13,30-12,70-12,20	16,30-15,60-17,00	20,30 - 19,40 - 18,60	4,39 - 4,17 - 4,02	5,58-5,30-5,11	6,71-6,37-6,14
Input power		kW	2,69	3,45	4,15	2,69	3,45	4,15
Heating capacity		kW	12,5	16,0	16,5	12,5	16,0	16,5
COP 1)		W/W	5,19	4,60	4,27	5,19	4,60	4,27
Current		Α	12,20-11,60-11,20	17,60 - 16,80 - 16,10	19,10-18,20-17,50	3,98-3,78-3,64	5,62-5,34-5,14	6,24-5,93-5,71
Input power		kW	2,41	3,48	3,86	2,41	3,48	3,86
Starting current		A	1,00	1,00	1,00	1,00	1,00	1,00
Maximum current		Α	17,30	24,30	27,40	7,90	10,10	10,70
Maximum input pow	ver	kW	3,50 - 3,66 - 3,82	4,92-5,14-5,37	5,61-5,86-6,12	4,34 - 5,09 - 5,28	6,25-6,55-6,82	6,62 - 6,97 - 7,23
Maximum number o	of connectable indoor un	its 2)	7(10)	8 (10)	9(12)	7 (10)	8(10)	9 (12)
External static pres	sure	Pa	0~35	0~35	0~35	0~35	0~35	0~35
Air flow		m³/min	69	72	74	69	72	74
	Cool	dB(A)	52	53	54	52	53	53
Sound pressure	Cool (Silent1/2/3/4)	dB(A)	50,5/49/47/45	51,5/50/48/46	52,5/51/48/46	50,5/49/49/47	48,5/50/48/46	48,5/50/48/46
	Heat	dB(A)	54	56	56	54	56	56
Sound power	Cool / Heat	dB(A)	69/72	71/75	73/75	69/72	71/75	73/75
Dimension	HxWxD	mm	996 x 980 x 370	996×980×370	996 x 980 x 370	996×980×370	996×980×370	996×980×370
Net weight		kg	106	106	106	106	106	106
	Liquid	Inch (mm)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)
Piping diameter	Gas	Inch (mm)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)
Maximum piping ler	ngth (total)	m	150 (180)	150 (180)	150 (180)	150 (180)	150 (180)	150 (180)
Elevation difference	(in / out)	m	50 (OU above)/ 40 (OU below)	50 (OU above) / 40 (OU below)	50 (OU above)/ 40 (OU below)	50 (OU above)/ 40 (OU below)	50 (OU above)/ 40 (OU below)	50 (OU above) / 40 (OU below)
Refrigerant (R410A)	/ CO _z Eq.	kg / T	6,70(14,40)/ 13,9896	6,70 (14,40)/ 13,9896	6,70(14,40)/ 13,9896	6,70(14,40)/ 13,9896	6,70(14,40)/ 13,9896	6,70(14,40)/ 13,9896
Maximum allowable capacity ratio	e indoor / outdoor	%	50~130	50~130	50~130	50~130	50~130	50~130
Operating range	Cool Min - Max	°C	-10~+46	-10~+46	-10~+46	-10~+46	-10~+46	-10~+46
Operating range	Heat Min ~ Max	°C	-20~+18	-20~+18	-20~+18	-20~+18	-20~+18	-20~+18

ErP data 3)						
SEER 4)	7,85	7,48	7,25	7,85	7,48	7,25
η _{s,c}	311,0%	296,2%	286,8%	311,0%	296,2%	286,8%
SCOP 4)	4,87	4,40	4,24	4,87	4,40	4,24
$\eta_{s,h}$	191,8%	172,9%	166,7%	191,8%	172,9%	166,7%

1) EER and COP calculation is based in accordance to EN 14511. 2) In case of 1,5 kW indoor units connection, able to connect maximum 12 indoor units. 3) SEER / SCOP and $\eta_{s,c}$ / $\eta_{s,b}$ are in accordance with ErP test data for F2 type variable static pressure hide-away indoor units. 4) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency "ŋ" values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = (ŋ + Correction) x PEF.

For light commercial use

Mini ECOi allows easier installation in condominiums and medium sized buildings with limited spaces. Utilising R410A and DC Inverter technology, Panasonic offers VRF to a new and growing market.

Reduced height of 996 mm

In addition to raising efficiency, the outdoor unit has been designed to be as compact as possible. It can now be installed in places that were previously too small.

Technical focus

- · 50 m piping without additional refrigeration charge
- · High static pressure 35 Pa
- High COP mode selectable with maintenance remote controller
- · Selectable silent mode





















Mini ECOi LE1 Series high efficiency 8 and 10 HP · R410A

Prepare to be blown away by Panasonic's Mini VRF system.

The Mini VRF compact system is the ideal solution for minimum outdoor space.

Panasonic extends the Mini VRF range by 8 and 10 HP units.

- Piping flexibility with 150 m maximum length
- · High efficiency



HP			8 HP	10 HP
Outdoor unit			U-8LE1E8	U-10LE1E8
	Voltage	٧	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase
	Frequency	Hz	50	50
Cooling capacity		kW	22,4	28,0
EER 1)		W/W	3,80	3,11
Current		Α	9,60-9,15-8,80	14,70 - 14,00 - 13,50
Input power		kW	5,89	9,00
Heating capacity		kW	25,0	28,0
COP 1)		W/W	4,02	3,93
Current		Α	10,20-9,65-9,30	11,60 - 11,10 - 10,70
Input power		kW	6,22	7,13
Starting current		Α	1,00	1,00
Maximum current		Α	13,70	19,60
Maximum input power		kW	9,16	13,10
Maximum number of connecta	able indoor units 2)		15	15
External static pressure		Pa	0~35	0~35
Air flow		m³/min	150	160
	Cool	dB(A)	60	63
Sound pressure	Cool (Silent 1/2/3)	dB(A)	57/55/53	60/58/56
	Heat	dB(A)	64	65
Sound power	Cool / Heat	dB(A)	81/85	84/86
Dimension	HxWxD	mm	1500 x 980 x 370	1500 x 980 x 370
Net weight		kg	132	133
Dining diameter	Liquid	Inch (mm)	3/8 (9,52) ³⁾ / 1/2 (12,70) ⁴⁾	3/8(9,52)3/1/2(12,70)4)
Piping diameter	Gas	Inch (mm)	3/4 (19,05) 3) /7/8 (22,22) 4)	7/8 (22,22) 3) / 1 (25,40) 4)
Maximum piping length (total)		m	7,5~150 (7,5~300)	7,5~150(7,5~300)
Elevation difference (in / out)	<u> </u>	m	50 (OU above) / 40 (OU below)	50 (OU above) /40 (OU below)
Refrigerant (R410A) / CO, Eq.		kg / T	6,30(24,00)/13,1544	6,60(24,00)/13,7808
Maximum allowable indoor / o	outdoor capacity ratio	%	50~130	50~130
0	Cool Min ~ Max	°C	-10~+46	-10~+46
Operating range	Heat Min ~ Max	°C	-20~+18	-20~+18

ErP data 5)		
SEER 61	6,27	6,37
η _{6.6}	247,9%	251,8%
SCOP 6)	4,24	4,31
$\eta_{s,h}$	166,4%	169,5%

1) EER and COP calculation is based in accordance to EN 14511. 2) If the heating utilized, it is necessary to increase 1 size with respect to the main liquid pipe, depending on the combination of the indoor unit. 3) Under 90 m for ultimate indoor unit. 4) Over 90 m for ultimate indoor unit. If the longest piping equivalent length exceeds 90 m, increase the sizes of the main tubes by 1 rank for gas and liquid pipes. 5) SEER / SCOP and $\eta_{\rm hc} / \eta_{\rm hc}$ are in accordance with ErP test data for F2 type variable static pressure hide-away indoor units. 6) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency "ŋ" values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = $(\eta + Correction) \times PEF$.

Increase external static pressure

When unit is installed on a narrow balcony, any barrier in front will be an obstacle. High external static pressure will overcome this obstacle and maintain operating capacity.

High ambient temperature performance

Cooling operation range up to 46 °C. The system can maintain the rated (100%) capacity up to 40 °C by 8 HP model and up to 37 °C by 10 HP model.

Technical focus

- · Connection of up to 15 indoor units
- Quiet operation mode (one of the lowest in the market)
- High ambient temp performance
- · High static pressure 35 Pa





















INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB, Cooling outdoor 35 °C DB / 24 °C WB, Heating indoor 20 °C DB, Heating outdoor 7 °C DB / 6 °C WB, [DB: Dry Bulb; WB: Wet Bulb], Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

ECOi EX Series



ECOi EX range system delivering energy-saving performance, powerful operation, reliability and comfort surpassing anything previously possible. Taking quality to the extreme — that's the Panasonic challenge.





High performance at extreme conditions.


ECOi EX is highly reliable, with strong cooling and heating power, even when operating at extreme ambient temperatures. The units deliver excellent cooling performance up to 52 °C and heating operation down to -25 °C*.

Also, the ECOi EX features include Bluefin in the heat exchanger, improving efficiency in marine ambient. A silicone coated PCB (Printed Circuit Board) protects the unit from being damaged by environmental factors such as moisture and dust.



Outstanding efficiency and comfort.

The ECOi EX system is designed to increase energy efficiency by delivering high SEER rating, as well as high efficiency for part-load operation. The system has reduced energy costs thanks to "All-Inverter Compressors" with independent control, to deliver highly flexible performance. Also, the ECOi EX features an enlarged heat exchanger with triple surfaces that allow for improved heat transfer and a curved air discharge bell-mouth, for better aerodynamics. The three-stage oil recovery design makes it able to minimise the frequency of forced oil recovery, leading to reduced energy costs and sustained comfort.



Superior flexibility.

With up to 1000* meters of pipeline, 30 meters maximum height difference between indoor units and maximum 100 meters between outdoor unit and indoor unit, the design possibilities have grown exponentially, making the ECOi EX the ideal air conditioning option for expansive buildings, such as train stations, airports, schools or hospitals. These advantages are enhanced with the wide range of indoor unit models and capacities, facilitating the perfect adaptation to all kinds of project. The careful selection of controls and peripherals such as the Pump Down, the AHU and / or the chiller, enables an optimised system selection. Maximum allowable indoor / outdoor connected capacity ratio of up to 200%.

New generation of 2-Pipe EC0i EX MZ1 Series R32

Extreme efficiency, quality, compact.

Panasonic provides safety measure compliant with the latest standards, as required based on R32 refrigerant density under specific project conditions. Everything necessary for R32 refrigerant safety is prepared by Panasonic.







η_{s,h}







Reliable quality - R32 standard-compliant 11.

High seasonal efficiency.


More sustainable solution 3).

Saving installation

Silent mode, maintaining high capacity.



Extended operation range.



Flexible piping installation.



Maximum indoor / outdoor capacity ratio 200%.



Saving installation cost.

1) Panasonic's R32 safety measures comply with IEC 60335-2-40 (ed. 7.0) and EN 378 (ISO 5149). 2) U-10MZ1E8. 3) Compared to R410A systems.

2-Pipe ECOi EX MZ1 Series R32. Enjoy greater installation flexibility and cost savings.



VIDEO


Extensive R32 range to meet any project requirements


- All air to air indoor units are equipped with nanoeTM X for improved indoor air quality
- A range of ventilations including ERVs and AHU connection kits
- A wide range of connectivity options, including standalone, central, and remote monitoring, with BMS integration for seamless operation



High efficiency in a compact outdoor unit

Significantly reduced volume and a lightweight chassis help reduce design and installation work.










1) 12 HP model compared to the equivalent conventional R410A ECOi EX model, 2) 8 and 10 HP models,

Maximum comfort with silent operation mode

Thanks to the optimised bell mouth design, sound pressure can be reduced to as low as 54 dB(A)* in silent mode while maintaining high cooling capacity.


* For model U-8MZ1E8.



- Silent operation mode reduces outdoor unit noise down to 50 dB(A)
- 3-step set point available
- Silent mode 1 maintains rated 100% cooling capacity


Noise (SPL)	8 HP	10 HP	12 HP
Nominal	57 dB(A)	60 dB(A)	64 dB(A)
Silent mode 1	54 dB(A)	57 dB(A)	61 dB(A)
Silent mode 2	52 dB(A)	55 dB(A)	59 dB(A)
Silent mode 3	50 dB(A)	50 dB(A)	50 dB(A)

Improved bell mouth design.




MZ1 Series maintains high performance even at extremely low winter temperatures.

Wide operating limits




Cooling: Outside air temperature ${\rm ^{\circ}C}$ (DB), Heating: Outside air temperature ${\rm ^{\circ}C}$ (WB),



* Maximum capacity unaffected by defrost operation.

Refrigerant amount reduction and piping material choice

The new MZ1 Series uses only 57%* of the R32 refrigerant compared to the R410A equivalent system and supports imperial or metric piping installation.



^{*} Panasonic's internal research. 12 HP model with 30 m piping installation.

R32 safety measures by Panasonic.

Everything necessary for R32 refrigerant safety is prepared by Panasonic.

Panasonic provides safety measure compliant with the latest standards, as required based on R32 refrigerant density under specific project conditions. Everything necessary for R32 refrigerant safety is prepared by Panasonic.

The safety measures which comply with EN 378 (ISO 5149) and IEC 60335-2-40 (ed. 7.0).

Leak detector -CZ-CGLSC2.

Leak detector designed for 4 way 90x90 cassettes, 4 way 60x60 cassettes, and wall-mounted units.



Leak alarm -CZ-CGLALC1.

R32 refrigerant leak alarm designed for adaptive duct and slim duct units.



2-pipe safety valve kit - CZ-P1160SVK.

A 2-pipe safety valve manages the shutdown of only the area / zone experiencing a refrigerant leak, instead of shutting down the whole system.




External power supply - PAW-16DC-ALC1.

External 16 V power supply (EN 378 compliant), including a leak alarm for remote locations. The leak alarm can be deactivated.



Example of how R32 safety measures work in an HVAC system.



^{*} A maximum of 1 leak detector can be connected per indoor unit or group. If a leak detector is connected, only 1 wired remote controller is allowed (no sub-controller). Up to 8 units, including indoor units and a safety valve, can be connected. 1) In accordance with EN 378-3, alarm systems such as external leak detectors and safety alarms require a power source independent of the air conditioning system they are protecting. In addition, they must have a backup power source and be able to alert a monitored location. For further information, please contact an authorised Panasonic dealer.

NEW 2-Pipe EC0i EX MZ1 Series - R32

Extreme efficiency, quality, compact.

With advanced R32 refrigerant technology and optimised system design, this series offers a more sustainable solution compared to R410A. Wide operation range from -25 °C in heating to +52 °C in cooling.



HP			8 HP	10 HP	12 HP
Outdoor unit			U-8MZ1E8	U-10MZ1E8	U-12MZ1E8
	Voltage	V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50
Cooling capacity		kW	22,4	28,0	33,5
EER 1)		W/W	3,30	3,50	3,00
Current		Α	11,70 - 11,10 - 10,70	13,50 - 12,80 - 12,40	18,30 - 17,40 - 16,80
Input power		kW	6,78	8,00	11,1
Heating capacity		kW	25,0	31,5	37,5
COP 1)		W/W	4,50	4,30	4,00
Current		Α	9,81 - 9,32 - 8,98	12,50 - 11,90 - 11,50	15,70 - 14,90 - 14,40
Input power		kW	5,55	7,32	9,37
Starting current		Α	1,00	1,00	1,00
External static pressure	(Max)	Pa	80	80	80
Air flow		m³/min	209	209	209
Cd	Normal mode (Cool / Heat)	dB(A)	57/57	60/60	64/67
Sound pressure	Silent mode 1 / 2 / 3 (Cool)	dB(A)	54/52/50	57/55/50	61/59/50
Sound power	Normal mode (Cool / Heat)	dB(A)	75/75	77/77	81/84
Dimension	HxWxD	mm	1660 x 880 x 765	1660 x 880 x 765	1660 x 880 x 765
Net weight		kg	203	203	206
	Liquid	Inch (mm)	3/8(9,52)/1/2(12,70)	3/8(9,52)/1/2(12,70)	3/8 (9,52) / 1/2 (12,70)
Piping diameter 2)	Gas	Inch (mm)	3/4(19,05)/7/8(22,22)	3/4(19,05)/7/8(22,22)	7/8(22,22)/1-1/8(28,58)
	Balance	Inch (mm)	1/4(6,35)	1/4(6,35)	1/4(6,35)
Refrigerant (R32) / CO, E	iq	kg/T	6,30/4,25	6,40/4,32	8,50/5,74
Maximum allowable indo	oor / outdoor capacity ratio 3)	%	50~200 (130)	50~200(130)	50~200 (130)
0	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52
Operating range	Heat Min ~ Max	°C	-25~+24	-25~+24	-25~+24

ErP data 4)			
SEER 5)	7,27	7,82	7,37
$\eta_{s,c}$	288,0%	310,1%	292,1%
SCOP 5)	4,35	4,38	4,33
n _{s,h}	171,0%	172,4%	170,3%

¹⁾ EER and COP calculation is based in accordance to EN 14511. 2) Piping diameter under 100 m for ultimate indoor unit / over 100 m for ultimate indoor unit (if the longest piping equivalent length exceeds 100 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes). 3) If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units. B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB (standard -25 °C WB). C. Simultaneous operation is limited to less than 130% of connectable indoor units. 4) SEER / SCOP and n₂, / n₃, are in accordance with ErP test data for U2 type 4 way 90x90 cassette indoor units. 5) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency "η" values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = (η + Correction) × PEF.

Technical focus

- · Compact outdoor unit with a significant 43% 1) footprint reduction, delivering high seasonal efficiency, reliable quality, and R32 standard compliance
- · The series uses only 57% 2 of the R32 refrigerant compared to R410A equivalent system, minimizing the need for extra safety measures
- Extensive R32 Range with all air-to-air indoor units equipped with nanoe™ X, along with ERVs and AHU connection kits
- · A wide range of connectivity options, including standalone, central, and remote monitoring, with BMS integration for seamless operation
- 1) 12 HP model compared to the equivalent conventional R410A ECOi EX ME2. 2) Panasonic's internal research. 12 HP model with 30 m piping installation.

















2-Pipe ECOi EX MZ1 Series R32 combination from 16 to 48 HP - R32

pressure Silent mo		Hz kW W/W A kW W/W	13,6 50,0 4,50 4,32/169,8%	14,8 56,5 4,30 4,33/170,3%	U-8MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 55,9 3,10 7,29/288,9% 30,00-28,50-27,50 17,9 62,5 4,10 4,29/168,8%	U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 56,0 3,50 7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20 4,38/172,2%	Three phase 50 61,5 3,20 7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	22,2 75,0 3,90	Three phase 50 67,2 3,20	U-8MZ1E8 U-8MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 72,8 3,30 7,46/295,6% 36,90-35,00-33,80 21,6 81,5 4,40
Power supply Phase Frequence Cooling capacity EER 1) SEER 2/ n _{s,c} Current Input power Starting capacity Current Input power Starting current External static pressure Air flow Sound Pressure Sound Normal ressure Sound power Normal ressure Nor		Hz kW W/W A kW W/W A kW W/W	380 - 400 - 415 Three phase 50 44,8 3,20 7,24/286,8% 23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	380 - 400 - 415 Three phase 50 50,4 3,40 7,56/299,6% 25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	380 - 400 - 415 Three phase 50 55,9 3,10 7,29/288,9% 30,00-28,50-27,50 17,9 62,5 4,10	380 - 400 - 415 Three phase 50 56,0 3,50 7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20	380 - 400 - 415 Three phase 50 61,5 3,20 7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	380 - 400 - 415 Three phase 50 67,0 3,00 7,33/290,2% 36,60-34,80-33,60 22,2 75,0 3,90	U-8MZ1E8 380-400-415 Three phase 50 67,2 3,20 7,24/286,8% 35,10-33,30-32,10 20,4 75,0	U-10MZ1E8 380 - 400 - 415 Three phase 50 72,8 3,30 7,46/295,6% 36,90-35,00-33,80 21,6 81,5
Power supply Phase Frequence Cooling capacity EER 11 SEER 21/ \(\eta_{s,c}\) Current Input power Heating capacity COP 11 SCOP 21/ \(\eta_{s,h}\) Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent modes Sound power Normal r Dimension HxWxD		Hz kW W/W A kW W/W A kW W/W	Three phase 50 44,8 3,20 7,24/286,8% 23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	Three phase 50 50,4 3,40 7,56/299,6% 25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	Three phase 50 55,9 3,10 7,29/288,9% 30,00-28,50-27,50 17,9 62,5 4,10	Three phase 50 56,0 3,50 7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20	Three phase 50 61,5 3,20 7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	Three phase 50 67,0 3,00 7,33/290,2% 36,60-34,80-33,60 22,2 75,0 3,90	380 - 400 - 415 Three phase 50 67,2 3,20 7,24/286,8% 35,10-33,30-32,10 20,4 75,0	380 - 400 - 415 Three phase 50 72,8 3,30 7,46/295,6% 36,90-35,00-33,80 21,6 81,5
Power supply Phase Frequence Cooling capacity EER 11 SEER 21/ \(\eta_{s,c}\) Current Input power Heating capacity COP 11 SCOP 21/ \(\eta_{s,h}\) Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent modes Sound power Normal r Dimension HxWxD		Hz kW W/W A kW W/W A kW W/W	Three phase 50 44,8 3,20 7,24/286,8% 23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	Three phase 50 50,4 3,40 7,56/299,6% 25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	Three phase 50 55,9 3,10 7,29/288,9% 30,00-28,50-27,50 17,9 62,5 4,10	Three phase 50 56,0 3,50 7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20	Three phase 50 61,5 3,20 7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	Three phase 50 67,0 3,00 7,33/290,2% 36,60-34,80-33,60 22,2 75,0 3,90	Three phase 50 67,2 3,20 7,24/286,8% 35,10-33,30-32,10 20,4 75,0	Three phase 50 72,8 3,30 7,46/295,6% 36,90-35,00-33,80 21,6 81,5
Frequence Cooling capacity EER 1) SEER 2/ N _{5,c} Current Input power Heating capacity COP 1/ SCOP 2/ N _{5,h} Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD	ncy	kW W/W A kW kW W/W	50 44,8 3,20 7,24/286,8% 23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	50 50,4 3,40 7,56/299,6% 25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	50 55,9 3,10 7,29/288,9% 30,00-28,50-27,50 17,9 62,5 4,10	50 56,0 3,50 7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20	50 61,5 3,20 7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	50 67,0 3,00 7,33/290,2% 36,60-34,80-33,60 22,2 75,0 3,90	50 67,2 3,20 7,24/286,8% 35,10-33,30-32,10 20,4 75,0	50 72,8 3,30 7,46/295,6% 36,90-35,00-33,80 21,6 81,5
Cooling capacity EER 1) SEER 2) / n _{s,c} Current Input power Heating capacity COP 1) SCOP 2) / n _{s,h} Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD	ncy	kW W/W A kW kW W/W	44,8 3,20 7,24/286,8% 23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	50,4 3,40 7,56/299,6% 25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	55,9 3,10 7,29/288,9% 30,00-28,50-27,50 17,9 62,5 4,10	56,0 3,50 7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20	61,5 3,20 7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	67,0 3,00 7,33/290,2% 36,60-34,80-33,60 22,2 75,0 3,90	67,2 3,20 7,24/286,8% 35,10-33,30-32,10 20,4 75,0	72,8 3,30 7,46/295,6% 36,90-35,00-33,80 21,6 81,5
EER 1) SEER 2) / \(\emptyset \), s.c Current Input power Heating capacity COP 1) SCOP 2) / \(\emptyset \), s.h Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		A kW kW W/W A kW	3,20 7,24/286,8% 23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	3,40 7,56/299,6% 25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	3,10 7,29 / 288,9% 30,00-28,50-27,50 17,9 62,5 4,10	3,50 7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20	3,20 7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	3,00 7,33/290,2% 36,60-34,80-33,60 22,2 75,0 3,90	3,20 7,24/286,8% 35,10-33,30-32,10 20,4 75,0	3,30 7,46/295,6% 36,90-35,00-33,80 21,6 81,5
SEER 21 / 1, s,c Current Input power Heating capacity COP 11 SCOP 21 / 1, s,h Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		A kW kW W/W	7,24/286,8% 23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	7,56/299,6% 25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	7,29 / 288,9% 30,00-28,50-27,50 17,9 62,5 4,10	7,82/310,1% 27,00-25,60-24,80 16,0 63,0 4,20	7,55/299,1% 31,80-30,20-29,20 19,1 69,0 4,10	7,33/290,2% 36,60-34,80-33,60 22,2 75,0 3,90	7,24/286,8% 35,10-33,30-32,10 20,4 75,0	7,46/295,6% 36,90-35,00-33,80 21,6 81,5
Current Input power Heating capacity COP 11 SCOP 21 / N _{5,h} Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		kW kW W/W	23,40-22,20-21,40 13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	25,20-23,90-23,10 14,8 56,5 4,30 4,33/170,3%	30,00-28,50-27,50 17,9 62,5 4,10	27,00-25,60-24,80 16,0 63,0 4,20	31,80-30,20-29,20 19,1 69,0 4,10	36,60-34,80-33,60 22,2 75,0 3,90	35,10-33,30-32,10 20,4 75,0	36,90-35,00-33,80 21,6 81,5
Input power Heating capacity COP 11 SCOP 21 / 1,s,h Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		kW kW W/W	13,6 50,0 4,50 4,32/169,8% 19,62-18,64-17,96	14,8 56,5 4,30 4,33/170,3%	17,9 62,5 4,10	16,0 63,0 4,20	19,1 69,0 4,10	22,2 75,0 3,90	20,4 75,0	21,6 81,5
Heating capacity COP 11 SCOP 21 / 1,s,h Current Input power Starting current External static pressure Air flow Sound Pressure Sound Normal r Sound power Normal r Dimension HxWxD		kW W/W A kW	50,0 4,50 4,32/169,8% 19,62-18,64-17,96	56,5 4,30 4,33/170,3%	62,5 4,10	63,0 4,20	69,0 4,10	75,0 3,90	75,0	81,5
COP 11 SCOP 21 / N _{s,h} Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		W/W A kW	4,50 4,32/169,8% 19,62-18,64-17,96	4,30 4,33/170,3 %	4,10	4,20	4,10	3,90		
SCOP 21 / 1,s,h Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		A kW	4,32/169,8% 19,62-18,64-17,96	4,33/170,3%					4,40	4.40
Current Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		kW	19,62-18,64-17,96		4,29/168,8%	4 38 / 172 2%	/ O / / 4 PO PO/			4,40
Input power Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		kW		22,31-21,22-20,48		-100/ 17E/E/0	4,34/170,7%	4,33/170,2%	4,32/169,8%	4,31/169,5%
Starting current External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD			11 1		25,51-24,22-23,38	25,00-23,80-23,00	28,20-26,80-25,50	31,40-29,80-28,80	29,43-27,96-26,94	32,12-30,54-29,46
External static pressure Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD				12,9	15,0	14,7	16,7	18,8	16,7	18,5
Air flow Sound Normal r pressure Silent mo Sound power Normal r Dimension HxWxD		Α	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00
Sound Normal repressure Silent more Sound power Normal reduced by Dimension HxWxD	e (Max)	Pa	80	80	80	80	80	80	80	80
pressure Silent mo Sound power Normal r Dimension HxWxD		m³/min	418	418	418	418	418	418	627	627
Sound power Normal r Dimension HxWxD	mode (Cool / Heat)	dB(A)	60,0/60,0	62,0/62,0	65,0/67,5	63,0/63,0	65,5/68,0	67,0/70,0	62,0/62,0	63,0/63,0
Dimension HxWxD	node 1 / 2 (Cool)	dB(A)	57,0/55,0	59,0/57,0	62,0/60,0	60,0/58,0	62,5/60,5	64,0/62,0	59,0/57,0	60,0/58,0
	mode (Cool / Heat)	dB(A)	78,0/78,0	79,5/79,5	82,0/84,5	80,0/80,0	82,5/85,0	84,0/87,0	80,0/80,0	80,5/80,5
Net weight)	mm	1660×1760 (+60)×765	1660 x 1760 (+60) x 765	1660 x 1760 (+60) x 765	1660 x 1760 (+60) x 765	1660 x 1760 (+60) x 765	1660×1760 (+60)×765	1660 x 2640 (+120) x 765	1660 x 2640 (+120) x 765
		kg	406	406	409	406	409	412	609	609
Liquid		Inch (mm)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)
Piping diameter ^{3]} Gas		Inch (mm)	1-1/8(28,58)/ 1-3/8(34,96)	1-1/8 (28,58) / 1-3/8 (34,96)	1-1/8 (28,58) / 1-3/8 (34,96)	1-1/8(28,58)/ 1-3/8(34,96)	1-1/8(28,58)/ 1-3/8(34,96)	1-1/8(28,58)/ 1-3/8(34,96)	1-1/8 (28,58)/ 1-3/8 (34,96)	1-1/8(28,58)/ 1-3/8(34,96)
Balance	ì	Inch (mm)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)
Refrigerant (R32) / CO, E	Eq.	kg / T	12,6/8,51	12,7/8,57	14,8/9,99	12,8/8,64	14,9/10,06	17,0/11,48	18,9/12,76	19,0/12,83
Maximum allowable indo capacity ratio 41	loor / outdoor	%	50~130(200)	50~130(200)	50~130(200)	50~130(200)	50 ~ 130 (200)	50~130(200)	50~130(200)	50~130(200)
Operating Cool Min		°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
range Heat Min	n ~ Max	°C	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24

HP			28 HP	28 HP	30 HP	30 HP	32 HP	32 HP	32 HP	34 HP
			U-8MZ1E8	U-8MZ1E8	U-8MZ1E8	U-10MZ1E8	U-8MZ1E8	U-10MZ1E8	U-8MZ1E8	U-10MZ1E8
0			U-8MZ1E8	U-10MZ1E8	U-10MZ1E8	U-10MZ1E8	U-12MZ1E8	U-10MZ1E8	U-8MZ1E8	U-12MZ1E8
Outdoor unit			U-12MZ1E8	U-10MZ1E8	U-12MZ1E8	U-10MZ1E8	U-12MZ1E8	U-12MZ1E8	U-8MZ1E8	U-12MZ1E8
									U-8MZ1E8	
	Voltage	V	380 - 400 - 415	380 - 400 - 415	380-400-415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase	Three phase	Three phase	Three phase	Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50	50	50	50	50	50
Cooling capac	ity	kW	78,3	78,4	83,9	84,0	89,4	89,5	89,6	95,0
EER 1)		W/W	3,10	3,40	3,20	3,50	3,00	3,30	3,20	3,10
SEER 2) / n _{s,c}			7,23/286,3%	7,61/301,5%	7,45/295,1%	7,82/310,1%	7,26/287,4%	7,63/302,4%	7,24/286,8%	7,37/291,8%
Current		Α	41,70-39,60-38,20	38,70-36,70-35,50	43,50-41,30-39,90	40,50-38,40-37,20	48,30-45,90-44,30	45,30-43,00-41,60	46,80-44,40-42,80	50,10-47,60-46,00
Input power		kW	24,7	22,8	25,9	24,0	29,0	27,1	27,2	30,2
Heating capac	ity	kW	87,5	88,0	94,0	94,5	100,0	100,0	100,0	106,0
COP 11		W/W	4,20	4,30	4,20	4,20	4,10	4,10	4,50	4,00
SCOP 2) / N _{s,h}			4,34/170,9%	4,35/171,2%	4,33/170,4%	4,38/172,4%	4,31/169,6%	4,38/172,2%	4,32/169,8%	4,29/168,7%
Current		Α	35,32-33,54-32,36	34,81-33,12-31,98	38,01-36,12-34,88	37,50-35,70-34,50	41,21-39,12-37,78	40,70-38,70-37,40	39,24-37,28-35,92	43,90-41,70-40,30
Input power		kW	20,5	20,2	22,3	22,0	24,3	24,1	22,2	26,1
Starting curre	nt	Α	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00
External station	pressure (Max)	Pa	80	80	80	80	80	80	80	80
Air flow		m³/min	627	627	627	627	627	627	836	627
Sound	Normal mode (Cool / Heat)	dB(A)	65,5/68,0	64,0/64,0	66,0/68,5	65,0/65,0	67,5/70,5	66,5/68,5	63,0/63,0	68,0/70,5
pressure	Silent mode 1 / 2 (Cool)	dB(A)	62,5/60,5	61,0/59,0	63,0/61,0	62,0/60,0	64,5/62,5	63,5/61,5	60,0/58,0	65,0/63,0
Sound power	Normal mode (Cool / Heat)	dB(A)	83,0/85,0	81,5/81,5	83,5/85,5	82,0/82,0	84,5/87,5	83,5/85,5	81,0/81,0	85,0/87,5
Dimension	HxWxD	mm	1660×2640	1660 x 2640	1660 x 2640	1660 x 2640	1660 x 2640	1660 x 2640	1660 x 3520	1660 x 2640
	1121125		(+120) x 765	(+120) x 765	(+120) x 765	(+120) x 765	(+120) x 765	(+120) x 765	(+180) x 765	(+120) x 765
Net weight		kg	612	609	612	609	615	612	812	615
	Liquid	Inch (mm)	1/2 (12,70) / 5/8 (15,88)	1/2(12,70)/ 5/8(15,88)	5/8 (15,88) / 3/4 (19,05)	5/8 (15,88) / 3/4 (19,05)	5/8 (15,88) / 3/4 (19,05)	5/8 (15,88) / 3/4 (19,05)	5/8 (15,88) / 3/4 (19,05)	5/8 (15,88) / 3/4 (19,05)
Piping diameter ³⁾	Gas	Inch (mm)	1-1/8(28,58)/ 1-3/8(34,96)	1-1/8 (28,58)/ 1-3/8 (34,96)	1-3/8 (34,96)/ 15/8 (15,88)	1-3/8 (34,96)/ 15/8 (15,88)	1-3/8 (34,96) / 15/8 (15,88)	1-3/8(34,96)/ 15/8(15,88)	1-3/8 (34,96)/ 15/8 (15,88)	1-3/8(34,96)/ 15/8(15,88)
	Balance	Inch (mm)	1/4(6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)
Refrigerant (R		kg / T	21,1/14,24	19,1/12,89	21,2/14,31	19,2/12,96	23,3/15,73	21,3/14,38	25,2/17,01	23,4/15,80
	wable indoor / outdoor	%	50~130(200)	50~130(200)	50~130(200)	50~130(200)	50~130(200)	50~130(200)	50~130(200)	50~130(200)
Operating	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
range	Heat Min ~ Max	°C	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24	-25~+24

1) EER and COP calculation is based in accordance to EN 14511. 2) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency " η " values of the COMMISSION REGULATION (EU) 2016/2281, SEER, SCOP = $|\eta|$ + Correction) × PEF, 3) Piping diameter under 100 m for ultimate indoor unit / over 100 m for ultimate indoor unit (if the longest piping equivalent length exceeds 100 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes). 4) If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units, B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB (standard -25 °C WB), C. Simultaneous operation is limited to less than 130% of connectable indoor units, 4) SEER / SCOP and $\eta_{s,c}$ / $\eta_{s,h}$ are in accordance with ErP test data for U2 type 4 way 90x90 cassette indoor units.

40 HP

36 HP

38 HP

38 HP

40 HP

36 HP

34 HP

36 HP

HP

пг				30 NF						
			U-8MZ1E8	U-12MZ1E8	U-8MZ1E8	U-8MZ1E8	U-8MZ1E8	U-8MZ1E	8 U-8MZ1E8	U-10MZ1E8
			U-8MZ1E8	U-12MZ1E8	U-8MZ1E8	U-8MZ1E8	U-8MZ1E8	U-10MZ1E	8 U-8MZ1E8	U-10MZ1E8
Outdoor unit			U-8MZ1E8	U-12MZ1E8	U-10MZ1E8	U-8MZ1E8	U-10MZ1E8	B U-10MZ1E	8 U-12MZ1E8	U-10MZ1E8
			U-10MZ1E8		U-10MZ1E8	U-12MZ1E8	U-12MZ1E8			
	Voltage	V	380 - 400 - 415		380 - 400 - 415	380-400-415	380 - 400 - 41			
Power supply	Phase		Three phase		Three phase	Three phase	Three phase			
	Frequency	Hz	50	50	50	50	50	50	50	50
Cooling capaci	ity	kW	95,2	100,0	100,0	100,0	106,0	106,0	111,0	112,0
EER 11	•	W/W	3,30	3,00	3,30	3,10	3,20	3,40	3,10	3,50
SEER 2) / n _{s,c}		**, **							7,30/289,0%	
Current		Α								0 54,00-51,20-49,60
Input power		kW	28,4	33,3	29,6	31,5	32,7	30,8	35,8	32,0
Heating capac	ity	kW	106,0	112,0	113,0	112,0	119,0	119,0	125,0	126,0
COP 11	•	W/W	4,40	3,90	4,30	4,20	4,20	4,30	4,10	4,30
SCOP 2) / n _{s.h}		,			4,33/170,3%				% 4,29/168,8%	
					· · · · · · · · · · · · · · · · · · ·					
Current		Α								6 50,00-47,60-46,00
Input power		kW	24,0	28,2	25,8	26,1	27,8	27,6	29,9	29,3
Starting curre	nt	Α	1,00	1,00	1,00	1,00	1,00	1,00	1,00	1,00
External static	pressure (Max)	Pa	80	80	80	80	80	80	80	80
Air flow	F	m³/min	836	627	836	836	836	836	836	836
Sound	Normal mode (Cool / Heat)	dB(A)	64,0/64,0	69,0/72,0	65,0/65,0	66,0/68,5	66,5/68,5			66,0/66,0
pressure	Silent mode 1 / 2 (Cool)	dB(A)	61,0/59,0	66,0/64,0	62,0/60,0	63,0/61,0	63,5/61,5	62,5/60,5	65,0/63,0	63,0/61,0
Sound power	Normal mode (Cool / Heat)	dB(A)	82,0/82,0	86,0/89,0	82,5/82,5	83,5/85,5	84,0/86,0	83,0/83,0		83,0/83,0
		•	1660 x 3520	1660 x 2640	1660 x 3520	1660 x 3520	1660 x 3520			1660 x 3520
Dimension	HxWxD	mm	(+180) x 765	(+120) x 765	(+180) x 765	(+180) x 765	(+180) x 765			(+180) x 765
No. of the contract of the con										
Net weight		kg	812	618	812	815	815	812	818	812
	Liquid	Inch (m)	5/8(15,88)/	5/8(15,88)/	5/8(15,88)/	5/8(15,88)/	5/8 (15,88)/	/ 5/8 (15,88)	/ 5/8(15,88)/	5/8(15,88)/
	Liquid	Inch (mm)	3/4 (19,05)	3/4(19,05)	3/4(19,05)	3/4 (19,05)	3/4 (19,05)			3/4(19,05)
Piping	-		1-3/8 (34,96)/		1-3/8 (34,96)/	1-3/8 (34,96)/	1-3/8 (34,96)			
diameter ³⁾	Gas	Inch (mm)					15/8 (15,88)			
			15/8 (15,88)	15/8 (15,88)	15/8 (15,88)	15/8 (15,88)				15/8 (15,88)
	Balance	Inch (mm)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)
Refrigerant (R	32) / CO ₂ Eq.	kg / T	25,3/17,08	25,5/17,21	25,4/17,15	27,4/18,50	27,5/18,56	25,5/17,2	1 29,6/19,98	25,6/17,28
	wable indoor / outdoor									
capacity ratio		%	50~130(200)	50~130(200)	50 ~ 130 (200)	50~130(200)	50~130(200	0) 50~130(20	10) 50~130(200) 50~130(200)
Operating	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
range	Heat Min ~ Max	°C	-25~+24	-25~+24	-25~+24	-25 ~ +24	-25~+24	-25~+24	-25~+24	-25~+24
HP			40 HP	42 HP	42 H	P 44	HP	44 HP	46 HP	48 HP
			II-8M71F8	II-8M71F8	II-10M7	1F8 II-8M	171F8 II	-10M71F8	II_10M71F8	II-12M71F8
			U-8MZ1E8	U-8MZ1E8	U-10MZ			-10MZ1E8	U-10MZ1E8	U-12MZ1E8
Outdoor unit			U-10MZ1E8	U-10MZ1E8	U-10MZ	1E8 U-12N	MZ1E8 U	-10MZ1E8	U-12MZ1E8	U-12MZ1E8
Outdoor unit			U-10MZ1E8 U-10MZ1E8	U-10MZ1E8 U-12MZ1E8	U-10MZ U-10MZ	1E8 U-12N	MZ1E8 U MZ1E8 U	-10MZ1E8 -12MZ1E8	U-12MZ1E8 U-12MZ1E8	U-12MZ1E8 U-12MZ1E8
Outdoor unit			U-10MZ1E8	U-10MZ1E8	U-10MZ U-10MZ	1E8 U-12N	MZ1E8 U MZ1E8 U	-10MZ1E8	U-12MZ1E8	U-12MZ1E8
Outdoor unit	Voltage	V	U-10MZ1E8 U-10MZ1E8	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8	U-10MZ U-10MZ U-12MZ	1E8 U-12N 1E8 U-12N 1E8 U-12N	MZ1E8 U MZ1E8 U MZ1E8 U	-10MZ1E8 -12MZ1E8	U-12MZ1E8 U-12MZ1E8	U-12MZ1E8 U-12MZ1E8
		V	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 41	U-10MZ U-10MZ U-12MZ 380-400	11E8 U-12N 11E8 U-12N 11E8 U-12N -415 380-4	MZ1E8 U MZ1E8 U MZ1E8 U 00-415 38	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 - 400 - 415	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415
Outdoor unit Power supply	Phase		U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase	U-10MZ U-10MZ U-10MZ U-12MZ 380-400 Three pl	11E8 U-12N 11E8 U-12N 11E8 U-12N -415 380-40 hase Three	MZ1E8 U MZ1E8 U MZ1E8 U 00-415 38 phase Th	I-10MZ1E8 I-12MZ1E8 I-12MZ1E8 I0-400-415 hree phase	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase
Power supply	Phase Frequency	Hz	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-41 Three phase 50	U-10MZ U-10MZ U-10MZ U-12MZ 380 - 400 Three pl	11E8 U-12N 11E8 U-12N 11E8 U-12N -415 380-4 hase Three	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Th	I-10MZ1E8 I-12MZ1E8 I-12MZ1E8 I0 - 400 - 415 hree phase 50	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50
Power supply Cooling capaci	Phase Frequency	Hz kW	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 111,0	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0	U-10MZ U-10MZ U-12MZ S 380 - 400 Three pl 50 117,(11E8 U-12P 11E8 U-12P 11E8 U-12P -415 380-4P hase Three 50 12	MZ1E8 U MZ1E8 U MZ1E8 U 00-415 38 phase Th 50 2,0	I-10MZ1E8 I-12MZ1E8 I-12MZ1E8 I0-400-415 hree phase 50 123,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0
Power supply	Phase Frequency	Hz	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-41 Three phase 50	U-10MZ U-10MZ U-10MZ U-12MZ 380 - 400 Three pl	11E8 U-12P 11E8 U-12P 11E8 U-12P -415 380-4P hase Three 50 12	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Th	I-10MZ1E8 I-12MZ1E8 I-12MZ1E8 I0 - 400 - 415 hree phase 50	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50
Power supply Cooling capaci	Phase Frequency	Hz kW	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 111,0	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0	U-10MZ U-10MZ U-12MZ S 380-400 Three pl 50 117,0 3,30	11E8 U-12I 11E8 U-12I 11E8 U-12I -415 380-4I hase Three 5 0 12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00-415 38 phase TH 60 2,0 00	I-10MZ1E8 I-12MZ1E8 I-12MZ1E8 I0-400-415 hree phase 50 123,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 134,0
Power supply Cooling capaci EER 11 SEER 21 / n _{s,c}	Phase Frequency	Hz kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53/298,2%	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49	U-10MZ U-10MZ U-12MZ S 380-400 Three pl 50 117,(3,30 6 7,65/30	11E8 U-12I 11E8 U-12I 11E8 U-12I -415 380-4I hase Three 50 12 1 3,	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase TI 00 2,0 00 288,5% 7,1	1-10MZ1E8 1-12MZ1E8 1-12MZ1E8 10-400-415 hree phase 50 123,0 3,20 56/299,4%	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7%	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1%
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current	Phase Frequency	Hz kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53/298,2% 57,00-54,10-52,3	U-10MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,4% 0 61,80-58,70-56	U-10MZ U-10MZ U-12MZ S 380 - 400 C Three pl 50 117, 3,30 7,65/30; 70 58,80-55,80	11E8 U-12I 11E8 U-12I 11E8 U-12I -415 380-4I hase Three 50 12 1 3, 3,2% 7,28/2 0-54,00 66,60-63	MZ1E8 U MZ1E8 U MZ1E8 U 00-415 38 phase TH 60 22,0 00 288,5% 7,4 30-61,10 63,6	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20
Power supply Cooling capaci EER 11 SEER 21 / n _{s,c} Current Input power	Phase Frequency ity	Hz kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0	U-10MZ U-10MZ U-10MZ U-12MZ U-	11E8 U-12N 11E8 U-12N 11E8 U-12N -415 380-44 hase Three 50 12 1 3, 3,2% 7,28/2 0-54,00 66,60-63	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase The control of the c	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4
Power supply Cooling capaci EER ¹¹ SEER ²¹ / 1, c. Current Input power Heating capac	Phase Frequency ity	Hz kW W/W A kW	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0	U-10MZ U-10MZ U-10MZ U-12MZ U-	11E8 U-12N 11E8 U-12N 11E8 U-12N -415 380-44 hase Three 5 0 12 1 3, 3,2% 7,28/ 0 13	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 60 2,0 00 288,5% 7,1 ,30 - 61,10 63,6 0,1 7,0	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0
Power supply Cooling capaci EER 11 SEER 21 / n _{s,c} Current Input power	Phase Frequency ity	Hz kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0	U-10MZ U-10MZ U-10MZ S 380 - 400 Three pl 50 117,(3,30 6 7,65/30: 70 58,80 - 55,86 35,1 132,4	11E8 U-12N 11E8 U-12N 11E8 U-12N -415 380-40 hase Three 5 0 12 1 3, 3,2% 7,28/2 0 54,60-63 0 13 0 13	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase The control of the c	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 58,40-65,00-62,80 41,3 144,0 4,00	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4
Power supply Cooling capaci EER ¹¹ SEER ²¹ / 1, c. Current Input power Heating capac	Phase Frequency ity	Hz kW W/W A kW	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0	U-10MZ U-10MZ U-10MZ S 380 - 400 Three pl 50 117, 3,30 6 7,65/30 70 58,80 - 55,80 35,1 132,4	11E8 U-12N 11E8 U-12N 11E8 U-12N -415 380-40 hase Three 5 0 12 3 3,2% 7,28/3 0-54,00 66,60-63 40 0 13	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 60 2,0 00 288,5% 7,1 3,30 - 61,10 63,6 0,1 7,0 00	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h}	Phase Frequency ity	Hz kW W/W A kW kW	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53 / 298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34 / 170,6%	U-10MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56, 37,0 131,0 4,10 4,35/171,09	U-10MZ U-10MZ U-10MZ U-12MZ U-	11E8 U-12N 11E8 U-12N 11E8 U-12N 11E8 U-12N 11E8 U-12N 11E8 U-12N 11E8 U-12N 11E8 U-12N 11E8 U-12N 12E8 U	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 00 2,0 00 288,5% 7,1 3,30 - 61,10 63,6 0,1 7,0 00 4,7	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7%	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 58,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2%	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3%
Power supply Cooling capaci EER ¹⁾ SEER ²⁾ / $\eta_{s,c}$ Current Input power Heating capac COP ¹⁾ SCOP ²⁾ / $\eta_{s,h}$ Current	Phase Frequency ity	Hz kW W/W A A kW kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53 / 298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51 - 48,02 - 46,3	U-10MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49	U-10MZ U-10MZ U-12MZ 5 380 - 400 e Three pl 50 117,(3,30 6 7,65/30: 70 58,80-55,80 35,1 132,(4,20 6 4,36/17 28 53,20-50,60	11E8 U-12N 11ER U-12N	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 00 2,0 00 288,5% 7,1 30 - 61,10 63,6 0,1 7,0 00 170,3% 4,1 0,02 - 52,18 56,4	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 58,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 59,60-56,60-54,70	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60
Power supply Cooling capaci EER ¹⁾ SEER ²⁾ / \(\eta_{s,c}\) Current Input power Heating capac COP ¹⁾ SCOP ²⁾ / \(\eta_{s,h}\) Current Input power	Phase Frequency ity	Hz kW W/W A kW kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53 / 298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51-48,02-46,3 29,6	U-10MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-59 131,0 4,10 4,35/171,09 8 53,71-51,02-49	U-10MZ U-10MZ U-10MZ S 380 - 400 D Three pl S 50 117,(3,30 6 7,65/30: 770 58,80-55,80 4,20 6 4,36/17 28 53,20-50,60 31,4	11E8 U-12N 11ER U-12N	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase TI 00 2,0 00 288,5% 7,1 30 - 61,10 63,6 0,1 7,0 00 170,3% 4,1 ,02 - 52,18 56,4	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 & 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 & 33,4	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting current	Phase Frequency ity ity	Hz kW W/W A kW kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00	U-10MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49 31,7 1,00	U-10MZ U-10MZ U-12MZ 5 380 - 400 e Three pl 50 117,(3,30 6 7,65/30: 70 58,80-55,80 35,1 132,(4,20 6 4,36/17 28 53,20-50,60	11E8 U-12N 11ER U-12N	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 00 2,0 00 288,5% 7,1 30 - 61,10 63,6 0,1 7,0 00 170,3% 4,1 0,02 - 52,18 56,4	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 3,20 -60,40-58,40 6,38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5,33,4 1,00	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 58,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 59,60-56,60-54,70	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting current	Phase Frequency ity	Hz kW W/W A kW kW W/W	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53 / 298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51-48,02-46,3 29,6	U-10MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-59 131,0 4,10 4,35/171,09 8 53,71-51,02-49	U-10MZ U-10MZ U-10MZ S 380 - 400 D Three pl S 50 117,(3,30 6 7,65/30: 770 58,80-55,80 4,20 6 4,36/17 28 53,20-50,60 31,4	11E8 U-12N 11ER U-12N	MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase TI 00 2,0 00 288,5% 7,1 30 - 61,10 63,6 0,1 7,0 00 170,3% 4,1 ,02 - 52,18 56,4	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 & 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 & 33,4	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²² / ¶ _{s,h} Current Input power Starting current External static	Phase Frequency ity ity	Hz kW W/W A kW A Pa	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49 31,7 1,00 80	U-10MZ U-10MZ U-10MZ S 380 - 400 D Three pl S 50 117,(3,30 6 7,65/30: 7,0 58,80-55,80 35,1 132,(4,20 4,20 4,20 5,30 31,4 1,00 80	11E8 U-12I 11E8 U-12I -415 380 - 44 hase Three 50 12 0-54,00 66,60 - 63 -4, 1,6% 4,33 / 1,0 - 48,90 56,91 - 54 -33	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Th 00 - 22,0 00 288,5% 7, ,30 - 61,10 63,6 0,1 7,0 00 1710,3% 4, ,02 - 52,18 56,4 3,7 00 00	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 -53,60-51,80 5 33,4 1,00 80	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 59,60 - 56,60 - 54,70 35,5 1,00 80	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80
Power supply Cooling capaci EER ¹¹ SEER ²³ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²³ / ¶ _{s,h} Current Input power Starting current External static Air flow	Phase Frequency ity ity nt pressure (Max)	Hz kW W/W A kW kW W/W A kW A Pa m³/min	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-9 8 10,00 80 836	U-10MZ U-10MZ U-10MZ U-12MZ U-	11E8 U-12N 11ER U-12N	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Theorem	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836	U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 59,60-56,60-54,70 35,5 1,00 80 836	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836
Power supply Cooling capaci EER ¹⁾ SEER ²⁾ / $\eta_{s,c}$ Current Input power Heating capac COP ¹⁾ SCOP ²⁾ / $\eta_{s,h}$ Current Input power Starting currei External static Air flow Sound	Phase Frequency ity ity ity nt pressure (Max) Normal mode (Cool / Heat)	Hz kW W/W A kW W/W A kW A Pa m³/min dB(A)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34/170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0/69,0	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0	U-10MZ U-10MZ U-10MZ U-12MZ U-	11E8 U-12N 11EN U-12N	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 60 22,0 00 288,5% 7, ,30 - 61,10 63,6 0,1 77,0 00 170,3% 4, ,02 - 52,18 56,4 38,7 00 60 60 60 60 60 60 60 60 60 60 60 60	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0	U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting currel External static Air flow Sound pressure	Phase Frequency ity ity ity Int Pressure (Max) Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool)	Hz kW W/W A kW W/W A KW A Pa m³/min dB(A) dB(A)	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34/170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5	U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8	-10MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 4,10 34/170,7% 0-53,60-51,80 83,6 68,5/71,0 65,5/63,5	U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting curret External static Air flow Sound	Phase Frequency ity ity ity nt pressure (Max) Normal mode (Cool / Heat)	Hz kW W/W A kW W/W A kW A Pa m³/min dB(A)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0	U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8	-10MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0
Power supply Cooling capaci EER ¹¹ SEER ²³ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²³ / ¶ _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power	Phase Frequency ity ity ity Normal mode [Cool / Heat] Silent mode 1 / 2 [Cool] Normal mode (Cool / Heat)	Hz kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A)	U-10MZ1E8 U-10MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34/170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5	U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8	-10MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 4,10 34/170,7% 0-53,60-51,80 83,6 68,5/71,0 65,5/63,5	U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting currei External static Air flow Sound pressure	Phase Frequency ity ity ity Int Pressure (Max) Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool)	Hz kW W/W A kW W/W A KW A Pa m³/min dB(A) dB(A)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0	U-10MZ U-10MZ U-10MZ S 380 - 400 Three pl 50 117,(3,30 6 7,65/30: 70 58,80 - 55,86 35,1 132,(4,20 6 4,36/17 ,28 53,20 - 50,66 31,4 1,00 80 80 836 67,5/6 64,5/6 84,5/8	1188 U-12 1288 U-12 1418 U-12 -415 380 - 4 hase Three 5 0	MZ1E8 U MZ1E8	-10MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0
Power supply Cooling capaci EER ¹¹ SEER ²¹ / \(\begin{align*}\end{align*}\) SCOP ²¹ / \(\begin{align*}\end{align*}\) SCOP ²¹ / \(\begin{align*}\end{align*}\) SCOP ²¹ / \(\begin{align*}\end{align*}\) Score to the second stating current stating	Phase Frequency ity ity ity Normal mode [Cool / Heat] Silent mode 1 / 2 [Cool] Normal mode (Cool / Heat)	Hz kW W/W A kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) mm	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53 / 298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0 / 69,0 64,0 / 62,0 84,5 / 86,0 1660 x 3520 [+180] x 765	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765	U-10MZ U-10MZ U-10MZ S 380 - 400 Three pl 50 117,(3,30 6 7,65/30: 70 58,80 - 55,86 35,1 132,(4,20 6 4,36/17 ,28 53,20 - 50,66 31,4 1,00 80 836 67,5/6 64,5/6 84,5/8 1660 x 3 1,160 x 3 1,170 x 3 1	1188 U-12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 00 2,0 00 288,5% 7,1 3,30 - 61,10 63,6 0,1 77,0 00 170,3% 4,3 0,02 - 52,18 56,4 3,7 00 80 80 80 80 80 80 80 87 87 89 80 80 80 80 80 80 80 80 80 80 80 80 80	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0 -60,40 -58,40 6 38,2 138,0 4,10 34/170,7% 0 -53,60 -51,80 5 33,4 1,00 80 836 668,5/71,0 65,5/63,5 85,5/88,0 660 x 3520 +180) x 765	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 58,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 59,60 - 56,60 - 54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 [+180] x 765	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660×3520 [+180] × 765
Power supply Cooling capaci EER ¹¹ SEER ²³ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²³ / ¶ _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power	Phase Frequency ity ity ity Normal mode [Cool / Heat] Silent mode 1 / 2 [Cool] Normal mode (Cool / Heat)	Hz kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53 / 298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0 / 69,0 64,0 / 62,0 84,5 / 86,0 1660 x 3520 (+180) x 765 815	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56, 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49, 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765	U-10MZ U-10MZ U-10MZ S 380 - 400 E Three pl 50 117,(3,30 6 7,65/30: 35,1 132,(4,20 6 4,36/17 28 53,20-50,66 31,4 1,00 80 836 67,5/6 64,5/6 84,5/8 1660x3 (+180)x 815	1188 U-12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase TI 00 2,0 00 288,5% 7,1 3,30 - 61,10 63,6 0,1 77,0 00 170,3% 4,3 0,02 - 52,18 56,4 3,7 00 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60 60	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0 -60,40 -58,40 6 38,2 138,0 4,10 34/170,7% 0 -53,60 -51,80 5 33,4 1,00 80 836 668,5/71,0 65,5/63,5 85,5/88,0 660 x 3520 +180) x 765 818	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 58,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 59,60 - 56,60 - 54,70 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 [+180] x 765	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 [+180] x 765
Power supply Cooling capaci EER ¹¹ SEER ²¹ / \(\begin{align*}\end{align*}\) \(\text{SEER} \) \(\text{Pi}_{s,c} \) Current Input power Heating capac COP ¹¹ SCOP ²¹ / \(\beta_{s,h} \) Current Input power Starting current External static Air flow Sound pressure Sound power Dimension	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD	Hz kW W/W A kW kW A A Pa m³/min dB(A) dB(A) mm kg	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53 / 298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0 / 69,0 64,0 / 62,0 84,5 / 86,0 1660 x 3520 (+180) x 765 815 5/8 (15,88) /	U-10MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8(15,88)/	U-10MZ U-10MZ U-10MZ S 380 - 400 E Three pl 50 117,(3,30 6 7,65/30: 70 58,80-55,8(35,1 132,(4,20 6 4,36/17 28 53,20-50,6(31,4 1,00 80 836 67,5/6 64,5/6 84,5/8 1660x3 [+180]x 815 5/8[15,4	1188 U-12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00-415 38 phase Theorem	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 3,20 -60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 665,7/1,0 65,5/63,5 85,5/88,0 660 x 3520 +180) x 765 818	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 58,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 59,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660×3520 [+180)×765 821 5/8(15,88)/	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 4,4,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 [+180] x 765 824 5/8[15,88]/
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting currel External static Air flow Sound pressure Sound power Dimension Net weight	Phase Frequency ity ity ity Normal mode [Cool / Heat] Silent mode 1 / 2 [Cool] Normal mode (Cool / Heat)	Hz kW W/W A kW W/W A R kW A Pa M³/min dB(A) dB(A) mm	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53 / 298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0 / 69,0 64,0 / 62,0 84,5 / 86,0 1660 x 3520 (+180) x 765 815	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56, 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49, 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765	U-10MZ U-10MZ U-10MZ S 380 - 400 E Three pl 50 117,(3,30 6 7,65/30: 35,1 132,(4,20 6 4,36/17 28 53,20-50,66 31,4 1,00 80 836 67,5/6 64,5/6 84,5/8 1660x3 (+180)x 815	1188 U-12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase Ti 00 2,0 00 288,5% 7,1 330 - 61,10 63,6 0,1 7,0 00 170,3% 4,1 0,02 - 52,18 56,4 3,7 00 60 36 7/72,0 60 60 36 7/72,0 60 60 37 64,0 66 67 689,0 88 ×3520 1 1)×765 [- 21 5,88] / 5	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0 -60,40 -58,40 6 38,2 138,0 4,10 34/170,7% 0 -53,60 -51,80 5 33,4 1,00 80 836 668,5/71,0 65,5/63,5 85,5/88,0 660 x 3520 +180) x 765 818	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 58,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 59,60 - 56,60 - 54,70 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 [+180] x 765	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 [+180] x 765
Power supply Cooling capaci EER ¹¹ SEER ²¹ / n _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / n _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power Dimension Net weight	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD	Hz kW W/W A A kW A Pa dB(A) dB(A) mm kg Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53 / 298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34 / 170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0 / 69,0 64,0 / 62,0 84,5 / 86,0 1660 x 3520 (+180) x 765 815 5/8 (15,88) /	U-10MZ1E8 U-12MZ1E8 380-400-41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8(15,88)/	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00-415 38 phase Theorem of the control of	-10MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 3,20 -60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 665,7/1,0 65,5/63,5 85,5/88,0 660 x 3520 +180) x 765 818	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380-400-415 Three phase 50 128,0 3,00 7,41/293,7% 58,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 59,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660×3520 [+180)×765 821 5/8(15,88)/	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 4,4,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 [+180] x 765 824 5/8[15,88]/
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting currel External static Air flow Sound pressure Sound power Dimension Net weight	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD	Hz kW W/W A kW kW A A Pa m³/min dB(A) dB(A) mm kg	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660x3520 (+180)x765 815 5/8(15,88)/3/4(19,05) 1-3/8(34,96)/	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,02 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3500 [+180 x 750 818 5/8 [15,88]/ 3/4 [19,05] 1-3/8 [34,96]	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	### 1-12h ### 1-	MZ1E8 U MZ1E8 MZ MZ MZ1E8 MZ M	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 334/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/68,5 85,5/88,0 660 x3520 +180) x765 818 1/8(15,88)/3/4(19,05) 3/8(34,96)/	U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 69,60 - 56,60 - 54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8[15,88]/ 3/4[19,05] 1-3/8[34,96]/	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660×3520 [+180] x 765 824 5/8 [15,88] / 3/4 (19,05) 1-3/8 [34,96]/
Power supply Cooling capaci EER ¹¹ SEER ²¹ / n _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / n _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power Dimension Net weight	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD Liquid Gas	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53/298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34/170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 (+180) x 765 815 5/8(15,88)/3/4(19,05) 1-3/8(34,96)/15/8(15,88)	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,00 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8 (15,88)/ 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88)	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	### Page 18	MZ1E8 U MZ1E8 MZ MZ MZ1E8 MZ MZ MZ1E8 MZ M	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 660×3520 +180)×765 818 818 1/8(15,88)/3/4(19,05) 3/8(34,96)/5/8(15,88)	U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8 [15,88]/ 3/4 [19,05] 1-3/8 [34,96]/ 15/8 [15,88]	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660x3520 (+180)x765 824 5/8(15,88)/ 3/4(19,05) 1-3/8(34,96)/ 15/8(15,88)
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting currei External static Air flow Sound pressure Sound power Dimension Net weight Piping diameter ³¹	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) Liquid Gas Balance	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) mm kg Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34/170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 (+180) x 765 815 5/8 [15,88]/3/4 [19,05] 1-3/8 [34,96]/15/8 [15,88] 1/4 [6,35]	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8 (15,88)/ 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88) 1/4 (6,35)	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8 MZ MZ MZ1E8 MZ M	-10MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 33/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 668,5/71,0 65,5/63,5 85,5/88,0 660×3520 +180)×765 818 818 818 3/4(19,05) 3/8(15,88)/ 3/4(19,05) 3/8(34,96)/ 5/8(15,88) 1/4(6,35)	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8(15,88)/ 3/4(19,05) 1-3/8(34,96)/ 15/8(15,88) 1/4(6,35)	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660x3520 [+180] x765 824 5/8[15,88] 1/4[6,35]
Power supply Cooling capaci EER ¹¹ SEER ²¹ / n _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / n _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power Dimension Net weight	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) Liquid Gas Balance	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53/298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34/170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 (+180) x 765 815 5/8(15,88)/3/4(19,05) 1-3/8(34,96)/15/8(15,88)	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,00 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8 (15,88)/ 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88)	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8 MZ MZ MZ1E8 MZ M	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 660×3520 +180)×765 818 818 1/8(15,88)/3/4(19,05) 3/8(34,96)/5/8(15,88)	U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8 [15,88]/ 3/4 [19,05] 1-3/8 [34,96]/ 15/8 [15,88]	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660x3520 (+180)x765 824 5/8(15,88)/ 3/4(19,05) 1-3/8(34,96)/ 15/8(15,88)
Power supply Cooling capaci EER ¹¹ SEER ²¹ / ¶ _{s,c} Current Input power Heating capac COP ¹¹ SCOP ²¹ / ¶ _{s,h} Current Input power Starting currei External static Air flow Sound pressure Sound power Dimension Net weight Piping diameter ³¹ Refrigerant (R	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) Liquid Gas Balance	Hz kW W/W A kW kW W/W A kW A Pa m²/min dB(A) dB(A) dB(A) Inch (mm) Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 (+180) x 765 815 5/8 (15,88)/3/4 (19,05) 1-3/8 (34,96)/15/8 (15,88) 1/4 (6,35) 27,6/18,63	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,00 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/83,0 1660 x35,0 1660 x35,0 1660 x35,0 1660 x36,0 17,0 818 5/8 (15,88) 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88) 1/4 (6,35) 29,7/20,05	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase TI 60 - 62,0 00	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 556/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 660 x3520 +1801 x765 818 //8(15,88)/3/4(19,05) 3/8(34,96)/5/8(15,88) 1/4(6,35) 29,8/20,12	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 59,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 350,0 (+180) x 765 821 5/8(15,88)/3/4(19,05) 1-3/8(34,96)/15/8(15,88) 1/4(6,35) 31,9/21,53	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 (+180) x 765 824 5/8(15,88)/3/4(19,05) 1-3/8(34,96)/15/8(15,88) 1/4(6,35) 34,0/22,95
Power supply Cooling capaci EER ¹⁾ SEER ²⁾ / ¶ _{s,c} Current Input power Heating capac COP ¹⁾ SCOP ²⁾ / ¶ _{s,h} Current Input power Starting currei External static Air flow Sound pressure Sound power Dimension Net weight Piping diameter ³⁾ Refrigerant (R	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD Liquid Gas Balance 32) / CO, Eq. wable indoor / outdoor	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) mm kg Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00 - 54,10 - 52,3 33,9 125,0 4,20 4,34/170,6% 50,51 - 48,02 - 46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 (+180) x 765 815 5/8 [15,88]/3/4 [19,05] 1-3/8 [34,96]/15/8 [15,88] 1/4 [6,35]	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80-58,70-56 37,0 131,0 4,10 4,35/171,09 8 53,71-51,02-49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8 (15,88)/ 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88) 1/4 (6,35)	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U MZ1E8 U 00 - 415 38 phase TI 60 - 62,0 00	-10MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 33/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 668,5/71,0 65,5/63,5 85,5/88,0 660×3520 +180)×765 818 818 818 3/4(19,05) 3/8(15,88)/ 3/4(19,05) 3/8(34,96)/ 5/8(15,88) 1/4(6,35)	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 68,40-65,00-62,80 41,3 144,0 4,00 4,35/171,2% 69,60-56,60-54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8(15,88)/ 3/4(19,05) 1-3/8(34,96)/ 15/8(15,88) 1/4(6,35)	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20-69,60-67,20 44,4 150,0 4,00 4,33/170,3% 62,80-59,60-57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660x3520 [+180] x765 824 5/8[15,88] 1/4[6,35]
Power supply Cooling capaci EER 11 SEER 21 / n _{s,c} Current Input power Heating capac COP 11 SCOP 21 / n _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power Dimension Net weight Piping diameter 31 Refrigerant (R Maximum allo capacity ratio 6	Phase Frequency ity ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD Liquid Gas Balance 32) / CO, Eq. wable indoor / outdoor	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) mm kg Inch (mm) Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 [+180] x 765 815 5/8 [15,88]/3/4 [19,05] 1-3/8 [34,96]/15/8 [15,88] 1/4 [6,35] 27,6/18,63 50~130 [200]	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8 (15,88)/ 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88) 1/4 (6,35) 29,7/20,05 50 ~ 130 (200	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12	MZ1E8 U MZ	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 660 x3520 +180) x765 818 //8(15,88)/ 3/4(19,05) 3/8(34,96)/ 5/8(15,88) 1/4(6,35) 1/4(6,35) 1/9,8/20,12 0-130(200)	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 38,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 59,60 - 56,60 - 54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8 [15,88] 1/4 [6,35] 31,9/21,53 50 ~ 130 [200]	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20 - 69,60 - 67,20 44,4 150,0 4,00 4,33/170,3% 62,80 - 59,60 - 57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 [+180] x 765 824 5/8[15,88] 3/4(19,05] 1-3/8[34,96]/ 15/8[15,88] 1/4[6,35] 34,0/22,95 50 ~ 130(200)
Power supply Cooling capaciters 11 SEER 21 / N _{s,c} Current Input power Heating capac COP 11 SCOP 21 / N _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power Dimension Net weight Piping diameter 31 Refrigerant (R Maximum allo capacity ratio 4 Operating	Phase Frequency ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD Liquid Gas Balance 32) / CO, Eq. wable indoor / outdoor	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) Inch (mm) kg Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 [+180] x 765 815 5/8[15,88]/3/4[19,05] 1-3/8[34,96]/15/8[15,88] 1/4[6,35] 27,6/18,63 50 ~ 130 (200) -10 ~ +52	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8 (15,88) 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88) 14 (6,35) 29,7/20,05 50 ~ 130 (200 -10 ~ +52	U-10MZ U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-12MZ U-12MZ U-10MZ U-12MZ U-10MZ U-12MZ U-10MZ U-	1188 U-12 1288 U-12 -415 380 - 4 hase	MZ1E8 U MZ	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 -0 -400 - 415 hree phase 50 123,0 3,20 56/299,4% 0 -60,40 -58,40 6 38,2 138,0 4,10 34/170,7% 0 -53,60 -51,80 5 33,4 1,00 80 836 668,5/71,0 65,5/63,5 85,5/88,0 660 x 3520 +180) x 765 818 y/8(15,88)/ 3/4(19,05) 3/8(34,96)/ 5/8(15,88) 1/4(6,35) 1/4(6,35) 1/29,8/20,12 0 ~130(200) -10 ~+52	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 58,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 59,60 - 56,60 - 54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8 [15,88]/ 3/4 [19,05] 1 - 3/8 [34,96]/ 15/8 [15,88]/ 31,9/21,53 50 ~ 130 (200) - 10 ~ +52	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20 - 69,60 - 67,20 44,4 150,0 4,00 4,33/170,3% 62,80 - 59,60 - 57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 [+180] x 765 824 5/8 [15,88]/3/4 (19,05] 1-3/8 [34,96]/15/8 [15,88] 1/4 [6,35] 34,0/22,95 50 - 130 [200] -10 ~ +52
Power supply Cooling capaci EER 11 SEER 21 / n _{s,c} Current Input power Heating capac COP 11 SCOP 21 / n _{s,h} Current Input power Starting current External static Air flow Sound pressure Sound power Dimension Net weight Piping diameter 31 Refrigerant (R Maximum allo capacity ratio 6	Phase Frequency ity ity ity ity Normal mode (Cool / Heat) Silent mode 1 / 2 (Cool) Normal mode (Cool / Heat) HxWxD Liquid Gas Balance 32) / CO, Eq. wable indoor / outdoor	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) dB(A) mm kg Inch (mm) Inch (mm)	U-10MZ1E8 U-10MZ1E8 U-10MZ1E8 380 - 400 - 415 Three phase 50 1111,0 3,20 7,53/298,2% 57,00-54,10-52,3 33,9 125,0 4,20 4,34/170,6% 50,51-48,02-46,3 29,6 1,00 80 836 67,0/69,0 64,0/62,0 84,5/86,0 1660 x 3520 [+180] x 765 815 5/8 [15,88]/3/4 [19,05] 1-3/8 [34,96]/15/8 [15,88] 1/4 [6,35] 27,6/18,63 50~130 [200]	U-10MZ1E8 U-12MZ1E8 380 - 400 - 41 Three phase 50 117,0 3,10 7,43/294,49 0 61,80 - 58,70 - 56 37,0 131,0 4,10 4,35/171,09 8 53,71 - 51,02 - 49 31,7 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 1660 x 3520 (+180) x 765 818 5/8 (15,88)/ 3/4 (19,05) 1-3/8 (34,96) 15/8 (15,88) 1/4 (6,35) 29,7/20,05 50 ~ 130 (200	U-10MZ U-10MZ U-10MZ U-10MZ U-12MZ U-	1188 U-12 1288 U-12 -415 380 - 4 hase	MZ1E8 U MZ	-10MZ1E8 -12MZ1E8 -12MZ1E8 -12MZ1E8 0-400-415 hree phase 50 123,0 3,20 56/299,4% 0-60,40-58,40 6 38,2 138,0 4,10 34/170,7% 0-53,60-51,80 5 33,4 1,00 80 836 68,5/71,0 65,5/63,5 85,5/88,0 660 x3520 +180) x765 818 //8(15,88)/ 3/4(19,05) 3/8(34,96)/ 5/8(15,88) 1/4(6,35) 1/4(6,35) 1/9,8/20,12 0-130(200)	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 128,0 3,00 7,41/293,7% 38,40 - 65,00 - 62,80 41,3 144,0 4,00 4,35/171,2% 59,60 - 56,60 - 54,70 35,5 1,00 80 836 69,5/72,0 66,5/64,5 86,5/89,0 1660 x 3520 (+180) x 765 821 5/8 [15,88] 1/4 [6,35] 31,9/21,53 50 ~ 130 [200]	U-12MZ1E8 U-12MZ1E8 U-12MZ1E8 380 - 400 - 415 Three phase 50 134,0 3,00 7,37/292,1% 73,20 - 69,60 - 67,20 44,4 150,0 4,00 4,33/170,3% 62,80 - 59,60 - 57,60 37,5 1,00 80 836 70,0/73,0 67,0/65,0 87,0/90,0 1660 x 3520 [+180] x 765 824 5/8[15,88] 3/4(19,05] 1-3/8[34,96]/ 15/8[15,88] 1/4[6,35] 34,0/22,95 50 ~ 130(200)

¹⁾ EER and COP calculation is based in accordance to EN 14511. 2) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency " η " values of the COMMISSION REGULATION (EU) 2016/2281, SEER, SCOP = [η + Correction] × PEF, 3] Piping diameter under 100 m for ultimate indoor unit / over 100 m for ultimate indoor unit (if the longest piping equivalent length exceeds 100 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes). 4] If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units, B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB [standard -25 °C WB], C. Simultaneous operation is limited to less than 130% of connectable indoor units. 4] SEER / SCOP and $\eta_{x,c}$ / $\eta_{x,h}$ are in accordance with ErP test data for U2 type 4 way 90x90 cassette indoor units.




2-Pipe EC0i EX ME2 Series R410A



Two independently controlled Inverter compressors achieve high efficiency. Redesigned components in the body provide performance improvement especially in the rated cooling condition and EER performance*.

* Applicable to ECOi EX outdoor units over 14 HP (2-compressor models).



2-Pipe EC0i EX ME2 Series - R410A

A VRF system delivering energy-saving performance, powerful operation, reliability and comfort, surpassing anything previously possible. It represents a true paradigm shift in air conditioning solutions.

VRF with outstanding energy-saving performance and powerful operation SEER 7,56 (18 HP model).



HP			8 HP	10 HP	12 HP	14 HP	16 HP	18 HP	20 HP
Outdoor unit			U-8ME2E8	U-10ME2E8	U-12ME2E8	U-14ME2E8	U-16ME2E8	U-18ME2E8	U-20ME2E8
	Voltage	V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380-400-415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase	Three phase	Three phase	Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50	50	50	50	50
Cooling capacity		kW	22,4	28,0	33,5	40,0	45,0	50,0	56,0
EER 11		W/W	4,70	4,37	3,96	3,88	3,52	3,52	3,35
ESEER		W/W	9,33	8,67	7,94	7,73	7,19	6,95	6,18
Current		А	7,79 - 7,40 - 7,14	10,70-10,20-9,80	13,70-13,00-12,50	17,40-16,50-15,90	21,10-20,10-19,40	23,20-22,00-21,20	26,70-25,40-24,50
Input power		kW	4,77	6,41	8,47	10,30	12,80	14,20	16,70
Heating capacity		kW	25,0	31,5	37,5	45,0	50,0	56,0	63,0
COP 11		W/W	5,13	4,76	4,73	4,56	4,42	4,38	3,94
Current		А	7,96 - 7,56 - 7,29	11,10-10,50-10,10	12,90-12,30-11,80	16,60-15,80-15,20	18,90-17,90-17,30	21,10-20,10-19,40	25,90-24,60-23,70
Input power		kW	4,87	6,62	7,92	9,86	11,30	12,80	16,00
Starting current		Α	1,00	1,00	1,00	2,00	2,00	2,00	2,00
External static pres	sure (Max)	Pa	80	80	80	80	80	80	80
Air flow		m³/min	224	224	232	232	232	405	405
Sound pressure	Normal mode	dB(A)	54	56	59	60	61	59	60
Journa pressure	Silent mode	dB(A)	51	53	56	57	58	56	57
Sound power	Normal mode	dB(A)	75	77	80	81	82	80	81
Dimension	HxWxD	mm	1842×770 ×1000	1842×770 ×1000	1842×1180 ×1000	1842×1180 ×1000	1842 x 1180 x 1000	1842×1540 ×1000	1842 x 1540 x 1000
Net weight		kg	210	210	270	315	315	375	375
	Liquid	Inch (mm)	3/8 (9,52) / 1/2 (12,70)	3/8 (9,52) / 1/2 (12,70)	1/2 (12,70)/ 5/8 (15,88)	1/2(12,70)/ 5/8(15,88)	1/2(12,70)/ 5/8(15,88)	5/8(15,88)/ 3/4(19,05)	5/8 (15,88) / 3/4 (19,05)
Piping diameter 2)	Gas	Inch (mm)	3/4 (19,05) / 7/8 (22,22)	7/8 (22,22) / 1 (25,40)	1 (25,40) / 1-1/8 (28,58)	1 (25,40) / 1-1/8 (28,58)	1-1/8 (28,58) / 1-1/4 (31,75)	1-1/8 (28,58) / 1-1/4 (31,75)	1-1/8 (28,58) / 1-1/4 (31,75)
	Balance	Inch (mm)	1/4 (6,35)	1/4[6,35]	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)
Refrigerant (R410A)	/ CO ₂ Eq	kg/T	5,60/11,6928	5,60/11,6928	8,30/17,3304	8,30/17,3304	8,30/17,3304	9,50/19,836	9,50/19,836
Maximum allowable capacity ratio 33	indoor / outdoor	%	50 ~ 130 (200)	50 ~ 130 (200)	50~130(200)	50 ~ 130 (200)	50 ~ 130 (200)	50 ~ 130 (200)	50 ~ 130 (200)
0	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
Operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18

ErP data 41							
SEER 5)	7,43	6,96	6,74	7,23	6,43	7,56	7,03
n _{s,c}	294,3%	275,4%	266,6%	286,0%	254,3%	299,2%	278,2%
SCOP 5)	4,79	4,27	4,72	4,28	4,05	4,29	4,09
$\eta_{s,h}$	188,4%	167,6%	185,8%	168,2%	159,0%	168,7%	160,4%

1) EER and COP calculation is based in accordance to EN 14511. 2) Piping diameter under 90 m for ultimate indoor unit / over 90 m for ultimate indoor unit (if the longest piping equivalent length exceeds 90 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes), 3) If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units. B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB (standard -25 °C WB), C. Simultaneous operation is limited to less than 130% of connectable indoor units. 4) SEER / SCOP and n_x / n_x are in accordance with ErP test data for F2 type variable static pressure hide-away indoor units. 5) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency "n" values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = {n + Correction} × PEF.

Technical focus

- · Twin rotary Inverter compressor
- · High performance at extreme conditions
- Outstanding efficiency and comfort
- Extraordinary partial load, SEER and SCOP
- SEER and SCOP following EN-14825
- · Oil recovery intelligent control

- Top comfort
- Superior flexibility
- · Bluefin full line up EX
- \cdot Extremely high capacity at -20 °C and unique heating capacity at -25 °C
- Smooth exhaust flow by bell-mouth















2-Pipe EC0i EX ME2 Series R410A high efficiency model combination from 18 to 64 HP

HP			18 HP	20 HP	22 HP	24 HP	26 HP	28 HP
0.11			U-8ME2E8	U-10ME2E8	U-10ME2E8	U-12ME2E8	U-10ME2E8	U-12ME2E8
Outdoor unit			U-10ME2E8	U-10ME2E8	U-12ME2E8	U-12ME2E8	U-16ME2E8	U-16ME2E8
	Voltage	٧	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase					
	Frequency	Hz	50	50	50	50	50	50
Cooling capacity		kW	50,0	56,0	61,5	68,0	73,0	78,5
EER 1)		W/W	4,55	4,38	4,13	3,93	3,80	3,69
Current		А	18,20 - 17,30 - 16,60	21,40 - 20,30 - 19,60	24,30-23,10-22,30	28,00-26,60-25,60	31,70-30,10-29,00	34,80-33,10-31,90
Input power		kW	11,00	12,80	14,90	17,30	19,20	21,30
Heating capacity		kW	56,0	63,0	69,0	76,5	81,5	87,5
COP 11		W/W	4,96	4,77	4,76	4,69	4,55	4,56
Current		А	18,70 - 17,70 - 17,10	22,00-20,90-20,20	23,90-22,70-21,90	26,60-25,30-24,40	29,90-28,40-27,40	31,70-30,10-29,00
Input power		kW	11,30	13,20	14,50	16,30	17,90	19,20
Starting current		А	2,00	2,00	2,00	2,00	3,00	3,00
External static press	sure (Max)	Pa	80	80	80	80	80	80
Air flow		m³/min	448	448	456	464	456	464
Sound pressure	Normal	dB(A)	58,5	59,0	61,0	62,0	62,5	63,5
Souria pressure	Silent mode	dB(A)	55,5	56,0	58,0	59,0	59,5	60,5
Sound power	Normal mode	dB(A)	79,5	80,0	82,0	83,0	83,5	84,5
Dimension / Net weight	HxWxD	mm / kg	1842 x 1600 x 1000/420	1842×1600 ×1000/420	1842×2010 ×1000/480	1842 x 2420 x 1000/540	1842 x 2010 x 1000/535	1842×2420 ×1000/585
	Liquid	Inch (mm)	5/8 (15,88) / 3/4 (19,05)	5/8 (15,88)/ 3/4 (19,05)	5/8(15,88)/ 3/4(19,05)	5/8(15,88)/ 3/4(19,05)	3/4 (19,05)/ 7/8 (22,22)	3/4(19,05)/ 7/8(22,22)
Piping diameter 2	Gas	Inch (mm)	1-1/8 (28,58) / 1-1/4 (31,75)	1-1/4 (31,75) / 1-1/2 (38,10)	1-1/4 (31,75) / 1-1/2 (38,10)			
	Balance	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4(6,35)	1/4(6,35)
Refrigerant (R410A)	/ CO ₂ Eq.	kg / T	11,20/23,3856	11,20/23,3856	13,90/29,0232	16,60/34,6608	13,90/29,0232	16,60/34,6608
Maximum allowable capacity ratio 31	indoor / outdoor	%	50 ~ 130 (200)	50~130(200)	50~130(200)	50~130(200)	50 ~ 130 (200)	50~130(200)
Onesatina sana:	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
Operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18

HP			30 HP	32 HP	34 HP	36 HP	38 HP	40 HP
			U-14ME2E8	U-16ME2E8	U-10ME2E8	U-12ME2E8	U-10ME2E8	U-12ME2E8
Outdoor unit			U-16ME2E8	U-16ME2E8	U-12ME2E8	U-12ME2E8	U-12ME2E8	U-12ME2E8
					U-12ME2E8	U-12ME2E8	U-16ME2E8	U-16ME2E8
	Voltage	٧	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase	Three phase	Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50	50	50	50
Cooling capacity		kW	85,0	90,0	96,0	101,0	107,0	113,0
EER 1)		W/W	3,68	3,52	4,05	3,95	3,84	3,75
Current		Α	38,60-36,60-35,30	42,30-40,20-38,70	38,70-36,80-35,50	41,40-39,30-37,90	46,10-43,80-42,20	49,20-46,70-45,0
Input power		kW	23,10	25,60	23,70	25,60	27,90	30,10
Heating capacity		kW	95,0	100,0	108,0	113,0	119,0	127,0
COP 1)		W/W	4,48	4,42	4,72	4,73	4,61	4,57
Current		Α	35,40-33,60-32,40	37,70-35,80-34,60	37,80-35,90-34,60	39,00-37,10-35,80	42,60-40,50-39,00	45,90-43,60-42,0
Input power		kW	21,20	22,60	22,90	23,90	25,80	27,80
Starting current		Α	4,00	4,00	3,00	3,00	4,00	4,00
External static press	sure (Max)	Pa	80	80	80	80	80	80
Air flow		m³/min	464	464	688	696	688	696
Cound procesure	Normal	dB(A)	63,5	64,0	63,0	64,0	64,0	64,5
Sound pressure	Silent mode	dB(A)	60,5	61,0	60,0	61,0	61,0	61,5
Sound power	Normal mode	dB(A)	84,5	85,0	84,0	85,0	85,0	85,5
Dimension / Net weight	HxWxD	mm / kg	1842×2420 ×1000/630	1842×2420 ×1000/630	1842x3250 x1000/750	1842x3660 x1000/810	1842x3250 x1000/795	1842×3660 ×1000/855
	Liquid	Inch (mm)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4 (19,05)/ 7/8 (22,22)	3/4(19,05)/ 7/8(22,22)
Piping diameter 2]	Gas	Inch (mm)	1-1/4 (31,75) / 1-1/2 (38,10)	1-1/4 (31,75)/ 1-1/2 (38,10)	1-1/4 (31,75) / 1-1/2 (38,10)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)
	Balance	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)
Refrigerant (R410A)	/ CO ₂ Eq.	kg / T	16,60/34,6608	16,60/34,6608	22,20/46,3536	24,90/51,9912	22,20/46,3536	24,90/46,3536
Maximum allowable capacity ratio 31	indoor / outdoor	%	50 ~ 130 (200)	50~130(200)	50~130 (200)	50 ~ 130 (200)	50 ~ 130 (200)	50~130(200)
0	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
Operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18

Data is for reference. 1) EER and COP calculation is based in accordance to EN 14511. 2) Piping diameter under 90 m for ultimate indoor unit / over 90 m for ultimate indoor unit (if the longest piping equivalent length exceeds 90 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes). 3] If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units. B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB (standard -25 °C WB). C. Simultaneous operation is limited to less than 130% of connectable indoor units.

Outdoor unit Power supply Cooling capacity EER ¹¹ Current Input power Heating capacity COP ¹¹ Current Input power	Voltage Phase Frequency	V Hz kW W/W A	U-10ME2E8 U-16ME2E8 U-16ME2E8 380 - 400 - 415 Three phase 50 118,0 3,69 52,80 - 50,20 - 48,40	U-12ME2E8 U-16ME2E8 U-16ME2E8 380 - 400 - 415 Three phase 50 124,0 3.62	U-14ME2E8 U-16ME2E8 U-16ME2E8 380 - 400 - 415 Three phase 50 130,0	U-16ME2E8 U-16ME2E8 U-16ME2E8 380 - 400 - 415 Three phase	U-10ME2E8 U-12ME2E8 U-12ME2E8 U-16ME2E8 380 - 400 - 415 Three phase 50	U-12ME2E8 U-12ME2E8 U-12ME2E8 U-16ME2E8 380 - 400 - 415 Three phase 50
Power supply Cooling capacity EER 11 Current Input power Heating capacity COP 11 Current Input power	Phase	Hz kW W/W A	U-16ME2E8 380 - 400 - 415 Three phase 50 118,0 3,69	U-16ME2E8 380 - 400 - 415 Three phase 50 124,0	U-16ME2E8 380 - 400 - 415 Three phase 50	U-16ME2E8 380 - 400 - 415 Three phase 50	U-12ME2E8 U-16ME2E8 380 - 400 - 415 Three phase	U-12ME2E8 U-16ME2E8 380 - 400 - 415 Three phase
Power supply Cooling capacity EER 11 Current Input power Heating capacity COP 11 Current Input power	Phase	Hz kW W/W A	380 - 400 - 415 Three phase 50 118,0 3,69	380 - 400 - 415 Three phase 50 124,0	380 - 400 - 415 Three phase 50	380 - 400 - 415 Three phase 50	U-16ME2E8 380 - 400 - 415 Three phase	U-16ME2E8 380 - 400 - 415 Three phase
Cooling capacity EER 11 Current Input power Heating capacity COP 11 Current Input power	Phase	Hz kW W/W A	Three phase 50 118,0 3,69	Three phase 50 124,0	Three phase 50	Three phase 50	380 - 400 - 415 Three phase	380 - 400 - 415 Three phase
Cooling capacity EER 11 Current Input power Heating capacity COP 11 Current Input power	Phase	Hz kW W/W A	Three phase 50 118,0 3,69	Three phase 50 124,0	Three phase 50	Three phase 50	Three phase	Three phase
Cooling capacity EER 11 Current Input power Heating capacity COP 11 Current Input power		kW W/W A kW	50 118,0 3,69	50 124,0	50	50	<u>'</u>	
EER 11 Current Input power Heating capacity COP 11 Current Input power	Frequency	kW W/W A kW	118,0 3,69	124,0			50	50
EER 11 Current Input power Heating capacity COP 11 Current Input power		W/W A kW	3,69		130,0			JU
Current Input power Heating capacity COP 11 Current Input power		A kW		3.62		135,0	140,0	145,0
Input power Heating capacity COP 11 Current Input power		kW	52,80-50,20-48,40		3,62	3,52	3,87	3,82
Heating capacity COP ¹¹ Current Input power				56,00-53,20-51,30	59,90-56,90-54,90	63,40 - 60,20 - 58,10	59,10-56,20-54,20	62,10 - 59,00 - 56,80
COP ¹⁾ Current Input power		1.347	32,00	34,30	35,90	38,40	36,20	38,00
Current Input power		kW	132,0	138,0	145,0	150,0	155,0	160,0
Input power		W/W	4,49	4,50	4,46	4,42	4,65	4,66
		Α	49,10-46,60-44,90	50,70 - 48,20 - 46,40	54,30-51,50-49,70	56,60-53,80-51,80	55,00-52,20-50,40	56,60 - 53,80 - 51,90
		kW	29,40	30,70	32,50	33,90	33,30	34,30
Starting current		Α	5,00	5,00	6,00	6,00	5,00	5,00
External static pressu	ıre (Max)	Pa	80	80	80	80	80	80
Air flow		m³/min	688	696	696	696	920	928
C	Normal	dB(A)	65,0	65,5	65,5	66,0	65,5	66,0
Sound pressure	Silent mode	dB(A)	62,0	62,5	62,5	63,0	62,5	63,0
Sound power	Normal mode	dB(A)	86,0	86,5	86,5	87,0	86,5	87,0
Dimension / Net weight	HxWxD	mm / kg	1842×3250 ×1000/840	1842×3660 ×1000/900	1842x3660 x1000/945	1842×3660 ×1000/945	1842×4490 ×1000/1065	1842×4900 ×1000/1125
	Liquid	Inch (mm)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4 (19,05) / 7/8 (22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)
Piping diameter 2)	Gas	Inch (mm)	1-1/2 (38,10)/ 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10)/ 1-5/8 (41,28)
	Balance	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)
Refrigerant (R410A) /	CO, Eq.	kg / T	22,20/51,9912	24,90/51,9912	24,90/51,9912	24,90/51,9912	30,50/63,6840	33,20/69,3216
Maximum allowable in capacity ratio 31	ndoor / outdoor	%	50~130(200)	50~130(200)	50~130(200)	50 ~ 130 (200)	50 ~ 130 (200)	50 ~ 130 (200)
	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
Operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18
ш								

HP			54 HP	56 HP	58 HP	60 HP	62 HP	64 HP
			U-10ME2E8	U-12ME2E8	U-10ME2E8	U-12ME2E8	U-14ME2E8	U-16ME2E8
Outdoor unit			U-12ME2E8	U-12ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8
Outdoor unit			U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8
			U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8
	Voltage	٧	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase					
	Frequency	Hz	50	50	50	50	50	50
Cooling capacity		kW	151,0	156,0	162,0	168,0	174,0	180,0
EER 11		W/W	3,75	3,71	3,65	3,60	3,60	3,52
Current		А	66,60-63,20-60,90	68,80-65,30-63,00	73,30-69,70-67,10	77,10-73,30-70,60	79,80 - 75,80 - 73,00	84,60-80,30-77,40
Input power		kW	40,30	42,10	44,40	46,70	48,30	51,20
Heating capacity		kW	169,0	175,0	182,0	189,0	195,0	201,0
COP 1)		W/W	4,56	4,56	4,47	4,47	4,45	4,42
Current		А	61,90 - 58,80 - 56,70	63,40-60,20-58,10	68,00-64,60-62,20	70,60-67,10-64,70	73,10-69,50-67,00	76,00 - 72,20 - 69,60
Input power		kW	37,10	38,40	40,70	42,30	43,80	45,50
Starting current		Α	6,00	6,00	7,00	7,00	8,00	8,00
External static press	ure (Max)	Pa	80	80	80	80	80	80
Air flow		m³/min	920	928	920	928	928	928
Sound pressure	Normal	dB(A)	66,0	66,5	66,5	67,0	67,0	67,0
Sound pressure	Silent mode	dB(A)	63,0	63,5	63,5	64,0	64,0	64,0
Sound power	Normal mode	dB(A)	87,0	87,5	87,5	88,0	88,0	88,0
Dimension / Net weight	HxWxD	mm / kg	1842×4490 ×1000/1110	1842×4900 ×1000/1170	1842×4490 ×1000/1155	1842×4900 ×1000/1215	1842×4900 ×1000/1260	1842×4900 ×1000/1260
	Liquid	Inch (mm)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)
Piping diameter 23	Gas	Inch (mm)	1-1/2 (38,10) / 1-5/8 (41,28)	1-5/8 (41,28) / 1-3/4 (44,45)	1-5/8 (41,28) / 1-3/4 (44,45)			
	Balance	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)
Refrigerant (R410A)	/ CO, Eq.	kg / T	30,50/63,6840	33,20/69,3216	30,50/63,6840	33,20/69,3216	33,20/69,3216	33,20/69,3216
Maximum allowable capacity ratio ³⁾	indoor / outdoor	%	50~130(200)	50~130(200)	50 ~ 130 (200)	50~130 (200)	50~130(200)	50~130(200)
0	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
Operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18

Data is for reference. 1) EER and COP calculation is based in accordance to EN 14511. 2) Piping diameter under 90 m for ultimate indoor unit / over 90 m for ultimate indoor unit / if the longest piping equivalent length exceeds 90 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes]. 3) If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units, B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB (standard -25 °C WB), C. Simultaneous operation is limited to less than 130% of connectable indoor units.



2-Pipe EC0i EX ME2 Series R410A space saving model combination from 22 to 80 HP

Detail of the properties of the propertie	НР			22 HP	24 HP	26 HP	28 HP	30 HP	32 HP	34 HP
Power supply Po	0			U-10ME2E8	U-12ME2E8	U-10ME2E8	U-12ME2E8	U-14ME2E8	U-16ME2E8	U-14ME2E8
Power supply Plase Invere phase Invere phase Three phase 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 50 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30	Outdoor unit			U-12ME2E8	U-12ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-20ME2E8
Prequency Hz S0 S0 S0 S0 S0 S0 S0 S		Voltage	٧	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380-400-415	380 - 400 - 415
No	Power supply	Phase		Three phase						
ERR® W/W 4,13 3,93 3,80 3,69 3,68 5,52 3,56 SEER® 6,90 6,80 6,62 6,00 6,88 6,52 7,21 Current 4 24,023,022,022 28,002,602,023 31,000,102,000 36,003,013,013 36,003,003,003 40,042,002,003 40,041,041,004,004 Heating capacity kW 14,90 71,50 81,5 87,5 95,0 100,0 108,0 COP 1 WW 4,76 4,68 4,55 4,58 4,48 4,22 1,70 COP 2 WW 4,75 4,68 4,55 4,58 4,48 4,20 1,70 COP 3 WW 14,50 16,30 17,90 30,00 30,00 30,00 30,00 30,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00		Frequency	Hz	50	50	50	50	50	50	50
SEER ³¹ 6,90 6,86 6,62 6,60 6,88 6,52 7,21 Current A 2,30-23,10-220 280-25,0-250 317-30,10-290 3,80-33,10-310 820-35,0-350 4,20-40,0-30 4,10-41,90-40,00 Input power kW 14,90 17,0 19,20 21,30 23,10 25,00 27,00 Reating capacity kW 4,76 4,69 4,55 4,56 4,48 4,42 4,17 SCOP ¹¹ W/W 4,76 4,69 4,56 4,56 4,58 4,69 4,56 4,59 4,16 4,29 4,18 4,09 4,14 4,17 4,14 4,17 4,14 4,17 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,14 4,10 4,10 4,10 4,10 4,10 4,10 4,10 4,10 4,10 4,10 4,10 <td>Cooling capacity</td> <td></td> <td>kW</td> <td>61,5</td> <td>68,0</td> <td>73,0</td> <td>78,5</td> <td>85,0</td> <td>90,0</td> <td>96,0</td>	Cooling capacity		kW	61,5	68,0	73,0	78,5	85,0	90,0	96,0
Current A 24,30-2310-22,30 28,00-26,60-25,60 31,70-310-29,00 48,90-33,10-31,90 38,90-36,60-35,30 42,90-40,20-38,70 44,10-49,04,040 Input power kW 14,90 17,30 19,20 21,30 23,10 25,60 27,00 Heating capacity kW 69,00 76,5 81,5 87,5 95,0 100,0 108,0 COP ¹⁰ W/W 4,76 4,69 4,55 4,56 4,48 4,42 4,17 SCOP ²⁰ L 4,53 4,78 4,16 4,29 4,13 4,09 4,14 Current A 23,90-22,70-2190 26,60-25,30-24,00 29,00-28,40-27,00 31,70-30,10-29,00 35,00-33,0-32,00 37,0-35,80-34,00 42,90 22,50 25,90 Starting current A 2,00 2,00 3,00 3,00 3,00 3,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00	EER 1)		W/W	4,13	3,93	3,80	3,69	3,68	3,52	3,56
Input power KW 14,90 17,30 19,20 21,30 23,10 25,60 27,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,00 108,0	SEER 2)			6,90	6,86	6,62	6,60	6,88	6,55	7,21
Heating capacity	Current		А	24,30-23,10-22,30	28,00-26,60-25,60	31,70-30,10-29,00	34,80-33,10-31,90	38,60-36,60-35,30	42,30-40,20-38,70	44,10-41,90-40,40
No	Input power		kW	14,90	17,30	19,20	21,30	23,10	25,60	27,00
SCOP ³¹ 4,53 4,78 4,16 4,27 4,13 4,09 4,14	Heating capacity		kW	69,0	76,5	81,5	87,5	95,0	100,0	108,0
Current A 23/90-22/70-21/90 26/00-25/30-24/40 29/90-28/40-27/40 31/70-3010-29/00 35/00-33/60-32/40 37/70-35/80-34/40 42/90-40/60-39/20 Input power kW 14,50 16,30 17,90 19,20 21,20 22,60 25,90 Starting current A 2,00 2,00 3,00 3,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,00 4,0	COP 11		W/W	4,76	4,69	4,55	4,56	4,48	4,42	4,17
Normal manual	SCOP 2)			4,53	4,78	4,16	4,29	4,13	4,09	4,14
Starting current A 2,00 2,00 3,00 3,00 4,00 4,00 4,00 External static pressure (Max) Pa 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80 80	Current		Α	23,90-22,70-21,90	26,60-25,30-24,40	29,90-28,40-27,40	31,70-30,10-29,00	35,40-33,60-32,40	37,70-35,80-34,60	42,80-40,60-39,20
External static pressure Max Pa 80 80 80 80 80 80 80 8	Input power		kW	14,50	16,30	17,90	19,20	21,20	22,60	25,90
Air flow m²/min 456 464 456 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 464 <th< td=""><td>Starting current</td><td></td><td>Α</td><td>2,00</td><td>2,00</td><td>3,00</td><td>3,00</td><td>4,00</td><td>4,00</td><td>4,00</td></th<>	Starting current		Α	2,00	2,00	3,00	3,00	4,00	4,00	4,00
Sound pressure Normal / Sitent mode dB[A] 61,0/58,0 62,0/59,0 62,5/59,5 63,5/60,5 63,5/60,5 64,0/61,0 63,0/60,0 Sound power Normal mode dB[A] 82,0 83,0 83,5 84,5 84,5 85,0 84,0 Dimension / Net weight hxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	External static press	sure (Max)	Pa	80	80	80	80	80	80	80
Sound power Normal mode dB(A) 82,0 83,0 83,5 84,5 84,5 85,0 84,0 Dimension / Net weight HxWxD mm / kg 1842x2210 x1000/480 x1000/540 x1000/520 x1000/525 x1000/585 x1000/630 x1000/630 x1000/630 x1000/630 x1000/630 1842x2420 x1000/630 x1000/630 x1000/630 x1000/630 x1000/630 1842x2420 x1000/630 x1000/630 x1000/630 x1000/630 x1000/630 1842x2420 x1000/630 x1000/630 x1000/630 x1000/630 x1000/630 x1000/630 1842x2420 x1000/630 x1000/630 x1000/630 x1000/630 x1000/630 x1000/630 1842x2420 x1000/630 1842x2420 x1000/630	Air flow		m³/min	456	464	456	464	464	464	637
Dimension / Net weight Netw	Sound pressure	Normal / Silent mode	dB(A)	61,0/58,0	62,0/59,0	62,5/59,5	63,5/60,5	63,5/60,5	64,0/61,0	63,0/60,0
Net weight HXWXD mm / kg x 1000/480 x 1000/540 x 1000/525 x 1000/585 x 1000/630	Sound power	Normal mode	dB(A)	82,0	83,0	83,5	84,5	84,5	85,0	84,0
Piping diameter Piping dia		HxWxD	mm / kg							
Gas Inch (mm) 1-1/4(31,75) 1-1/4(31,75) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1-1/2(38,10) 1		Liquid	Inch (mm)							
Refrigerant [R410A] / CO ₂ Eq. kg / T 13,90/23,3856 16,60/34,6608 13,90/29,0232 16,60/34,6608 16,60/34,6608 16,60/34,6608 17,80/37,1664 Maximum allowable indoor / outdoor capacity ratio 4 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [200] 50 ~ 130 [Piping diameter 3]	Gas	Inch (mm)							
Maximum allowable indoor / outdoor capacity ratio 4		Balance	Inch (mm)	1/4(6,35)	1/4(6,35)	1/4 (6,35)	1/4[6,35]	1/4 (6,35)	1/4 [6,35]	1/4 (6,35)
Capacity ratio 4	Refrigerant (R410A)	/ CO ₂ Eq.	kg / T	13,90/23,3856	16,60/34,6608	13,90/29,0232	16,60/34,6608	16,60/34,6608	16,60/34,6608	17,80/37,1664
Operating range		indoor / outdoor	%	50~130(200)	50 ~ 130 (200)	50 ~ 130 (200)	50 ~ 130 (200)	50 ~ 130 (200)	50 ~ 130 (200)	50~130(200)
Uperating range	0	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
⊓eat Mill ~ Max	operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18

HP			36 HP	38 HP	40 HP	42 HP	44 HP	46 HP	48 HP
			U-16ME2E8	U-18ME2E8	U-20ME2E8	U-10ME2E8	U-12ME2E8	U-14ME2E8	U-16ME2E8
Outdoor unit			U-20ME2E8	U-20ME2E8	U-20ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8
				-	-	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8
	Voltage	٧	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase	Three phase	Three phase	Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50	50	50	50	50
Cooling capacity		kW	101,0	107,0	113,0	118,0	124,0	130,0	135,0
EER 1)		W/W	3,42	3,42	3,34	3,69	3,62	3,62	3,52
SEER 2)			6,86	7,32	7,16	6,57	6,60	6,70	6,55
Current		А	47,70-45,30-43,70	50,60-48,10-46,30	54,10-51,40-49,50	52,80-50,20-48,40	56,00-53,20-51,30	59,90-56,90-54,90	63,40-60,20-58,10
Input power		kW	25,9	31,3	33,8	32,0	34,3	35,9	38,4
Heating capacity		kW	113,0	119,0	127,0	132,0	138,0	145,0	150,0
COP 11		W/W	4,14	4,13	3,92	4,49	4,50	4,46	4,42
SCOP 2]			4,06	4,14	4,13	4,11	4,21	4,12	4,09
Current		Α	44,60-42,40-40,80	47,10-44,70-43,10	52,40-49,80-48,00	49,10-46,60-44,90	50,70-48,20-46,40	54,30-51,50-49,7	56,60-53,80-51,8
Input power		kW	27,30	28,80	32,40	29,40	30,70	32,50	33,90
Starting current		Α	4,00	4,00	4,00	5,00	5,00	6,00	6,00
External static press	sure (Max)	Pa	80	80	80	80	80	80	80
Air flow		m³/min	637	810	810	688	696	696	696
Sound pressure	Normal / Silent mode	dB(A)	63,5/60,5	62,5/59,5	63,0/60,0	65,0/62,0	65,5/62,5	65,5/62,5	66,0/63,0
Sound power	Normal mode	dB(A)	84,5	83,5	84,0	86,0	86,5	86,5	87,0
Dimension / Net weight	HxWxD	mm / kg	1842×2780 ×1000/690	1842×3140 ×1000/750	1842×3140 ×1000/750	1842 x 3250 x 1000/840	1842 x 3660 x 1000/900	1842×3660 ×1000/945	1842×3660 ×1000/945
	Liquid	Inch (mm)	3/4 (19,05)/ 7/8 (22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4 (19,05) / 7/8 (22,22)
Piping diameter 3]	Gas	Inch (mm)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10)/ 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2 (38,10)/ 1-5/8 (41,28)	1-1/2 (38,10) / 1-5/8 (41,28)
	Balance	Inch (mm)	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)
Refrigerant (R410A)	/ CO ₂ Eq.	kg / T	17,80/37,1664	19,00/39,672	19,00/39,672	22,20/46,3536	24,90/51,9912	24,90/51,9912	24,90/51,9912
Maximum allowable capacity ratio 4	indoor / outdoor	%	50~130(200)	50 ~ 130 (200)	50~130 (200)	50~130 (200)	50~130(200)	50~130(200)	50~130(200)
Operating range	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
Operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18

1) EER and COP calculation is based in accordance to EN 14511. 2) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency "ŋ" values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = [ŋ + Correction] × PEF. 3] Piping diameter under 90 m for ultimate indoor unit / over 90 m for ultimate indoor unit lif the longest piping equivalent length exceeds 90 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes). 4) If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units. B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB (standard -25 °C WB). C. Simultaneous operation is limited to less than 130% of connectable indoor units.

НР			50 HP U-14ME2E8	52 HP U-16ME2E8	54 HP U-14ME2E8	56 HP U-16ME2E8	58 HP U-18ME2E8	60 HP U-20ME2E8	62 HP U-14ME2E8	64 HP U-16ME2E8
			U-16ME2E8	U-16ME2E8	U-20ME2E8	U-20ME2E8	U-20ME2E8	U-20ME2E8	U-16ME2E8	U-16ME2E8
Outdoor unit			U-20ME2E8	U-20ME2E8	U-20ME2E8	U-20ME2E8	U-20ME2E8	U-20ME2E8	U-16ME2E8	U-16ME2E8
				,		,	,	,	U-16ME2E8	U-16ME2E8
	Voltage	٧	380 - 400 - 415	380 - 400 - 415	380-400-415	380-400-415	380-400-415	380-400-415	380 - 400 - 415	380 - 400 - 415
Power supply	Phase		Three phase	Three phase	Three phase	Three phase	Three phase	Three phase	Three phase	Three phase
	Frequency	Hz	50	50	50	50	50	50	50	50
Cooling capacity		kW	140,0	145,0	151,0	156,0	162,0	168,0	174,0	180,0
SEER 2)		W/W	3,55 6,96	3,46 6,72	3,49 7,16	3,41 6,92	3,40 7,30	3,35 7,16	3,60 6,68	3,52 6,55
Current		A	64,40-61,10-58,90	68,50-65,00-62,70	70,00-66,50-64,10	74,00-70,30-67,80		80,10-76,10-73,40	79,80-75,80-73,00	84,60-80,30-77,40
Input power	<u>.</u>	kW	39,40	41,90	43,30	45,80	47,60	50,10	48,30	51,20
Heating capacity		kW	155,0	160,0	169,0	175,0	182,0	189,0	195,0	201,0
COP 11		W/W	4,29	4,27	4,11	4,08	4,06	3,94	4,45	4,42
SCOP 2)			4,08	4,05	4,13	4,07	4,13	4,13	4,11	4,09
Current		Α	59,60-56,60-54,60	61,90-58,80-56,70	67,10-63,80-61,50	70,10-66,60-64,20	73,20-69,50-67,00	77,60-73,70-71,00	73,10-69,50-67,00	76,00-72,20-69,6
Input power		kW	36,10	37,50	41,10	42,90	44,80	48,00	43,80	45,50
Starting current		A	6,00	6,00	6,00	6,00	6,00	6,00	8,00	8,00
External static press	ure (Max)	Pa	80	80	80	80	80	80	80	80
Air flow	Normal / Silent mode	m³/min dB(A)	869	869	1042	1042	1215	1215 65,0/62,0	928	928
Sound pressure Sound power	Normal / Silent mode	dB(A)	65,5/62,5 86,5	65,5/62,5 86,5	65,0/62,0 86,0	65,5/62,5 86,5	64,5/61,5 85,5	86,0	67,0/64,0 88,0	67,0/64,0 88,0
Dimension /		UD(A)	1842 x 4020	1842 x 4020	1842 x 4380	1842 x 4380	1842 x 4740	1842 x 4740	1842 x 4900	1842 x 4900
Net weight	HxWxD	mm / kg	x1000/1005	x1000/1005	x1000/1065	x1000/1065	x1000/1125	x1000/1125	x1000/1260	x1000/1260
	Liquid	Inch (mm)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4 (19,05) / 7/8 (22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)	3/4(19,05)/ 7/8(22,22)
Piping diameter 3)	Gas	Inch (mm)	1-1/2 (38,10) / 1-5/8 (41,28)	1-1/2(38,10)/ 1-5/8(41,28)	1-1/2 (38,10)/ 1-5/8 (41,28)	1-1/2 (38,10)/ 1-5/8 (41,28)	1-1/2(38,10)/ 1-5/8(41,28)	1-1/2(38,10)/ 1-5/8(41,28)	1-5/8(41,28)/ 1-3/4(44,45)	1-5/8 (41,28)/ 1-3/4 (44,45)
	Balance	Inch (mm)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)
Refrigerant (R410A)	/ CO ₂ Eq.	kg / T	26,10/54,4968	26,10/54,4968	27,30/57,0024	27,30/57,0024	28,50/59,508	28,50/59,508	33,20/69,3216	33,20/69,3216
Maximum allowable capacity ratio 4)	indoor / outdoor	%	50~130(200)	50 ~ 130 (200)	50~130 (200)	50~130 (200)	50 ~ 130 (200)	50~130(200)	50 ~ 130 (200)	50~130(200)
Operating range	Cool Min ~ Max	°C	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52	-10~+52
- operating range	Heat Min ~ Max	°C	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18	-25~+18
		-								
НР		-	66 HP	68 HP	70 HP	72 HP	74 HP	76 HP	78 HP	80 HP
пР			U-10ME2E8	U-12ME2E8	U-10ME2E8	U-16ME2E8	U-16ME2E8	U-16ME2E8	U-18ME2E8	U-20ME2E8
Outdoor unit				U-12ME2E8 U-16ME2E8	U-10ME2E8 U-20ME2E8		U-16ME2E8 U-18ME2E8		U-18ME2E8 U-20ME2E8	U-20ME2E8 U-20ME2E8
			U-10ME2E8 U-16ME2E8	U-12ME2E8	U-10ME2E8	U-16ME2E8 U-16ME2E8	U-16ME2E8	U-16ME2E8 U-20ME2E8	U-18ME2E8	U-20ME2E8
	Voltage	V	U-10ME2E8 U-16ME2E8 U-20ME2E8	U-12ME2E8 U-16ME2E8 U-20ME2E8	U-10ME2E8 U-20ME2E8 U-20ME2E8	U-16ME2E8 U-16ME2E8 U-20ME2E8	U-16ME2E8 U-18ME2E8 U-20ME2E8	U-16ME2E8 U-20ME2E8 U-20ME2E8	U-18ME2E8 U-20ME2E8 U-20ME2E8	U-20ME2E8 U-20ME2E8 U-20ME2E8
	Voltage Phase	V	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8	U-12ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8	U-10ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8	U-16ME2E8 U-18ME2E8 U-20ME2E8 U-20ME2E8	U-16ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8	U-18ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8	U-20ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8
Outdoor unit Power supply		V	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415	U-12ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415	U-10ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415	U-16ME2E8 U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415	U-16ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415	U-18ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415	U-20ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415
Outdoor unit Power supply Cooling capacity	Phase	Hz kW	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0	U-12ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 190,0	U-10ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 196,0	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0	U-16ME2E8 U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0	U-16ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0	U-18ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0	U-20ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0
Outdoor unit Power supply Cooling capacity EER ¹¹	Phase	Hz	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52	U-12ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 190,0 3,49	U-10ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 196,0 3,47	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42	U-16ME2E8 U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42	U-16ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39	U-18ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38	U-20ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35
Outdoor unit Power supply Cooling capacity EER 11 SEER 21	Phase	Hz kW W/W	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92	U-12ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 190,0 3,49 6,91	U-10ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 196,0 3,47 7,09	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86	U-16ME2E8 U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03	U-16ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01	U-18ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18	U-20ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current	Phase	Hz kW W/W	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80	U-12ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70	U-10MEZE8 U-20MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 %540-90,60-87,30	U-16ME2E8 U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 %30-9340-90,00	U-16ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power	Phase	Hz kW W/W	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50	U-10MEZE8 U-20MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 9540-90,60-87,30 59,00	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 %30-9340-90,00 60,80	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70-96,60-93,10 62,90	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-9470 64,70	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 10680-101509780 66,80
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current	Phase	Hz kW W/W	U-10ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80	U-12ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70	U-10MEZE8 U-20MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60	U-16ME2E8 U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 %540-90,60-87,30	U-16ME2E8 U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 %30-9340-90,00	U-16ME2E8 U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18	U-20ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 224,0 3,35 7,16 10680-101509780 66,80 252,0
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity	Phase	Hz kW W/W A kW	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0	U-12ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0	U-10MEZE8 U-20MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 9540-90,60-87,30 59,00 226,0	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 %30-9340-90,00 60,80 233,0	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70-%60-93,10 62,90 239,0	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-94,70 64,70 245,0	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 10680-101509780 66,80
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11	Phase	Hz kW W/W A kW	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70-%60-93,10 62,90 239,0 4,03 4,07	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-9470 64,70 245,0 4,03 4,13	U-20ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 224,0 3,35 7,16 10\(\)00-101\(\)00-101\(\)00-101 66,80 252,0 3,94 4,13
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power	Phase	Hz kW W/W A kW kW W/W	U-10ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 213,0 4,18 4,17 83,30-79,20-76,30 51,00	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 4,12 92,30-87,70-84,50 56,50	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70-%,60-%310 62,90 239,0 4,03 4,07 %,90-92,00-88,70 59,30	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-830-94,70 64,70 245,0 4,03 4,13 8830-9340-90,00 60,80	U-20ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 224,0 3,35 7,16 10\(\)00-101\(\)00-101\(\)00-101 66,80 252,0 3,94 4,13
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power Starting current	Phase Frequency	Hz kW W/W A A kW A	U-10ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10 7,00	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 8,00	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 4,12 9230-87,70-84,50 56,50 8,00	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70-%60-9310 62,90 239,0 4,03 4,07 %,90-92,00-88,70 59,30 8,00	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-830-9470 64,70 245,0 4,03 4,13 8830-9340-9000 60,80 8,00	U-20ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 224,0 3,35 7,16 10\(\rho_{00}\) 10\(\rho_{00}\) 77\(\rho_{00}\) 66,80 252,0 3,94 4,13 103\(\rho_{00}\) 830-9470 64,00 8,00
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power Starting current External static press	Phase Frequency	Hz kW W/W A kW A Pa	U-10ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10 7,00 80	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 8,00 80	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 4,12 9230-87,70-84,50 8,00 80	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%,60%310 62,90 239,0 4,03 4,07 %,90-92,00-83,70 59,30 8,00 80	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-830-94,70 64,70 245,0 4,03 4,13 9830-93,40-90,00 60,80 8,00	U-20ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 224,0 3,35 7,16 10\(\frac{9}{2}\)0.10\(\frac{9}{2}\)0.252,0 3,94 4,13 103\(\frac{4}{2}\)0.7830-9470 64,00 8,00
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power Starting current External static press Air flow	Phase Frequency	Hz kW W/W A kW A Pa m³/min	U-10ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10 7,00 80 1439	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 8,00 80 1274	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 4,12 9230-87,70-84,50 56,50 8,00 80 1447	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%,60%310 62,90 239,0 4,03 4,07 %,90-9200-88,70 59,30 8,00 80 1447	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-830-94,70 64,70 245,0 4,03 4,13 9830-93,40-90,00 60,80 8,00 80 1620	U-20ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 224,0 3,35 7,16 10690-10150-77,0 66,80 252,0 3,94 4,13 103,40-98,30-94,70 64,00 8,00 80 1620
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power Starting current External static press Air flow Sound pressure	Phase Frequency ure (Max) Normal / Silent mode	Hz kW W/W A kW A Pa m³/min dB(A)	U-10ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10 7,00 80 1439 65,5/62,5	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 8,00 80 1274 66,5/63,5	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 4,12 92,30-87,70-84,50 8,00 80 1447 66,5/63,5	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%609310 62,90 239,0 4,03 4,07 %,90-92,00-88,70 8,00 80 1447 66,5/63,5	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-830-94,70 64,70 245,0 4,03 4,13 9830-93,40-90,00 60,80 8,00 80 1620 66,0/63,0	U-20ME2E8 U-20ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 224,0 3,35 7,16 10680-101509780 66,80 252,0 3,94 4,13 103,4098,30-94,70 64,00 8,00 80 1620 66,0/63,0
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power Starting current External static press Air flow Sound pressure Sound power Dimension /	Phase Frequency	Hz kW W/W A kW A Pa m³/min	U-10ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0 87,0 1842×5210×	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5 87,5	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10 7,00 80 1439 65,5/62,5 86,5 1842×5570×	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 8,00 80 1274 66,5/63,5 87,5 1842×5620×	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 92,30-87,70-84,50 56,50 8,00 80 1447 66,5/63,5 87,5 1842×5980×	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%609310 62,90 239,0 4,03 4,07 96,90-92,00-88,70 59,30 8,00 80 1447 66,5/63,5 87,5 1842×5980×	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-9470 64,70 245,0 4,03 4,13 9830-9340-9000 60,80 8,00 80 1620 66,0/63,0 87,0 1842×6340×	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 10680-101507780 66,80 252,0 3,94 4,13 103,40-9830-94,70 64,00 8,00 80 1620 66,0/63,0 87,0 1842×6340×
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power Starting current External static press Air flow Sound pressure Sound power	Phase Frequency ure (Max) Normal / Silent mode Normal mode HxWxD	Hz kW W/W A kW A Pa m³/min dB(A) dB(A)	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0 87,0 1842×5210× 1000/1275 3/4(19,05)/	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5 87,5 1842×5620× 1000/1335 7/8 (22,22)/	U-10ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 7,00 80 1439 65,5/62,5 86,5 1842×5570× 1000/1335 7/8 (22,22]/	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 8,00 80 1274 66,5/63,5 87,5 1842 x 5620 x 1000/1380 7/8 (22,22)/	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 4,12 9230-87,70-84,50 56,50 8,00 80 1447 66,5/63,5 87,5 1842 x 5980 x 1000/1440 7/8 (22,22)/	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%609310 62,90 239,0 4,03 4,07 %,90-9200-88,70 59,30 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8 (22,22)/	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 1035098309470 64,70 245,0 4,03 4,13 9830-9340-9000 60,00 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8 (22,22)/	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 106001015097780 66,80 252,0 3,94 4,13 103,409830-94,70 64,00 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8 (22,22)/
Outdoor unit Power supply Cooling capacity EER 11 SEER 21 Current Input power Heating capacity COP 11 SCOP 21 Current Input power Starting current External static press Air flow Sound pressure Sound power Dimension /	Phase Frequency ure (Max) Normal / Silent mode Normal mode HxWxD Liquid	Hz kW W/W A kW kW W/W A kW A B a m³/min dB(A) dB(A) mm / kg Inch (mm)	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0 87,0 1842x5210x 1000/1275 3/4(19,05)/ 7/8(22,22) 1-5/8(41,28)/	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5 87,5 1842×5620× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/	U-10ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 196,0 3,47 7,09 91;30-86;80-83,60 56,50 219,0 4,05 4,13 87;40-83,10-80,10 54,10 7,00 80 1439 65,5/62,5 86,5 1842×5570× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 80 1274 66,5/63,5 87,5 1842×5620× 1000/1380 7/8 (22,22)/ 1(25,04) 1-3/4(44,45)/	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 92,30-87,70-84,50 8,00 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%609310 62,90 239,0 4,03 4,07 %,%0-92,00-88,70 59,30 8,00 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-94,70 64,70 245,0 4,03 4,13 9830-93,40-90,00 60,80 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 1060-10150-97/80 66,80 252,0 3,94 4,13 103,40-98,30-94,70 64,00 8,00 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/
Outdoor unit Power supply Cooling capacity EER ¹¹ SEER ²¹ Current Input power Heating capacity COP ¹¹ SCOP ²¹ Current Input power Starting current External static press Air flow Sound pressure Sound power Dimension / Net weight	Phase Frequency ure (Max) Normal / Silent mode Normal mode HxWxD	Hz kW W/W A kW kW W/W A kW A B B B B B B B B B B B B B B B B B B	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0 87,0 1842×5210× 1000/1275 3/4(19,05)/ 7/8(22,22) 1-5/8(41,28)/ 1-3/4(44,45)	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5 87,5 1842×5620× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/ 1-3/4(44,45)	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91;30-86;80-83,60 56,50 219,0 4,05 4,13 87;40-83,10-80,10 7,00 80 1439 65,5/62,5 86,5 1842×5570× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/ 1-3/4(44,45)	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 80 1274 66,5/63,5 87,5 1842×5620× 1000/1380 7/8 (22,22)/ 1(25,04) 1-3/4(44,45)/ 2(50,80)	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 4,12 92,30-87,70-84,50 8,00 80 1447 66,5/63,5 87,5 1842 x 5980 x 1000/1440 7/8 (22,22)/1(25,04) 1-3/4 (44,45)/2 (50,80)	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%609310 62,90 239,0 4,03 4,07 %,%0-9200-88,70 59,30 8,00 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8 (22,22)/ 1(25,04) 1-3/4 (44,45)/ 2(50,80)	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-94,70 64,70 245,0 4,03 4,13 9830-93,40-90,00 60,80 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/ 2(50,80)	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 1060101009760 66,80 252,0 3,94 4,13 1034098309470 64,00 80 1620 66,0/63,0 87,0 1842x6340x 1000/1500 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/ 2(50,80)
Outdoor unit Power supply Cooling capacity EER ¹¹ SEER ²¹ Current Input power Heating capacity COP ¹¹ SCOP ²¹ Current Input power Starting current External static press Air flow Sound pressure Sound power Dimension / Net weight	Phase Frequency ure (Max) Normal / Silent mode Normal mode H x W x D Liquid Gas Balance	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) mm / kg Inch (mm)	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0 87,0 1842x5210x 1000/1275 3/4(19,05)/ 7/8(22,22) 1-5/8(41,28)/	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5 87,5 1842×5620× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/	U-10ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 196,0 3,47 7,09 91;30-86;80-83,60 56,50 219,0 4,05 4,13 87;40-83,10-80,10 54,10 7,00 80 1439 65,5/62,5 86,5 1842×5570× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 80 1274 66,5/63,5 87,5 1842×5620× 1000/1380 7/8 (22,22)/ 1(25,04) 1-3/4(44,45)/	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 92,30-87,70-84,50 8,00 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%609310 62,90 239,0 4,03 4,07 %,%0-92,00-88,70 59,30 8,00 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-94,70 64,70 245,0 4,03 4,13 9830-93,40-90,00 60,80 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 106010509760 66,80 252,0 3,94 4,13 10340983094,70 64,00 80 1620 66,0/63,0 87,0 1842 x 6340 x 1000/1500 7/8 [22,22]/1[25,04] 1-3/4 [44,45]/2 [50,80] 1/4 [6,35]
Outdoor unit Power supply Cooling capacity EER ¹¹ SEER ²¹ Current Input power Heating capacity COP ¹¹ SCOP ²¹ Current Input power Starting current External static press Air flow Sound pressure Sound power Dimension / Net weight	Phase Frequency ure (Max) Normal / Silent mode Normal mode H x W x D Liquid Gas Balance / CO ₂ Eq.	Hz kW W/W A kW kW W/W A kW A Pa m³/min dB(A) dB(A) mm / kg Inch (mm) Inch (mm)	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0 87,0 1842x5210x 1000/1275 3/4(19,05)/ 7/8(22,22) 1-5/8(41,28)/ 1-3/4(44,45) 1/4(6,35)	U-12ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 54,50 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5 87,5 1842×5620× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/ 1-3/4(44,45) 1/4(6,35)	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10 7,00 80 1439 65,5/62,5 86,5 1842×5570× 1000/1335 7/8(22,22)/ 1(25,04) 1-5/8(41,28)/ 1-3/4(44,45) 1/4(6,35)	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 80 1274 66,5/63,5 87,5 1842 x 5620 x 1000/1380 7/8 (22,22)/1(25,04) 1-3/4 (44,45)/2(50,80) 1/4 (6,35) 35,80/68,6952	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 98,30-93,40-90,00 60,80 233,0 4,12 4,12 92,30-87,70-84,50 8,00 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/ 2(50,80) 1/4(6,35)	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70%6,093,10 62,90 239,0 4,03 4,07 %,90-92,00-88,70 59,30 8,00 80 1447 66,5/63,5 87,5 1842×5980× 1000/1440 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/ 2(50,80) 1/4(6,35)	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-94,70 64,70 245,0 4,03 4,13 9830-9340-90,00 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8(22,22)/ 1(25,04) 1-3/4(44,45)/ 2(50,80) 1/4(6,35)	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 1060-1015097/30 66,80 252,0 3,94 4,13 103,40-98,30-94,70 64,00 8,00 80 1620 66,0/63,0 87,0 1842×6340× 1000/1500 7/8 (22,22)/ 1 (25,04) 1-3/4 (44,45)/ 2 (50,80) 1/4 (6,35)
Outdoor unit Power supply Cooling capacity EER ¹¹ SEER ²¹ Current Input power Heating capacity COP ¹¹ SCOP ²¹ Current Input power Starting current External static press Air flow Sound pressure Sound power Dimension / Net weight Piping diameter ³⁰ Refrigerant [R410A] / Maximum allowable	Phase Frequency ure (Max) Normal / Silent mode Normal mode H x W x D Liquid Gas Balance / CO ₂ Eq.	Hz kW W/W A kW kW W/W A kW A Pa m'/min dB(A) dB(A) mm / kg Inch (mm) Inch (mm)	U-10ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 185,0 3,52 6,92 85,00-80,80-77,80 52,60 207,0 4,16 4,11 81,20-77,10-74,30 49,70 7,00 80 1266 66,0/63,0 87,0 1842×5210× 1000/1275 3/4(19,05)/ 7/8(22,22) 1-5/8(41,28)/ 1-3/4(44,45) 1/4(6,35) 32,90/68,6952	U-12ME2E8 U-16ME2E8 U-20ME2E8 380 - 400 - 415 Three phase 50 190,0 3,49 6,91 88,10-83,70-80,70 213,0 4,18 4,17 83,30-79,20-76,30 51,00 7,00 80 1274 66,5/63,5 87,5 1842 x 5620 x 1000/1335 7/8 (22,22)/1(25,04) 1-5/8 (41,28)/1-3/4 (44,45) 1/4 (6,35) 35,60/74,3328	U-10MEZE8 U-20MEZE8 U-20MEZE8 380-400-415 Three phase 50 196,0 3,47 7,09 91,30-86,80-83,60 56,50 219,0 4,05 4,13 87,40-83,10-80,10 54,10 7,00 80 1439 65,5/62,5 86,5 1842 x 5570 x 1000/1335 7/8(22,22)/1(25,04) 1-5/8(41,28)/1-3/4(44,45) 1/4(6,35) 34,10/19,836	U-16ME2E8 U-16ME2E8 U-20ME2E8 380-400-415 Three phase 50 202,0 3,42 6,86 95,40-90,60-87,30 59,00 226,0 4,14 4,06 89,20-84,70-81,70 54,60 80 1274 66,5/63,5 87,5 1842 x 5620 x 1000/1380 7/8 (22,22)/1(25,04) 1-3/4 (44,45)/2(50,80) 1/4 (6,35) 35,80/68,6952	U-16ME2E8 U-18ME2E8 U-20ME2E8 380-400-415 Three phase 50 208,0 3,42 7,03 %830-9340-90,00 60,80 233,0 4,12 4,12 92,30-87,70-84,50 8,00 80 1447 66,5/63,5 87,5 1842 x 5980 x 1000/1440 7/8 (22,22)/ 1(25,04) 1-3/4 (44,45)/ 2(50,80) 1/4 (6,35) 36,80/76,8384	U-16ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 213,0 3,39 7,01 101,70-%60-%310 62,90 239,0 4,03 4,07 96,90-200-88,70 59,30 8,00 80 1447 66,5/63,5 87,5 1842 x 5980 x 1000/1440 7/8 (22,22)/1(25,04) 1-3/4 (44,45)/2(50,80) 1/4 (6,35) 36,80/76,8384	U-18ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 219,0 3,38 7,18 10350-9830-94,70 4,70 245,0 4,03 4,13 98,30-93,40-90,00 60,80 80 1620 66,0/63,0 87,0 1842 x 6340 x 1000/1500 7/8 (22,22)/1(25,04) 1-3/4 (44,45)/2(50,80) 1/4 (6,35) 38,00/79,344	U-20ME2E8 U-20ME2E8 U-20ME2E8 380-400-415 Three phase 50 224,0 3,35 7,16 10680-1015097/80 66,80 252,0 3,94 4,13 103/40-98,30-94,70 64,00 8,00 80 1620 66,0/63,0 87,0 1842 x 6340 x 1000/1500/78 (22,22)/1(25,04) 1-3/4(44,45)/2(50,80) 1/4(6,35) 38,00/79,344

1) EER and COP calculation is based in accordance to EN 14511. 2) SEER / SCOP is calculated based on the seasonal space cooling / heating efficiency "ŋ" values of the COMMISSION REGULATION (EU) 2016/2281. SEER, SCOP = [ŋ + Correction] × PEF. 3) Piping diameter under 90 m for ultimate indoor unit / over 90 m for ultimate indoor unit (if the longest piping equivalent length exceeds 90 m, increase the sizes of the main tubes by 1 rank for gas tubes and liquid tubes). 4) If the following conditions are satisfied, the effective range is above 130% and below 200%: A. Obey the limited number of connectable indoor units. B. The lower limit of operating range for heating outdoor temperature is limited to -10 °C WB (standard -25 °C WB). C. Simultaneous operation is limited to less than 130% of connectable indoor units.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. [DB: Dry Bulb; WB: Wet Bulb]. Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.



ECOi and ECO G indoor units range

1,0 kW 1,5 kW 2,2 kW 2,8 kW 3,6 kW 4,5 kW 5,6 kW Indoor units U2 type 4 way 90x90 cassette - R32 / R410A S-22MU2E5C S-28MU2E5C S-36MU2E5C S-45MU2E5C S-56MU2E5C Y3 type 4 way 60x60 cassette - R32 / R410A S-22MY3EB S-28MY3EB S-36MY3EB S-45MY3EB S-56MY3EB S-15MY3EB L1 type 2 way cassette - R410A S-28ML1E5 S-36ML1E5 S-45ML1E5 S-22ML1E5 S-56ML1E5 D1 type 1 way cassette - R410A S-28MD1E5 S-36MD1E5 S-45MD1E5 S-56MD1E5 F3 type variable static pressure adaptive duct - R32 / R410A S-15MF3E5D S-22MF3E5D S-28MF3E5D S-36MF3E5D S-45MF3E5D S-56MF3E5D **NEW M2 type slim** variable static pressure hide-away - R32 / R410A S-10MM2EB S-15MM2EB S-22MM2EB S-28MM2EB S-36MM2EB S-45MM2EB S-56MM2EB E2 type high static pressure hide-away - R410A **NEW K3 type wall**mounted - R32 / **R410A** S-15MK3E S-22MK3E S-28MK3E S-36MK3E S-45MK3E S-56MK3E T2 type ceiling - R410A S-36MT2E5A S-45MT2E5A S-56MT2E5A G1 type floor console - R410A S-22MG1E5N S-28MG1E5N S-36MG1E5N S-45MG1E5N S-56MG1E5N P1 type floor-standing - R410A S-22MP1E5 S-28MP1E5 S-36MP1E5 S-45MP1E5 S-56MP1E5 R1 type concealed floor-standing - R410A S-22MR1E5 S-28MR1E5 S-36MR1E5 S-45MR1E5 S-56MR1E5 Hydrokit for ECOi, water at 45 °C - R410A

NEW HT Booster for ECOi EX Series, water at 70 °C - R410A

Energy recovery ventilation with DX coil - HRPT Series - R32 / R410A



PAW-HRPT40HX PAW-HRPT40 (2,5 kW)



PAW-HRPT80HX PAW-HRPT80 (5 kW)

+ OPTIONAL UNITS ON VENTILATION SECTION



R32





S-73MD1E5



S-60MF3E5D S-73MF3E5D



S-90MF3E5D



S-112MF3E5D



S-140MF3E5D



S-160MF3E5D



S-280ME2E5



S-73MK3E



S-106MK3E



S-73MT2E5A



S-106MT2E5A



S-140MT2E5A



S-71MP1E5



S-71MR1E5



S-80MW1E5



S-125MW1E5





PAW-HRPT120HX PAW-HRPT120 (7 kW)





PAW-HRPT160HX PAW-HRPT200HX PAW-HRPT200 (12,5 kW)

4 way 90x90 cassette with nance X Generator Mark 3

+ C•nanoe X

Large capacity VRF. Trusted power and high efficiency. These Cassettes offer upgraded nanoe TM X technology and Econavi as accessories for making application space more comfortable and efficient.

White and graphite black panels now available for the 4 way 90x90 cassette, offering versatile options for commercial applications.



Standard panel, white (RAL9003). CZ-KPU3

Econavi panel, white (RAL9003). CZ-KPU3A



Standard panel, graphite black (RAL9011). CZ-KPU3B




Always fresh and clean air with nanoe™ X

The 4 way 90x90 cassette with nanoeTM X, when tested, has shown to inhibit hazardous substances by 92%, when compared to natural reduction*.

In addition to the 7 effects of nanoeTM X, the indoor unit can also be cleaned with a short operation of nanoeTM X and dry operation.

* Controllers (CZ-RTC5B or CZ-RTC6/BL/BLW) are required.








ECONAVI

Operates the fan to discharge internal humidity.


Optional Econavi intelligent sensor

Human activity sensor and floor temperature sensor can reduce waste energy, by optimising air conditioner operation.



Humidity sensor.


A humidity sensor positioned in the air inlet provides comfort and saves energy based on temperature and humidity.



Advanced Econavi functions.

2 sensors (movement and floor

temperature) can provide a reduction in wasted energy by means of effective control. The floor temperature can be detected with a ceiling height of up to 5 m.



Group control, circulation function.

Circulating operation is activated when a room is unoccupied to evenly distribute air and minimize thermal stratification in both heating and cooling operation.



Circulation by detecting no movement



Indirect air flow by detecting movement

U2 type 4 way 90x90 cassette - R32 / R410A

The 4 way 90x90 cassettes with integrated nance X Generator Mark 3 and design panel.

(+

COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Standard, white (RAL9003). CZ-KPU3 Econavi, white (RAL9003). CZ-KPU3A Standard, graphite black (RAL9011). CZ-KPU3B

R32



Indoor unit. S-**	*MU2E5C		22	28	36	45	56	60	73	90	112	140	160
Cooling capacity		kW	2,2	2,8	3,6	4,5	5,6	6,0	7,3	9,0	11,2	14,0	16,0
Input power		W	20,00	20,00	20,00	20,00	25,00	35,00	40,00	40,00	95,00	95,00	105,00
Current		Α	0,21	0,21	0,21	0,21	0,23	0,33	0,36	0,38	0,74	0,74	0,82
Heating capacity		kW	2,5	3,2	4,2	5,0	6,3	7,1	8,0	10,0	14,0	16,0	18,0
Input power		W	20,00	20,00	20,00	20,00	25,00	35,00	40,00	40,00	90,00	90,00	100,00
Current		Α	0,20	0,20	0,20	0,20	0,22	0,32	0,35	0,37	0,72	0,72	0,80
Fan type			Turbo fan	Turbo fan	Turbo fan	Turbo fan	Turbo fan	Turbo fan					
nanoe X Generat	or		Mark 3	Mark 3	Mark 3	Mark 3	Mark 3	Mark 3					
Air flow	Hi/	m³/min	12,8/12,1/ 11,5	12,8/12,1/ 11,5	14,5/13,0/ 11,5	15,5/13,0/ 11,5	16,5/13,5/ 11,5	21,0/16,0/ 13,0	22,5/16,0/ 13,0	23,0/18,5/ 14,0	36,0/26,0/ 20,0	36,0/26,0/ 20,0	37,0/28,0/ 24,0
Sound pressure	- Med/ - Lo	dB(A)	30/29/28	30/29/28	30/29/28	31/29/28	32/30/28	36/32/29	37/32/29	38/35/32	45/39/35	45/39/35	46/40/38
Sound power		dB(A)	45/44/43	45/44/43	45/44/43	46/44/43	47/45/43	51/47/44	52/47/44	53/50/47	60/54/50	60/54/50	61/55/53
Dimension	Indoor	mm	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840					
(HxWxD)	Panel	mm	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950					
Net weight (Pane	l)	kg	20 (5)	20 (5)	20 (5)	20 (5)	20 (5)	20 (5)	20 (5)	20 (5)	25 (5)	25 (5)	25 (5)
Piping diameter	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)
R32 model	Gas	Inch (mm)	1/2 (12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2[12,70]	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)
Piping diameter	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	3/8 (9,52) 1)	3/8 (9,52) 1)	3/8 (9,52) 1)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)
R410A model	Gas	Inch (mm)	1/2 (12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	5/8 (15,88) ^{1]}	5/8(15,88) ¹⁾	5/8 (15,88) 1	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)

1) When the piping diameter is (liquid) Ø1/4 (6,35) - (gas) Ø1/2 (12,70), connect the liquid socket tube (Ø1/4 (6,35) - Ø3/8 (9,52)) to the liquid tubing side indoor unit and connect the gas socket tube (Ø1/2 (12,70) - Ø5/8 (15,88)) to the gas tubing side indoor unit, * Above values are in the case of nance * X OFF.

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3 + CZ-RWRU3	Infrared remote controller and receiver
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black

Accessories	
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-KPU3	Standard panel, white (RAL9003)
CZ-KPU3B	Standard panel, graphite black (RAL9011)
CZ-KPU3A	Econavi exclusive panel, white (RAL9003)
CZ-CENSC1	Econavi energy saving sensor
CZ-FDU3+CZ-ATU2	Fresh air-intake kit
CZ-CGLSC2	Panasonic R32 refrigerant leak detector

Technical focus

- · High performance turbo fan
- · Lower noise in low fan operation
- · Ceiling height up to 5,0 m
- · Industry leading lightweight design
- Econavi: Temperature, humidity and activity sensor
- nanoe[™] X (Generator Mark 3: 48 trillion hydroxyl radicals/sec) as standard for better indoor air quality, indoor unit internal cleaning with nanoe[™] X and dry operation
- · Powerful drain pump gives 850 mm lift
- · Fresh air knockout
- · Branch duct connection
- High volume fresh air input with optional air-intake plenum and chamber (CZ-FDU3+CZ-ATU2)
- New graphite black and white panels providing options to suit a variety of light commercial applications


Panel design

A modern flat panel design blends into any space. These cassettes provide high energy saving, comfort and better indoor air quality that satisfy customers.

- · Flat design, well-matched with interior aesthetic
- 4-way individual flap control

The drain pipe can be raised to a maximum height of 850 mm from the bottom of the ceiling

Integrated drain pump allows a drain height of 850 mm making the installation much easier.























ECONAVI and INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. [DB; Dry Bulb; WB: Wet Bulb]. Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

Y3 type 4 way 60x60 cassette - R32 / R410A

Mini cassette with a modern panel design is available in VRF range.

The Y3 type not only perfectly matches with 600×600 mm ceiling grids but also provides the additional benefits of nanoeTM X, for better indoor air quality.



Panel. CZ-KPY4





+

COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Indoor unit			S-15MY3EB	S-22MY3EB	S-28MY3EB	S-36MY3EB	S-45MY3EB	S-56MY3EB
Cooling capacity		kW	1,5	2,2	2,8	3,6	4,5	5,6
Input power		W	19,00	20,00	21,00	22,00	30,00	42,00
Current		Α	0,24	0,24	0,25	0,26	0,34	0,43
Heating capacity		kW	1,7	2,5	3,2	4,2	5,0	6,3
Input power		W	17,00	18,00	19,00	20,00	28,00	40,00
Current		Α	0,21	0,21	0,22	0,23	0,31	0,40
Fan type			Turbo fan					
nanoe X Generator			Mark 3					
A:= #1=	Cool (Hi/Med/Lo)	m³/min	8,5/7,0/6,0	8,7/7,0/6,0	9,0/7,5/6,0	9,5/7,8/6,0	11,5/9,0/6,5	13,5/10,5/8,0
Air flow	Heat (Hi/Med/Lo)	m³/min	8,5/7,0/6,0	8,7/7,0/6,0	9,0/7,5/6,0	9,5/7,8/6,0	11,5/9,0/6,5	13,5/10,5/8,0
Sound pressure	Hi/Med/Lo	dB(A)	33/30/28	33/30/28	34/30/28	35/31/28	39/34/30	42/37/33
Sound power	Hi/Med/Lo	dB(A)	48/45/43	48/45/43	49/45/43	50/46/43	54/49/45	57/52/48
Dimension	Indoor	mm	243 x 575 x 575					
(H x W x D) 1)	Panel	mm	30 x 625 x 625					
Net weight		kg	17,8 (15 + 2,8)	17,8 (15 + 2,8)	17,8 (15+2,8)	17,8 (15 + 2,8)	17,8 (15 + 2,8)	17,8 (15 + 2,8)
Dining diameter	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)
Piping diameter	Gas	Inch (mm)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)

¹⁾ Unit height is 230 mm, but need 243 mm height in ceiling space for its installation.

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3 + CZ-RWRY3	Infrared remote controller and receiver

Accessories	
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-CENSC1	Econavi energy saving sensor
CZ-CGLSC2	Panasonic R32 refrigerant leak detector
CZ-KPY4	Panel for 4 way 60x60 cassette

Technical focus

- · Built-in drain pump
- DC drain pump and float switch to reduce the noise
- nanoe[™] X (Generator Mark 3: 48 trillion hydroxyl radicals/sec) as standard for better indoor air quality, indoor unit internal cleaning with nanoe[™] X and dry operation


Compact and stylish design

- Required ceiling depth of only 250 mm 13
- · Exposed area is only 30 mm

Individual flap control

Better control of the air flow with 4 motors, providing individual flap control.

Perfect air distribution without direct air flow, to reduce the feeling of cold drafts.



Internal cleaning function


When cooling or dry operation stopped, internal drying and nanoeTM X circulation air flow is activated in order to suppress the mould proliferation inside the unit (air flow passage, fan, heat exchanger)*.

* Depending on the installation environment or operating hours, mould proliferation or inhabitation of mould growth will be changed.

After cooling/drying operation, the inside of the indoor unit is automatically dried and nanoe $^{\text{TM}}$ X is activated to suppress mould growth.



Operates the fan to discharge internal humidity.



Uperate the fan to circulate nanoe™)
internally.























ECONAVI and INTERNET CONTROL: Optional.

¹⁾ Installation dimension.

L1 type 2 way cassette - R410A

Slim, compact and lightweight units.

Remarkable size and weight reductions have been achieved by improvement of the design around the fan, the weight of all models now just 30 kg.



+

COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Indoor unit			S-22ML1E5	S-28ML1E5	S-36ML1E5	S-45ML1E5	S-56ML1E5	S-73ML1E5
Cooling capacity		kW	2,2	2,8	3,6	4,5	5,6	7,3
Input power		W	90,00	92,00	93,00	97,00	97,00	145,00
Current		А	0,45	0,45	0,45	0,45	0,45	0,65
Heating capacity		kW	2,5	3,2	4,2	5,0	6,3	8,0
Input power		W	58,00	60,00	61,00	65,00	65,00	109,00
Current		А	0,29	0,29	0,29	0,29	0,29	0,48
Fan type			Sirocco fan					
Air flow	Hi/Med/Lo	m³/min	8,0/7,0/6,0	9,0/8,0/7,0	9,7/8,7/7,7	11,0/9,0/8,0	11,0/9,0/8,0	19,0/16,0/14,0
Sound pressure	Hi/Med/Lo	dB(A)	30/27/24	33/29/26	34/31/28	35/33/29	35/33/29	38/35/33
Dimension	Indoor	mm	350 x 840 x 600	350 x 1140 x 600				
(HxWxD)	Panel	mm	8 x 1060 x 680	8 x 1360 x 680				
Net weight (Panel)		kg	26 (8)	26 (8)	26 (8)	26 (8)	26 (8)	26 (8)
D: : : :	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)	3/8 (9,52)
Piping diameter	Gas	Inch (mm)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	5/8 (15,88)

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3 + CZ-RWRL3	Infrared remote controller and receiver

Accessories	
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-02KPL2	Panel for S-22 to S-56 models
CZ-03KPL2	Panel for S-73 model

Technical focus


- · Air flow and distribution is automatically altered depending on the operational mode of the unit
- Drain pump provides up to 500 mm lift height
- · Simplified maintenance

Simplified maintenance

The drain pan is equipped with site wiring and can be removed. The fan case has a split construction, and the fan motor can be removed easily when the lower case is removed.


Auto flap control

Air flow and distribution is automatically altered depending on the operational mode of the unit.



Drain pump provides up to 500 mm lift height

Maintenance of the drain pump is possible from two sides, from the left side (piping side) and from the inside of the unit.





















INTERNET CONTROL: Optional

D1 type 1 way cassette - R410A

Designed for installation within the ceiling void, the D1 range of slimline 1 way blow cassettes feature powerful yet quiet fans for installation of up to 4,2 m.



+

COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Indoor unit			S-28MD1E5	S-36MD1E5	S-45MD1E5	S-56MD1E5	S-73MD1E5
Cooling capacity		kW	2,8	3,6	4,5	5,6	7,3
Input power		W	51,00	51,00	51,00	60,00	87,00
Current		А	0,39	0,39	0,39	0,46	0,70
Heating capacity		kW	3,2	4,2	5,0	6,3	8,0
Input power		W	40,00	40,00	40,00	48,00	76,00
Current		А	0,35	0,35	0,35	0,41	0,65
Fan type			Sirocco fan				
Air flow	Hi/Med/Lo	m³/min	12,0/10,0/9,0	12,0/10,0/9,0	12,0/11,0/10,0	13,0/11,5/10,0	18,0/15,0/13,0
Sound pressure	Hi/Med/Lo	dB(A)	36/34/33	36/34/33	36/35/34	38/36/34	45/40/36
Dimension	Indoor	mm	200 x 1000 x 710				
(HxWxD)	Panel	mm	20 x 1230 x 800				
Net weight (Panel)		kg	23,5 (7,5)	23,5 (7,5)	23,5 (7,5)	23,5 (7,5)	24,5(7,5)
Dining diameter	Liquid	Inch (mm)	1/4(6,35)	1/4(6,35)	1/4(6,35)	1/4(6,35)	3/8 (9,52)
Piping diameter	Gas	Inch (mm)	1/2 (12,70)	1/2 (12,70)	1/2 (12,70)	1/2 (12,70)	5/8 (15,88)


Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3 + CZ-RWRD3	Infrared remote controller and receiver

Accessories	
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-KPD2	Panel

Technical focus

- · Ultra-Slim
- Suitable for standard and high ceilings
- Built-in drain pump provides 590 mm lift
- · Easy to install and maintain
- · Hanging height can be easily adjusted
- · Uses a DC fan motor to improve energy-efficiency

Drain height



With 2 types of air-blow systems, the units can be used in various ways



1. One-direction "down-blow" system.

Powerful one-direction "down-blow" system reaches the floor even from high ceilings (up to 4,2 m).



2. Two-direction ceiling-mounted system.

"Down-blow" and "front-blow" systems are combined in a ceiling-mounted unit to blow air over a wide area.



















INTERNET CONTROL: Optional.

R410A

F3 type variable static pressure adaptive duct - R32 / R410A

Design adaptive ducted F3 range.

2 installation possibilities (horizontal / vertical) with high ESP 150 Pa allows for flexible installation.





COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Indoor unit. S-**	*MF3E5D		15	22	28	36	45	56	60	73	90	112	140	160
Cooling capacity		kW	1,5	2,2	2,8	3,6	4,5	5,6	6,0	7,3	9,0	11,2	14,0	16,0
Input power		W	60,00	60,00	60,00	60,00	60,00	89,00	79,00	79,00	136,00	265,00	265,00	330,00
Current		А	0,45	0,45	0,45	0,45	0,45	0,63	0,52	0,52	0,90	1,76	1,76	2,14
Heating capacity		kW	1,7	2,5	3,2	4,2	5,0	6,3	7,1	8,0	10,0	12,5	16,0	18,0
Input power		W	60,00	60,00	60,00	60,00	60,00	89,00	79,00	79,00	136,00	265,00	265,00	330,00
Current		Α	0,45	0,45	0,45	0,45	0,45	0,63	0,52	0,52	0,90	1,76	1,76	2,14
R32 leakage sens	sors 11		2	2	2	2	2	2	2	2	2	2	2	2
Fan type			Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan						
nanoe X Generat	or		Mark 3	Mark 3	Mark 3	Mark 3	Mark 3	Mark 3						
External static pr	essure	Pa	30 (10-150)	30 (10-150)	40 (10-150)	50 (10-150)	50 (10-150)	50 (10-150)						
Air flow ^{2]}	Hi/	m³/min	12,8/11,0/ 8,0	12,8/11,0/ 8,0	12,8/11,0/ 8,0	14,0/12,0/ 8,0	14,0/12,0/ 8,0	16,0/14,0/ 10,0	21,0/18,0/ 15,0	21,0/18,0/ 15,0	25,0/23,0/ 16,0	37,0/32,0/ 26,0	37,0/32,0/ 26,0	40,0/34,0/ 28,0
Sound pressure	- Med/ _ Lo	dB(A)	31/28/20	31/28/20	31/28/20	31/28/20	31/28/20	35/32/24	31/28/23	31/28/23	35/33/25	41/36/32	41/36/32	43/37/33
Sound power		dB(A)	54/51/43	54/51/43	54/51/43	54/51/43	54/51/43	58/55/47	54/51/46	54/51/46	58/56/48	64/59/55	64/59/55	66/60/56
Dimension (HxW	xD)	mm	250 x 800 x 730	250 x 1000 x 730	250 x 1000 x 730	250×1000 ×730	250 x 1400 x 730	250 x 1400 x 730	250 x 1400 x 730					
Net weight		kg	26	26	26	26	26	26	31	31	31	40	40	40
Piping diameter	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)
R32 model	Gas	Inch (mm)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	5/8(15,88)	5/8(15,88)	5/8 (15,88)
Piping diameter	Liquid	Inch (mm)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8(9,52)	3/8 (9,52)	3/8 (9,52)
R410A model	Gas	Inch (mm)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	5/8(15,88)	5/8 (15,88)	5/8(15,88)	5/8(15,88)	5/8(15,88)	5/8 (15,88)

1) Only available in the R32 version. 2) Value referred to standard settings at shipment [H curve 8, M curve 5, L curve 1].

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white

Accessories	
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-CENSC1	Econavi energy saving sensor
PAW-APF800F	BION air pollutant filter for MF3 15, 22, 28, 36, 45 and 56
PAW-APF1000F	BION air pollutant filter for MF3 60 and 73
PAW-APF1400F	BION air pollutant filter for MF3 90, 112, 140 and 160
CZ-CGLALC1	R32 refrigerant leak alarm

Technical focus

- 4 installation possibilities with horizontal and vertical mounting, plus selectable rear or bottom air inlet
- Industry leading low noise with super quiet operation, minimum 20 dB(A)
- Only 250 mm height and lightweight unit from, 26 to 40 kg
- · Integrated Panasonic R32 refrigerant leak detectors 1)
- · Improved drain pan suitable for both horizontal / vertical installation
- · Drain pump included 2)
- nanoe™ X (Generator Mark 3: 48 trillion hydroxyl radicals/sec) as standard, effective even with duct connections up to 10 m with 3 x 90° bends 31
- BION air pollutant filter for certain types of pollutants, such as nitrogen dioxide (NO₂), nitrogen oxides (NO₂) and Ozone (O_3) (optional)

1) Only available in the R32 version. 2) For use with horizontal installation only. 3) Panasonic

Vertical Installation

Vertical installation option. Variable external static pressure to support ducted installations with bends.


* Vertical installation requires additional settings on field, please check the installation manual.



Improved drain pan design

Drain pan is shared in both cases horizontal and vertical installation.

No need to modify the unit.























ECONAVI and INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

NEW M2 type slim variable static pressure hide-away concealed duct • R32 / R410A

Upgraded nanoe™ X (Generator Mark 3).

Ultra-slim profile: 200 mm for all capacities.

Ideal for hotel application with very narrow false ceilings.

+

COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION





Indoor unit			S-10MM2EB	S-15MM2EB	S-22MM2EB	S-28MM2EB	S-36MM2EB	S-45MM2EB	S-56MM2EB
Cooling capacity		kW	1,0	1,5	2,2	2,8	3,6	4,5	5,6
Input power		W	12,00	19,00	25,00	29,00	32,00	39,00	54,00
Current		Α	0,25	0,30	0,33	0,35	0,36	0,44	0,51
Heating capacity		kW	1,3	1,7	2,5	3,2	4,2	5,0	6,3
Input power		W	12,00	19,00	25,00	29,00	32,00	39,00	54,00
Current		Α	0,25	0,30	0,33	0,35	0,36	0,44	0,51
Fan type			Sirocco fan						
Air flow	Hi/Med/Lo	m³/min	4,5/4,3/4,1	6,8/6,2/5,0	8,0/7,0/5,0	8,5/7,5/6,5	9,0/8,0/7,0	13,0/11,0/10,5	15,0/13,0/11,0
External static pres	sure	Pa	10 (30)	10 (30)	10 (30)	15 (30)	15 (40)	15 (40)	15 (40)
Sound pressure	Hi/Med/Lo 13	dB(A)	22/21/20	24/23/20	26/25/20	27/26/23	28/26/23	30/27/26	32/29/27
Sound power	Hi/Med/Lo	dB(A)	37/36/35	39/38/35	41/40/35	42/41/38	43/41/38	45/42/41	47/44/42
Dimension	HxWxD	mm	200 x 700 x 450	200 x 900 x 450	200 x 900 x 450				
Net weight		kg	17	17	17	17	17	19	19
B	Liquid	Inch (mm)	1/4(6,35)	1/4(6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)
Piping diameter	Gas	Inch (mm)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)

¹⁾ By DIP switches or by RC setting.

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function


Accessories	
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-CENSC1	Econavi energy saving sensor
CZ-CGLALC1	R32 refrigerant leak alarm

Technical focus

- · Ultra-slim profile: 200 mm for all models
- DC fan motor greatly reduces power consumption
- Ideal for hotel application with very narrow false ceilings
- Easy maintenance and service by external electrical box
- · Up to 40 Pa static pressure enables ductwork to be fitted
- Includes drain pump


In addition, its high-efficiency and extremely quiet sound levels make it very popular with many users, including hotels and small offices.

Ultra-slim profile for all models



Drain pump with increased power!

By adoption of a high-lift drain pump, the drain piping can achieve up to 500 mm lift from the outlet port of the unit.



















ECONAVI and INTERNET CONTROL: Optional.

E2 type high static pressure hide-away - R410A

High pressure duct and 100% fresh air duct function.

The E2 range of ducted units offers improved design flexibility for extended duct layouts as a result of their increased external static pressures whilst reducing energy consumption.



COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Туре			100% fresh air duct function (by using kit for 100% fresh air)				High pressure duct			
Indoor unit			S-224ME2E5		S-280ME2E5		S-224ME2E5		S-280ME2E5	
			Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Capacity		kW	22,4	21,2	28,0	26,5	22,4	25,0	28,0	31,5
Input power		W	290,00	290,00	350,00	350,00	440,00	440,00	715,00	715,00
Current		Α	1,85	1,85	2,20	2,20	2,45	2,45	3,95	3,95
Air flow	Hi/Med/Lo m³/min		28,3/-/-		35,0/—/—		56,0/51,0/44,0		72,0/63,0/53,0	
External static pressure		Pa	200		200		140 (60 - 270) 1)		140 (72 - 270) 11	
Sound pressure 2)	Hi/Med/Lo	dB(A)	43/-	-/-	44/	-/-	45/43/41		49/4	7/43
Sound power	Hi/Med/Lo	dB(A)	75/-	-/-	76/—/—		77/75/73		81/79/75	
Dimension	HxWxD	mm	479 x 1453 x 1205		479 x 1453 x 1205		479 x 1453 x 1205		479 x 1453 x 1205	
Net weight kg		kg	102		106		102		106	
Dining diameter	Liquid	Inch (mm)	3/8[9,52)	3/81	9,52)	3/8 (9,52)		3/8(9,52)
Piping diameter	Gas	Inch (mm)	3/4(19,05)	7/8(:	22,22)	3/4(19,05)		7/8(22,22)	

Rating conditions for 100% fresh air duct function: Cooling outdoor 33 °C DB / 28 °C WB. Heating outdoor 0 °C DB / -2,9 °C WB.

1) Available to select the setting by initial setup. 2) Values with 140 Pa setting. * No filter included. ** No compatible with 3-Pipe ECO G GF3.

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver


Accessories	
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-CENSC1	Econavi energy saving sensor

Technical focus

- · No need of rap valves for standard operation
- 100% fresh air duct function*
- DC fan motor for more savings
- Complete flexibility for ductwork design
- Can be located within a weatherproof housing for external installation
- · Air OFF sensor avoids cold air dumping
- Configurable air temperature control

System example

An inspection port (450 x 450 mm or more) is required at the lower side of the indoor unit body (field supply).



100% fresh air duct function

The E2 duct with 100% fresh air duct function have exceptional discharge temperature.

	Discharge	Discharge Range					
	Min	Max	Default				
Cooling	15 °C	24 °C	18 °C				
Heating	17 °C	45 °C	40 °C				

Plenums

Air outlet plenum (suitable for rigid + flexible duct)					
	Number of exits with diameters	Model			
S-224ME2E5	1 x 500 mm	CZ-TREMIESPW705			
S-280ME2E5	1 x 500 mm	CZ-TREMIESPW706			

Kit for 100% fresh air function

Kit for 2 way syste	ms	Kit for 3 way systems			
2x CZ-P160RVK2	Rap valve kit	2x CZ-P160HR3	3 way valve kit		
2x CZ-CAPE2	3 way control PCB	2x CZ-CAPE2	3 way control PCB		
CZ-P680BK2BM	Distribution joint kit	CZ-P680BH2BM	Distribution joint kit		
	1x remote controller		1x remote controller		

















ECONAVI and INTERNET CONTROL: Optional.

^{*} Rap valves required, see 100% fresh air duct function below.

NEW K3 type wall-mounted - R32 / R410A

Equipped with the upgraded nanoe $^{\text{TM}}$ X (Generator Mark 3) for improved indoor air quality.

It's modern, flat design with a stylish matte white finish complements any interior, while improved fan serviceability ensures effortless maintenance.

+

COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION



Indoor unit			S-15MK3E	S-22MK3E	S-28MK3E	S-36MK3E	S-45MK3E	S-56MK3E	S-73MK3E	S-106MK3E
Cooling capacity		kW	1,5	2,2	2,8	3,6	4,5	5,6	7,3	10,6
Input power		W	15,00	18,00	19,00	20,00	25,00	40,00	55,00	80,00
Current		А	0,18	0,19	0,20	0,22	0,25	0,35	0,50	0,70
Heating capacity		kW	1,7	2,5	3,2	4,2	5,0	6,3	8,0	10,6
Input power		W	15,00	18,00	19,00	20,00	25,00	40,00	55,00	80,00
Current		А	0,18	0,19	0,20	0,22	0,25	0,35	0,50	0,70
Fan type			Cross flow	Cross flow	Cross flow	Cross flow				
Air flow	Cool (Hi/Med/Lo)	m³/min	6,8/6,3/5,5	9,0/8,0/7,0	9,5/8,5/7,0	10,5/9,0/7,5	11,5/10,0/7,5	15,0/14,0/13,0	19,0/17,0/14,0	22,0/18,0/14,0
All Itow	Heat (Hi/Med/Lo)	m³/min	6,8/6,3/5,5	9,0/8,0/7,0	10,0/8,5/7,0	10,5/9,0/7,5	11,5/10,0/7,5	15,0/14,0/13,0	19,0/17,0/14,0	22,0/18,0/14,0
Sound pressure	Hi/Med/Lo	dB(A)	31/29/28	32/30/29	33/31/29	35/32/29	38/33/29	40/38/35	47/44/40	50/45/40
Sound power	Hi/Med/Lo	dB(A)	46/44/43	47/45/44	48/46/44	50/47/44	53/48/44	55/53/50	62/59/55	65/60/55
Dimension	HxWxD	mm	295 x 890 x 244	295x1060x249	295 x 1060 x 249	295×1060×249				
Net weight		kg	12	12	12	12	12	14	14	14
Dining diameter	Liquid	Inch (mm)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	3/8 (9,52) 13	3/8 (9,52)
Piping diameter	Gas	Inch (mm)	1/2 [12,70]	1/2 (12,70)	1/2 (12,70)	1/2 (12,70)	1/2(12,70)	1/2 (12,70)	5/8 (15,88) 1)	5/8 (15,88)

1) When the piping diameter is (liquid) Ø1/4 (6,35) - (gas) Ø1/2 (12,70), connect the liquid socket tube (Ø1/4 (6,35) - Ø3/8 (9,52)) to the liquid tubing side indoor unit and connect the gas socket tube (Ø1/2 (12,70) - Ø5/8 (15,88)) to the gas tubing side indoor unit. * Available in summer 2025.

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW2	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3	Infrared remote controller

Accessories	
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-CENSC1	Econavi energy saving sensor
CZ-P73SVK3	External valve for model sizes 15 to 73*
CZ-P106SVK3	External valve for model size 106
CZ-CGLSC2	Panasonic R32 refrigerant leak detector

Technical focus

- · Modern, flat design with a stylish matte white finish
- Quiet operation
- nanoe™ X (Generator Mark 3: 48 trillion hydroxyl radicals/sec) as standard
- Easy fan, front grill, and blow-off grill removal for easy maintenance
- Efficient installation with drain hose support holders and lock mechanism
- Piping outlet in six directions
- Air distribution is automatically altered depending on the operational mode

External valve (optional)

CZ-P73SVK3 (model sizes 15 to 73*). CZ-P106SVK3 (model size 106).

* A 3/8" to 1/4" reducer is required when combining the S-73MK3E with ECOi EX R410A outdoor units (ME2 and MF3).



Efficient installation with drain hose support holders and lock mechanism

Easy connection and disconnection of the drain hose.

Locking mechanism between the drain tray and hose ensures a tight connection during installation and easy dismantling.

Built-in support holders for secure spacing.

Holds the indoor unit against the wall, providing clear access for setting up the drain hose and piping.























ECONAVI and INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

T2 type ceiling - R410A

The T2 type ceiling mounted units feature a DC fan motor for increased efficiency and reduced operating sound levels.

All the units are the same height and depth for a uniform appearance in mixed installations, and feature a fresh air knockout for improved air quality.



COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Indoor unit			S-36MT2E5A	S-45MT2E5A	S-56MT2E5A	S-73MT2E5A	S-106MT2E5A	S-140MT2E5A
Cooling capacity		kW	3,6	4,5	5,6	7,3	10,6	14,0
Input power		W	35,00	40,00	40,00	55,00	80,00	100,00
Current		А	0,36	0,38	0,38	0,44	0,67	0,79
Heating capacity		kW	4,2	5,0	6,3	8,0	11,4	16,0
Input power		W	35,00	40,00	40,00	55,00	80,00	100,00
Current		А	0,36	0,38	0,38	0,44	0,67	0,79
Fan type			Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan
Air flow	Hi/Med/Lo	m³/min	14,0/12,0/10,5	15,0/12,5/10,5	15,0/12,5/10,5	21,0/18,0/15,5	30,0/25,0/23,0	32,0/28,0/24,0
Sound pressure	Hi/Med/Lo	dB(A)	36/32/30	37/33/30	37/33/30	39/35/33	42/37/36	46/40/37
Sound power	Hi/Med/Lo	dB(A)	54/50/48	55/51/48	55/51/48	57/53/51	60/55/54	62/58/55
Dimension	HxWxD	mm	235 x 960 x 690	235 x 960 x 690	235 x 960 x 690	235 x 1275 x 690	235 x 1590 x 690	235 x 1590 x 690
Net weight		kg	27	27	27	33	40	40
District discrete	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)
Piping diameter	Gas	Inch (mm)	1/2(12,70)	1/2 (12,70)	1/2(12,70)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)

R410A


Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3 + CZ-RWRT3	Infrared remote controller and receiver

Accessories	
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-CENSC1	Econavi energy saving sensor

Technical focus

- · Low sound levels
- · All units just 235 mm high
- · Large and wide air distribution
- · Easy to install and maintain
- · Fresh air knockout


Air distribution is altered depending on the operational



Further comfort improvement with air flow distribution

Horizontal air flow reaches maximum 9,5 m. This is ideal for wide rooms.

The wide air discharge opening expands the air flow to the left and right. The unpleasant feeling caused when the air flow directly hits the human body is prevented by the "Draft prevention position", which changes the swing width, increasing the degree of comfort.





















ECONAVI and INTERNET CONTROL: Optional.

G1 type floor console - R410A

The stylish and compact unit profile, also used for residential market range, is easy to integrate into any design of building.

Compact and versatile, this system is capable of being installed in an area with limited space. It is a perfect solution for retrofit, replacing existing radiator panels.



COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION





Indoor unit	·		S-22MG1E5N	S-28MG1E5N	S-36MG1E5N	S-45MG1E5N	S-56MG1E5N
Cooling capacity		kW	2,2	2,8	3,6	4,5	5,6
Input power		W	20,00	20,00	22,00	28,00	31,00
Current		Α	0,20	0,20	0,23	0,25	0,28
Heating capacity		kW	2,5	3,2	4,2	5,0	6,3
Input power		W	21,00	21,00	23,00	29,00	32,00
Current		А	0,20	0,20	0,24	0,26	0,28
Fan type			Cross flow				
nanoe X Generator			Mark 1				
A:- fl	Cool (Hi/Med/Lo)	m³/min	9,2/7,5/6,0	9,2/7,5/6,0	9,7/8,2/6,0	10,5/9,0/6,5	12,0/9,5/6,5
Air flow	Heat (Hi/Med/Lo)	m³/min	9,7/8,0/6,5	9,7/8,0/6,5	10,2/8,7/6,5	11,0/9,5/7,0	12,5/10,0/7,0
Sound pressure	Hi/Med/Lo	dB(A)	38/34/29	38/34/29	39/35/29	42/37/30	44/38/30
Dimension	HxWxD	mm	600 x 750 x 207				
Net weight		kg	14	14	14	14	14
Piping diameter	Liquid	Inch (mm)	1/4 (6,35)	1/4(6,35)	1/4(6,35)	1/4(6,35)	1/4 (6,35)
	Gas	Inch (mm)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)

^{*} Infrared receiver is integrated with the unit as standard.

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function
CZ-RWS3*	Infrared remote controller

Accessories	
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black
CZ-CENSC1	Econavi energy saving sensor

nanoe™ X: Bringing nature's balance indoors

Panasonic's nanoe™ X technology brings nature's detergent - hydroxyl radicals - indoors to help improve protection 24/7 against several types of pollutants can be inhibited such as certain types of bacteria, viruses, mould, allergens, pollen or hazardous substances.

Stylish and simple

- · Clean and modern European design with slim depth
- Modern matt white color panel
- · Washable air filter

The stylish and compact unit profile, also used for residential market range, is easy to integrate into any design of building.



Dimension: W x H x D = 750 x 600 x 207 mm Weight:




















Flexible easy installation

Four different mounting styles possible: exposed (floor or wall), semi-recessed and recessed.

Flexible installation with 4 different options.



Functions for comfort

- · Double Air Flow direction to maximize comfort
- Self-cleaning function
- Compatible with Commercial Wi-Fi Adaptor for cloud control

Self-cleaning function.

- Self cleaning function can be pre-scheduled with remote controller, up to a maximum of 90 minutes following cooling / dry operation
- Air flow will not blow directly at occupants during self-cleaning



P1 type floor-standing - R410A

The compact floor-standing P1 units are the ideal solution for providing perimeter air conditioning.

R1 type concealed floor-standing - R410A

At just 229 mm deep, the R1 unit can be easily concealed in perimeter areas to provide powerful and effective air conditioning.



COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

P1 indoor unit			S-22MP1E5	S-28MP1E5	S-36MP1E5	S-45MP1E5	S-56MP1E5	S-71MP1E5
R1 indoor unit			S-22MR1E5	S-28MR1E5	S-36MR1E5	S-45MR1E5	S-56MR1E5	S-71MR1E5
Cooling capacity		kW	2,2	2,8	3,6	4,5	5,6	7,1
Input power		W	56,00	56,00	85,00	126,00	126,00	160,00
Current		А	0,25	0,25	0,38	0,56	0,56	0,72
Heating capacity		kW	2,5	3,2	4,2	5,0	6,3	8,0
Input power		W	40,00	40,00	70,00	91,00	91,00	120,00
Current		Α	0,18	0,18	0,31	0,41	0,41	0,54
Fan type			Sirocco fan					
Air flow	Hi/Med/Lo	m³/min	7,0/6,0/5,0	7,0/6,0/5,0	9,0/7,0/6,0	12,0/9,0/8,0	15,0/13,0/11,0	17,0/14,0/12,0
External static pres	sure	Pa	15	15	15	15	15	15
Sound pressure	Hi/Med/Lo	dB(A)	33/30/28	33/30/28	39/35/29	38/35/31	39/36/31	41/38/35
P1 dimension	HxWxD	mm	615 x 1065 x 230	615 x 1065 x 230	615 x 1065 x 230	615 x 1380 x 230	615 x 1380 x 230	615 x 1380 x 230
P1 net weight		kg	29	29	29	39	39	39
R1 dimension	HxWxD	mm	616 x 904 x 229	616 x 904 x 229	616 x 904 x 229	616 x 1219 x 229	616 x 1219 x 229	616 x 1219 x 229
R1 net weight		kg	21	21	21	28	28	28
Dining diameter	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4(6,35)	1/4 (6,35)	1/4 (6,35)	3/8 (9,52)
Piping diameter	Gas	Inch (mm)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	1/2(12,70)	5/8 (15,88)

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function

Accessories	
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black


P1 Technical focus

- · Pipes can be connected to either side of the unit from the bottom or rear
- · Easy to install
- · Front panel opens fully for easy maintenance
- · Removable air discharge grille gives flexible air flow
- · Room for condensate pump


R1 technical focus

- · Chassis unit for discreet installation
- · Complete with removable filters
- · Pipes can be connected to either side of the unit from the bottom or rear
- · Easy to install

Effective perimeter handling



Perimeter air conditioning with high interior quality















INTERNET CONTROL: Optional.

New HT Booster for EC0i EX Series

Hydraulic module solution for high-temperature heating applications, ideal for boiler replacements.





Maximum water outlet

temperature of 70 °C.







Priority mode selectable for hot water or space heating.




Smart logic built-in controller.



Direct BMS integration.

Overview: HT Booster in VRF system

- Multiple HT Boosters can be connected within the same system circuit
- \cdot Hot water or space heating mode can be set via HT Booster
- · A 3 way water valve (field supplied) is required for the HT Booster if both DHW and space heating are needed. For DHW or space heating alone, no valve is required
- A 3-Pipe control solenoid valve kit is required for each indoor unit and HT Booster in the case of 3-Pipe ECOi EX system



* Field supplied.

NEW HT Booster for ECOi EX Series, water at 70 °C - R410A

Contributes to building decarbonisation through heat recovery operation.



Indoor unit			P-250WXHT1E5					
	Voltage	٧	400					
leating capacity Maximum temperature Dimension Vater pipe connector Vater pump (built-in) Vater flow rate Piping diameter Indoor operating range	Phase		Three phase					
	Frequency Hz		50					
	Maximum amperage	Three pha ency Hz 50 um amperage A 28 kW 25,0 11 °C 70 D mm 925×640×4 Inch R 1 ½ Modulating / EC al L/min 73 Inch (mm) 3/8(9,52 Inch (mm) 5/8(15,88 nt °C +55~+40 c -25~+52 Z-Pipe ECOI EX M	28					
Heating capacity		kW	25,0 ¹⁾					
Maximum temperature		°C	70					
Dimension	HxWxD	mm	925 x 640 x 445					
Water pipe connector		Inch	R 1 ½ Modulating / EC motor					
Water pump (built-in)			Modulating / EC motor					
Water flow rate	Nominal	L/min	73					
Dialog disease.	Liquid	Inch (mm)	3/8 (9,52)					
Piping diameter	Gas	V Thi Hz A kW °C mm 925 Inch Modulat L/min Inch (mm) 3 Inch (mm) °C °C °C -2 2-Pipe ECG 3-Pipe ECGI EX MF3	5/8(15,88)					
Indoor and the control of	Ambient	°C	+5~+40					
indoor operating range	Water	°C	+35~+70					
Outdoor operating range	Ambient	°C	-25~+52 ^{2]}					
Connectable system			2-Pipe ECOi EX ME2 R410A 3-Pipe ECOi EX MF3 R410A (heat recovery type)					
Maximum Indoor ratio (connect	able hydrokit module capacity ratio)		Total indoor unit + HT Booster capacity: up to 130%					

1) 25 kW heating capacity at 50 °C temperature, 20 kW heating capacity at 70 °C temperature, 2) Minimum operating temperature of -25 °C is considering connection with 2-Pipe EC0i EX ME2 or MZ1. For Mini EC0i or 3-Pipe EC0i EX MF3 the minimum operating range is -20 °C. For 3-Pipe EC0i EX operation, the available heating range is -25 °C to +24 °C, varying depending on the outdoor unit type. * Available in Autumn 2025.


Technical focus

- Maximum water outlet temperature of 70 °C
- Cascade circuit system using R290 refrigerant for efficient high-temperature hot water production
- · High-volume flow ensures rapid recovery and flexible installation options
- Integrated pump simplifies installation
- Built-in R290 sensor and safety ventilation compliant with IEC 60335-2-40 edition 7
- Built-in remote controller designed for straightforward programming and enhanced customisation
- Direct Modbus communication without requiring an additional interface
- Optimised control prioritising energy-saving performance, including heat recovery operation with the 3-Pipe EC0i EX outdoor unit
- Compatible with ECOi EX Series 2-Pipe (ME2) and 3-Pipe (MF3)
- Operates in ambient temperatures as low as -25 °C for heating and up to +52 °C for cooling with 2-Pipe ECOi EX outdoor unit.

How the HT Booster works

Optimised cascade circuit system with R290 refrigerant efficiently delivers high-temperature hot water up to 70 °C, ensuring energy-saving performance and sustainability.

Boosts hot water up to 70 °C



* BPHE: Brazed plate heat exchanger.

AHU connection kit MAH4M for ECOi 2-Pipe

Space-saving compact casing.

Direct Modbus communication without the need for an additional interface.

Accurate control with a pressure transducer.





Built-in controller.



PAW-P+100MAH4M			6 HP	12 HP	16 HP	18 HP	20 HP	22 HP	24 HP	34 HP 1)
Cooling capacity	Nominal	kW	16,0	33,5	45,0	50,0	56,0	61,5	68,0	96,0
Heating capacity	Nominal	kW	17,0	37,5	50,0	56,0	63,0	69,0	76,5	108,0
Air flow	Min / Max	m³/h	1800/4400	2000/10000	3500/12000	5000 / 20000	5000 / 20000	5000 / 20000	6000 / 24000	8500 / 32000
Dimension	HxWxD	mm	300 x 400 x 150							
Weight		kg	11	11	11	11	11	11	11	11
Pipe length range		m	10 ~ 100	10~100	10~100	10~100	10~100	10~100	10~100	10~100
Elevation difference (in	n / out)	m	10	10	10	10	10	10	10	10
Piping diameter	Liquid	Inch (mm)	3/8 (9,52)	1/2 (12,70)	1/2(12,70)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)	5/8 (15,88)	3/4(19,05)
≤ 90 m	Gas	Inch (mm)	5/8 (15,88)	1 (25,40)	1 1/8 (28,57)	1 1/8 (28,57)	1 1/8 (28,57)	1 1/8 (28,57)	1 1/8 (28,57)	1 1/4 (31,75)
Piping diameter	Liquid	Inch (mm)	_	5/8 (15,88)	5/8 (15,88)	3/4(19,05)	3/4(19,05)	3/4 (19,05)	3/4 [19,05]	7/8 (22,22)
> 90 m ²	Gas	Inch (mm)	_	1 1/8 (28,57)	1 1/4 (31,75)	1-1/4(31,75)	1 1/4 (31,75)	1 1/4 (31,75)	1 1/4 (31,75)	1 1/2 (38,10)

¹⁾ High-efficiency combination: U-10ME2E8 + 2×U-12ME2E8, 2) For R410A models only.

AHU connecti	on kit / system combination					
Cooling	Mini VRF		2-Pipe VRF	AHU connection kit	EEV pack	
capacity	Mini ECOi LZ2 Series (R32)	Mini EC0i LE Series (R410A)	EC0i EX ME2 Series			
4~6 HP	U-4LZ2E5(8) / U-5LZ2E5(8) / U-6LZ2E5(8)	U-4LE2E5(8) / U-5LE2E5(8) / U-6LE2E5(8)	_	PAW-P+100MAH4M	PAW-P+116EEVPACK	
8~12 HP	U-8LZ2E8 / U-10LZ2E8		U-8ME2E8 / U-10ME2E8 / U-12ME2E8	PAW-P+100MAH4M	PAW-P+133EEVPACK	
14~18 HP	-	_	U-14ME2E8 / U-16ME2E8 / U-18ME2E8	PAW-P+100MAH4M	PAW-P+145EEVPACK	
20~22 HP	-	_	20 HP (2×U-10ME2E8) 22 HP (U-10ME2E8 + U-12ME2E8)	PAW-P+100MAH4M	PAW-P+156EEVPACK	
24~34 HP	_	_	24 HP (2×U-12ME2E8) 34 HP*	PAW-P+100MAH4M	PAW-P+174EEVPACK	

^{*} Multiple combinations available.


Accessories	
PAW-P+102SENSPACK	AHU connection kit sensor pack 1 (2 pcs of SENSOR PT1000 HT IP67 -50/250 CABLE 6 m PCK)
PAW-P+116EEVPACK	EEV pack 1 (1 pc of expansion valve < 16,0 kW [R410A / R32] and 1 pc of UNIPOLAR stator]
PAW-P+133EEVPACK	EEV pack 2 (1 pc of expansion valve \leq 33,0 kW (R410A / R32) and 1 pc of UNIPOLAR stator)
PAW-P+145EEVPACK	EEV pack 3 (1 pc of expansion valve ≤ 45,0 kW (R410A / R32) and 1 pc of UNIPOLAR stator)

Accessories	
PAW-P+156EEVPACK	EEV pack 4 (1 pc of expansion valve < 61,5 kW (R410A / R32) and 1 pc of UNIPOLAR stator)
PAW-P+174EEVPACK	EEV pack 5 (1 pc of expansion valve \leq 96,0 kW (R410A / R32) and 1 pc of UNIPOLAR stator)
PAW-P+100PGNEPACK	Remote control pack (1 pc of PGNE 132 x 64 mm, mounting panel and 1 pc of cable L= 1,5 m, telephone connectors)

Technical focus

- Maximum capacity / system: 34 HP (96 kW*)
- · Selectable expansion valve packs depending on the capacity
- DC 12 V outlet available without optional interface
- Maximum elevation difference indoor/outdoor unit: 10 m
- Elevation difference (indoor unit / indoor unit): 4 m
- In / out connection capacity ratio: 50~100%
- · Maximum number of AHU connection kits: 1 unit
- Outdoor temperature range in heating: -20 ~ +15 °C
- · Available temperature range for the suction air at AHU connection kit: cool: +18 ~ +32 °C / heat: +16 ~ +30 °C
- · The system's set temperature can be selected either as the default setting discharge air temperature (supply room temperature) or the suction air set temperature (or room return air temperature)
- Accurate control with a pressure transducer
- · Direct Modbus communication with a built-in Modbus S-Link interface
- · Various technical parameters available with Modbus
- SG Ready fulfilled. Demand input can be set Thermostat OFF or 40 - 200% by the user

- Defrost operation signal, compressor status ON / OFF output
- Display an error message concerning drain water overflow
- Connectable with S-Link system. Special care for electrical noise may be necessary depending on the on-site system
- · Fan control signal output to manage the air flow (ON / OFF)
- Alarm status monitoring output
- * Nominal cooling capacity.



System and regulations. System overview.

- AHU Unit equipment (field supplied)
- Thermistor for gas pipe (E3) Pressure transductor
- Thermistor for discharge air (BL)
 Thermistor for liquid pipe (E1)
- Thermistor for suction air (TA)
- Expansion valve (accessorie part)
- Fan (field supplied)
- AHU connection kit controller box
- Optional remote controller
- Outdoor unit Mini ECOi and 2-Pipe ECOi EX

AHU connection kit MAH3M for EC0i and EC0 G

Available with ECOi and ECO G Series. CONEX Bluetooth® version (CZ-RTC6BL) is built-in. 0-10 V demand control.



CONEX CONEX Bluetooth® control built-in. CZ-RTC6BL







			5 HP	10 HP	20 HP	30 HP	40 HP	50 HP	60 HP	70 HP	80 HP
Model		PAW-	160MAH3M	280MAH3M	560MAH3M	280MAH3M	560MAH3M	560MAH3M	560MAH3M	560MAH3M	560MAH3M
						560MAH3M	560MAH3M	560MAH3M	560MAH3M	560MAH3M	560MAH3M
								280MAH3M	560MAH3M	560MAH3M	560MAH3M
										280MAH3M	560MAH3M
Cooling capacity		kW	14,0	28,0	56,0	84,0	112,0	140,0	168,0	196,0	224,0
Heating capacity		kW	16,0	31,5	63,0	95,0	127,0	155,0	189,0	219,0	252,0
Air flow	Cool Min/Max	m³/h	1140/2598	3498/4998	7002/10002	10500/15000	13998/19998	17496/24996	21000/30000	35000/24000	40000/28000
Bypass factor recommended	l		0,9	0,9	0,9	0,9	0,9	0,9	0,9	0,9	0,9
Dimension	HxWxD	mm	500 x 400 x 150	500 x 400 x 150	500 x 400 x 150	500 x 400 x 150*					
Net weight		kg	11,5	11,5	11,5	11,5*	11,5*	11,5*	11,5*	11,5*	11,5*
Pipe length range		m	10~100	10~100	10~100	10~100	10~100	10~100	10~100	10~100	10~100
Elevation difference (in / out)	Max	m	10	10	10	10	10	10	10	10	10
Dining diameter	Liquid	Inch (mm)	3/8 (9,52)	3/8 (9,52)	5/8 (15,88)	3/4(19,05)	3/4(19,05)	3/4 (19,05)	3/4 (19,05)	7/8 (22,22)	7/8 (22,22)
Piping diameter	Gas	Inch (mm)	5/8 (15,88)	7/8(22,22)	11/8(28,58)	1 1/4 (31,75)	11/2(38,15)	1 1/2 (38,15)	1 1/2 (38,15)	15/8 (41,28)	13/4(44,45)
	Cool Min~Max	°C DB	+18~+32	+18~+32	+18~+32	+18~+32	+18~+32	+18~+32	+18~+32	+18~+32	+18~+32
Intake temperature of AHU connection kit	Cool Min ~ Max	°C WB	+13~+23	+13~+23	+13~+23	+13~+23	+13~+23	+13~+23	+13~+23	+13~+23	+13~+23
connection kit	Heat Min~Max	°C	+16~+30	+16~+30	+16~+30	+16~+30	+16~+30	+16~+30	+16~+30	+16~+30	+16~+30
Ambient temperature of	Cool Min ~ Max	°C	-10~+43	-10~+43	-10~+43	-10~+43	-10~+43	-10~+43	-10~+43	-10~+43	-10~+43
outdoor unit	Heat Min~Max	°C	-20~+15	-20~+15	-20~+15	-20~+15	-20~+15	-20~+15	-20~+15	-20~+15	-20~+15

^{*} The value applies to one unit of the AHU connection kit.


AHU con	nection kit	t / system combination						
Capacity	/	EC0i	AHU kit					
5 HP	16 kW	Mini ECOi / ECO	Di EX ME2 Seri	ies	160MAH3M	_	_	_
10 HP	28 kW	U-8LZ2E8/U-10LZ2E8/ U-8LE1E8/U-10LE1E8/ U-10ME2E8	_	_	280MAH3M	_	_	-
20 HP	56 kW	U-20ME2E8	_	_	560MAH3M	_	_	_
30 HP	84 kW	U-16ME2E8	U-14ME2E8	_	560MAH3M	280MAH3M	_	_
40 HP	112 kW	U-20ME2E8	U-20ME2E8	_	560MAH3M	560MAH3M	_	_
50 HP	140 kW	U-18ME2E8	U-16ME2E8	U-16ME2E8	560MAH3M	560MAH3M	280MAH3M	_
60 HP	168 kW	U-20ME2E8	U-20ME2E8	U-20ME2E8	560MAH3M	560MAH3M	560MAH3M	_
70 HP	196 kW	U-20ME2E8	U-20ME2E8	U-20ME2E8	560MAH3M	560MAH3M	560MAH3M	280MAH3M
80 HP	224 kW	U-20ME2E8	U-20ME2E8	U-20ME2E8	560MAH3M	560MAH3M	560MAH3M	560MAH3M

Capacit	у	ECO G Series	AHU kit			
5 HP	16 kW	All ECO G	160MAH3M			
10 HP	28 kW	All ECO G	280MAH3M			
20 HP	56 kW	U-20GE3E5	560MAH3M			

Technical focus

- Maximum capacity / system: 80 HP (224 kW)
- Maximum piping length: 100 m (120 m equivalent)
- · Elevation difference (indoor unit / indoor unit): 4 m
- · In / out capacity ratio: 50~100%
- Maximum number of AHU connection kits: 4 units*
- Outdoor temperature range in heating: -20 ~ +15 °C
- Available temperature range for the suction air at AHU connection kit: cool: $+18 \sim +32$ °C / heat: $+16 \sim +30$ °C
- The systems is controlled by the suction air (or room return air) temperature (same as standard indoor unit)
- The discharge air temperature is also controlled to prevent too-low air discharge in cooling or too-high air discharge in heating (in case of VRF)
- Demand control (forcible thermostat-OFF control by operating current)
- · Defrost operation signal, Thermo-ON / OFF states output
- Drain pump control (drain pump and the float switch to be supplied in local)
- External target temperature setting via indoor / outdoor signal interface is available with CZ-CAPBC2 (Ex. 0-10 V)
- Demand control 40% to 120% (5% steps) by 0-10 V input signal
- · Connectable with S-Link system. Special care for electrical noise may be necessary depending on the on-site system

- · Fan control signal from the PCB can be used to control the air flow (high / mid / low and LL for Th-OFF). Need to change the fan control circuit wiring at field
- * To be simultaneous operation controlled by one remote controller sensor.



System and regulations. System overview.

- AHU Unit equipment (field supplied) 2 AHU Unit system controller (field
- supplied)
- 3 | AHU connection kit controller box (with control PCB)
- Thermistor for discharge air
- Electronic expansion valve
- Thermistor for gas pipe (E3) Thermistor for liquid pipe (E1)
- Thermistor for suction air
- Inter-unit wiring
- 10 | ECOi or ECOi G outdoor unit

Optional controller.

Timer remote controller. CZ-RTC5B.



Advanced energy recovery ventilation - ZY Series

- Extended 9 model line-up including 2000 m³/h model
- DC motors
- ESP up to 150 Pa
- · F7 grade filter built-in as a standard
- · Intuitive remote controller
- BMS integration with RS485



Rated flow rate			150 m³/h	250 m³/h	350 m³/h	500 m³/h	650 m³/h	800 m³/h	1000 m³/h	1500 m³/h	2000 m³/h
Indoor unit			FV-15ZY1G	FV-25ZY1G	FV-35ZY1G	FV-50ZY1G	FV-65ZY1G	FV-80ZY1G	FV-1KZY1G	FV-1HZY1G	FV-2KZY1G
	Voltage	٧	220 - 240	220 - 240	220 - 240	220 - 240	220 - 240	220 - 240	220 - 240	220 - 240	220 - 240
Power supply	Phase		Single phase	Single phase	Single phase	Single phase	Single phase	Single phase	Single phase	Single phase	Single phase
	Frequency	Hz	50	50	50	50	50	50	50	50	50
Motor type			DC	DC	DC	DC	DC	DC	DC	DC	DC
ERV											
Air flow	Max	m³/h	150	250	350	500	650	800	1000	1500	2000
External static pressure	Max	Pa	100	120	140	130	150	150	150	130	130
Sound power 2)	Max	dB(A)	37	38	39	43	45	45	46	49	51
Input power	Max	W	76~84	106~117	141 ~ 155,5	180~198	420~462	470~517	550~605	940~1034	1100~1210
Heat exchange efficiency	/ ^{3]}										
Cooling	Max	%	68,0	69,0	71,0	65,0	64,0	63,0	65,0	63,0	65,0
Heating	Max	%	83,0	82,0	83,0	81,0	82,0	83,0	82,0	83,0	82,0
Enthalpy exchange effici	ency										
Cooling	Max	%	66,0	66,0	67,0	62,5	62,5	63,5	63,0	63,5	63,0
Heating	Max	%	76,0	74,0	75,0	73,0	72,0	73,0	74,0	73,0	74,0
Adapter diameter		mm	100	150	150	200	200	250	250	250	250
Dimension	HxWxD	mm	289 x 610 x 860	289 x 735 x 860	331 x 874 x 968	331 x 1016 x 968	404 x 954 x 1008	404 x 1004 x 1224	404 x 1231 x 1224	808 x 1004 x 1224	808 x 1231 x 1224
Net weight		kg	23	27	37	40	48	60	64	119	142

¹⁾ Different dimensions depending on models, 2) Measurement of noise 1,5 m below the center of the main unit (anechoic chamber), 3) Heat exchange efficiency measurement standard JIS B 8628 (2003), * JIS B 8628 (2017) is used in the measurement environment, * A remote controller is included.

Accessories	
FV-FP15ZY1G	Replacement high efficiency filter for FV-15ZY1G
FV-FP25ZY1G	Replacement high efficiency filter for FV-25ZY1G
FV-FP35ZY1G	Replacement high efficiency filter for FV-35ZY1G

Replacement high efficiency filter for FV-50ZY1G


Accessories	
FV-FP65ZY1G	Replacement high efficiency filter for FV-65ZY1G
FV-FP80ZY1G	Replacement high efficiency filter for FV-80ZY1G and FV-1HZY1G 11
FV-FP1KZY1G	Replacement high efficiency filter for FV-1KZY1G and FV-2KZY1G 11
PAW-ERV-IAQCT	IAQ Controller

FV-FP50ZY1G


Recovers up to 83% of the heat in the outgoing air

ZY Series achieves more than 80% of heat exchange efficiency in all the line-up ^{1]}. The high recovery rate optimizes operation cost and can be considered as a sustainable solution.

1) Heating operation, H1 speed setting.



Ventilation volume setting PQ curve example.



Easy adjust for air volume balance

DC motors are equipped with independent control settings for air supply and exhaust. Air volume balance can be easily adjusted with 4 speeds settings for each Hi / Low operation.

Intuitive remote controller with RS485 connection.

- · Simple and clean screen with white back light panel
- RS485 terminal equipped to integrate with Building Management Systems
- Metal switch box is included in the package



^{1) 2} sets of filters required for those models.

Energy recovery ventilation with DX coil - HRPT Series - R32 / R410A

- Dual flow ventilation with EC fan, featuring high efficiency heat recovery (>85% η)
- · 2 types of polystyrene heat exchanger (high efficiency and sensible) with countercurrent flows and integrated bypass as standard
- Modbus connection available



COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Indoor unit with high-efficiency heat exchanger			PAW-HRPT40HX		PAW-HRPT80HX		PAW-HRPT120HX		PAW-HRPT160HX		PAW-HRPT200HX	
Voltage		V	230		230		230		230		380	
Power supply	Phase		Single phase		Single phase		Single phase		Single phase		Three phase	
	Frequency	Hz	50		50		50		50		50	
Heat recovery ventilation 1)			Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Temperature efficiency		%	63,4	76,7	60,0	73,5	61,4	75,0	62,2	76,0	59,4	73,2
Enthalpy efficiency		%	52,3	53,2	47,8	49,2	49,5	50,7	50,0	51,2	46,8	48,3
Weight kg		kg	70		120		135		150		180	

Indoor unit with sensible	heat exchanger		PAW-I	IRPT40	PAW-H	IRPT80	PAW-H	RPT120	PAW-H	RPT160	PAW-H	RPT200
	Voltage	٧	2	30	2	30	23	30	2	30	38	80
Power supply	Phase		Single	phase	Single	phase	Single	phase	Single	phase	Three	phase
	Frequency	Hz		50	5	0	5	0	5	i0	5	50
Heat recovery ventilation	1)		Cooling	Heating								
Temperature efficiency		%	84,6	84,9	84,3	84,7	84,8	85,2	84,7	85,1	83,8	84,2
Weight		kg	ć	7	1	17	1;	32	1.	47	1'	77

Common data												
DX coil 2)			Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Total / Sensible capacity		kW	3,0 / 2,4	3,2	6,0 / 4,1	6,2	8,0 / 5,5	8,3	10,0 / 7,1	11,0	12,5 / 8,6	12,8
Maximum input current		Α	1,5		2,2		4	,1	4	,4	3,	,3
Sound pressure @1 m / @3 m	1	dB(A)	41	/ 35	51,	/ 43	42	/ 36	49	/ 41	57 /	49
Air flow	High	m³/h	4	80	81	00	11	00	15	500	17	50
External static pressure	High	Pa	1	50	1	50	1	50	1	50	15	50
Dimension	HxWxD	mm	283 x 97	'5 x 1400	408 x 118	30 x 1720	408 x 158	30 x 1720	408 x 198	80 x 1720	408 x 198	30 x 1720
Dining disposits	Liquid	Inch (mm)	1/4(6,35)	3/8(9,52)	3/8(9,52)	3/8(9,52)	3/8(9	9,52)
Piping diameter	Gas	Inch (mm)	1/2 (12,70)	5/8(1	5,88)	5/8(1	5,88)	5/8(1	15,88)	5/8(1	5,88)

1) Data refers to the following conditions (UNI EN 13141-7): nominal air flow, external air 5 °C with 72% r. / expelled air 25 °C with 28% r. 2) Data refers to the following conditions: nominal air flow, cooling inlet coil summer 27 °C with 48% / heating inlet coil winter 20 °C with 50% r. * Image is for PAW-HRPT40.


Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function

Accessories	
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver
PAW-RE2C4-MOD-WH	Room controller for hotel rooms, white
PAW-RE2C4-MOD-BK	Room controller for hotel rooms, black
PAW-RE2D4-WH	Display control for hotel rooms, white
PAW-RE2D4-BK	Display control for hotel rooms, black

Interconnection to outdoor / indoor units


Technical focus

- Dual flow ventilation with EC fan, featuring high efficiency heat recovery (>85% η)
- 5 model line-up is available with air flow rates of 480, 800, 1100, 1500 and 1750 m³/h
- · 2 types of polystyrene heat exchanger (high efficiency and sensible) with counter-current flows and integrated bypass as standard
- · Automatic defrosting of the exchanger
- · Low consumption and EC motors with electronic speed control ensure high useful static pressure for circular inlet connection to air ducts
- Wide ambient temperature range up to +50 °C and down to -15 °C
- · Modbus connection available



Aeraulic performance

EC motors with electronic speed control ensure high values of effective static pressure for ducting.















S-Link communication line

Indoor terminal units

Air curtain with DX coil, connected to VRF systems

Comfort: Easy redirection of air flow by means of manual deflector.

Ease of use: Speed selector (high and low) on the unit itself.

Easy installation and maintenance: Easy installation / Compact dimensions improve installation and positioning / Easy cleaning of grid without opening of the unit.



Outdoor unit capacity			4 HP	4 HP	5 HP	8 HP
Air outlet height 2,7 m			PAW-10EAIRC-LS	PAW-15EAIRC-LS	PAW-20EAIRC-LS	PAW-25EAIRC-LS
Cooling capacity 1)	Max	kW	6,1	9,7	13,0	17,0
Heating capacity 2)	Max	kW	7,9	12,0	15,0	19,0
Air flow	High	m³/h	1800	2700	3600	4500
Heat Exchanger	Volume	L	1,67	2,85	3,94	5,03
Electric consumption fan	230 V / 50 Hz	kW	0,30	0,50	0,60	0,80
Current	230 V / 50 Hz	Α	2,10	3,10	4,10	5,10
Sound pressure 3)	Max	dB(A)	65	66	67	69
Air outlet height 3,0 m			PAW-10EAIRC-HS	PAW-15EAIRC-HS	PAW-20EAIRC-HS	PAW-25EAIRC-HS
Cooling capacity 1)	Max	kW	9,1	13,0	19,5	23,7
Heating capacity 2)	Max	kW	11,8	15,8	23,6	27,6
Air flow	High	m³/h	2700	3600	5400	6300
Heat Exchanger	Volume	L	1,67	2,85	3,94	5,12
Electric consumption fan	230 V / 50 Hz	kW	0,75	1,00	1,50	1,75
Current	230 V / 50 Hz	Α	4,10	5,50	8,20	9,60
Sound pressure 3)	Max	dB(A)	66	67	68	68
Common data						
Dimension 4)	HxWxD	mm	260 (+140) x 1000 x 460	260 (+140) x 1500 x 460	260 (+140) x 2000 x 460	260 (+140) x 2500 x 460
Nink	Air outlet height 2,7 m	kg	50	65	80	95
Net weight	Air outlet height 3,0 m	kg	55	65	85	110
Fan type			EC	EC	EC	EC
Piping diameter	Liquid / Gas	Inch (mm)	3/8 (9,52) / 5/8 (15,88)	3/8 (9,52) / 3/4 (19,05)	3/8(9,52) / 7/8 (22,22)	3/8 (9,52) / 7/8 (22,22)
Door width	<u> </u>	m	1,0	1,5	2,0	2,5
Refrigerant			R32 / R410A	R32 / R410A	R32 / R410A	R32 / R410A

LS / VRF outdoor combination							
Operation until	40 °C	35 °C	30 °C				
PAW-1EAIRC-LS	U-4	U-4	U-4				
PAW-15EAIRC-LS	U-6	U-5	U-4				
PAW-20EAIRC-LS	U-8	U-6	U-4				
PAW-25EAIRC-LS	U-8	U-8	U-5				

40 °C	35 °C	30 °C
		30 ·C
U-6	U-5	U-4
U-8	U-6	U-4
U-8	U-8	U-8
11.12	U-10	U-8
	U-12	U-12 U-10


1) Cooling capacity DX coil, air temperature in / out +27 / +18 °C, R32 and R410. 2) Heating capacity condenser, air temperature in / out +20 / +33 °C, R32 and R410. In the case of lower outdoor temperatures, an outdoor model with higher capacity may be necessary. 3) Measured in distance up to 5,0 m, direction factor 2, absorbing surfaces 200 m², Min / Max air flow. 4) 140 mm is the height of an electrical box if it is installed on the top. * Also compatible with ECO G Series (GE3 and GF3) and Hybrid Serie.

Technical focus

- · Compatible with R32 and R410A refrigerant
- Save up to 40% energy costs by use of the integrated EC fan technology (higher efficiency than conventional AC fan, soft start and longer motor duration)
- · 4 length of air curtain LS and HS are available 1,0, 1,5, 2.0 and 2.5 m
- · Installation height up to 3,0 m
- · Outlet grilles can be adjusted in five positions, to suite different indoor and installation requirements
- · Control with Panasonic remote control systems (optional)
- Direct integration to BMS via optional Panasonic interfaces
- · Drip tray included in all DX air curtains
- · Drain pump included

Internet control

An app added to your tablet or smartphone or via the Internet allows you to control and manage the system remotely. There is also the option to integrate into existing BMS systems by using other Panasonic interfaces.





Ceiling mounted air-e nanoe X Generator

- nanoe™ X technology
- (Generator Mark 1: 4,8 trillion hydroxyl radicals/sec)
- Silent operation. Whisper quiet at 25,5 dB(A)*
- Low power consumption 4 W
- · Easy installation
- · Compact and modern design
- * 230 V




Model				FV-15CSD1G	
D 1	Voltage	٧	220	230	240
Power supply	Frequency	Hz	50	50	50
A: (I		m³/h	15	16	17
Air flow		CFM	8,8	9,4	10,0
Consumption		W	4	4	4
Sound pressure		dB(A)	23,5	25,5	27,0
Net weight		kg		1,1	

^{*} The value of air volume, power consumption and noise are specified at static pressure 0 Pa. The value of air volume is the mean value and a tolerance of +-10% is allowed. The value of noise level is a weighted average sound pressure level, the mean value is measured by Panasonic. A tolerance of +3 dB/-7 dB is allowed. The noise is measure at 1 m apart from the left, the front and below of the tested product. Conditions of generating nance[™] X: room temperature: about 5 °C ~ 40 °C (dew point temperature more than 2 °C), relative humidity: about 30% ~ 85%, nance[™] X is generated using the air in the room, and its amount is subject to the temperature and humidity in the air.

One device is suitable for around 20 m² (with a ceiling height 3 m)

Ex. 3 air-e devices are required for the room size 60 m².



Concentration simulator is ready

See how nanoe TM X fills space.



The air-e is a stand alone device which is an easy and simple choice to improve indoor air quality. It can be easily installed to various commercial projects including refurbishments.





















The tested effects of nanoe™ X

Bacteria and viruses.

SARS-CoV-2: 99,9% % inhibited ¹⁾. Influenza virus H1N1 subtype: 99,9 % inhibited ²⁾.

Odour


nanoe X Generator can reduce cigarette smoke odour intensity by 2,4 levels in 12 minutes.

- 1) Novel coronavirus [SARS-CoV-2] > [Test organization] Texcell [France] [Test subject] Adhered novel coronavirus [SARS-CoV-2] [Test volume] 45 L enclosed box [Test result] Inhibited 99,9% in 2 hours [Test report] 1140-01 A1.
 2) Adhered virus [Influenza virus H1N1 subtype] > [Test organization] Kitasato Research Center for
- 2) Adhered virus (Influenza virus H1N1 subtype) > [Test organization] Kitasato Research Center for Environmental Science [Test subject] Influenza virus (H1N1 subtype) [Test volume] 1000 L enclosed box [Test result] Inhibited 99,9% in 2 hours [Test report] 21_0084_1.
- 3) Deodorisation effect for adhering odour [cigarette smoke] > [Test report 2 __008__1.

 3) Deodorisation effect for adhering odour [cigarette smoke] > [Test organization] Panasonic Product Analysis Center [Test subject] Adhered cigarette smoke odour [Test volume] Approx. 24 m² laboratory [Test result] Odour intensity reduced 2,4 levels in 0,2 hours [Test report] 4AA33-160615-N04.

Performance of nanoe™ X might differ in real life environment and is only expected in the same room as where the unit is placed. The nanoe™ X performance varies depending on the room size, environment and usage and it may take several hours to reach the full effect. nanoe™ X is not a medical device.

Deodorisation effect for adhering odour (cigarrette smoke) $^{\mbox{\scriptsize 3)}}.$



For further details and validation data, please refer to the following website.





Accessories and control

Distribution joint kits



		\sim
2-Pipe ME2 for outdoor units (up to 68,0 kW).	2-Pipe ME2 for outdoor units (from 68,0 kW to 168,0 kW).	2-Pipe ME2 and Mini ECOi for indoor units (up to 22,4 kW*).
———— CZ-P680PH2BM	 CZ-P1350PH2BM	 CZ-P224BK2BM
2-Pipe ME2 for indoor units (from 22,4 kW to 68,0 kW*).	2-Pipe ME2 for indoor units (from 68,0 kW to 168,0 kW*).	3-Pipe MF3 for outdoor units (up to 68,0 kW).
CZ-P680BK2BM	 CZ-P1350BK2BM	CZ-P680PJ2BM
3-Pipe MF3 for outdoor units (from 68,0 kW to 135,0 kW).	3-Pipe MF3 for indoor units (up to 22,4 kW).	3-Pipe MF3 for indoor units (from 22,4 kW to 68,0 kW).
———— CZ-P1350PJ2BM	CZ-P224BH2BM	CZ-P680BH2BM
3-Pipe MF3 for indoor units (up to 68,0 kW).	2-Pipe ME2 header pipe.	3-Pipe MF3 header pipe.
CZ-P1350BH2BM	CZ-P4HP4C2BM	CZ-P4HP3C2BM

^{*} In case the total capacity of indoor units connected after distribution exceeds the total capacity of the outdoor units, select the distribution piping size for the total capacity of the outdoor units.

Heat recovery box





3-Pipe control Solenoid valve kit (up to 5,6 kW).

CZ-P56HR3 + CZ-CAPE2.

KIT-P56HR3

3-Pipe control Solenoid valve kit (from 5,6 to 16,0 kW).

CZ-P160HR3 + CZ-CAPE2.

KIT-P160HR3

Solenoid valve kit (up to 5,6 kW).

CZ-P56HR3

Solenoid valve kit (from 5,6 kW to 16,0 kW).

CZ-P160HR3



3-Pipe control PCB.

CZ-CAPE2

3-Pipe control PCB for wall-mounted.

CZ-CAPEK2



4 ports 3 pipe box (up to 5,6 kW per port).

CZ-P456HR3


4 ports 3 pipe box (up to 16,0 kW per port).

CZ-P4160HR3



6 ports 3 pipe box (up to 5,6 kW per port).

CZ-P656HR3



8 ports 3 pipe box (up to 5,6 kW per port).

CZ-P856HR3

Panels



Standard panel for 4 way 90x90 cassette, white (RAL9003).

CZ-KPU3



Econavi panel for 4 way 90x90 cassette, white (RAL9003).

CZ-KPU3A



NEW Standard panel for 4 way 90x90 cassette, graphite black (RAL9011).

CZ-KPU3B



Panel for 4 way 60x60 cassette -MY3.

CZ-KPY4



Panel for ML1 22 to 56.

CZ-02KPL2

Panel for ML1 73.

CZ-03KPL2



Panel for MD1.

CZ-KPD2

Sensors









Econavi energy saving sensor.

CZ-CENSC1

Remote temperature sensor.

CZ-CSRC3

Fresh air-intake kit.

CZ-FDU3+CZ-ATU2

R32 safety measures



Leak detector for 4 way 90x90 cassette, 4 way 60x60 cassette, and wall-mounted units.

CZ-CGLSC2



R32 refrigerant leak alarm for adaptive duct and slim duct units.

CZ-CGLALC1



2-pipe safety valve kit.

CZ-P1160SVK



External 16 V power supply.

PAW-16DC-ALC1

IAQ filter for adaptive ducted unit





BION air pollutant filter for MF3 15 to 56.

PAW-APF800F

BION air pollutant filter for MF3 60 and 73.

PAW-APF1000F

BION air pollutant filter for MF3 90 to 160.

PAW-APF1400F

Plenums Valves



Air outlet plenum for MF3 15, 22, 28, 36, 45 and 56.

CZ-56DAF2

Air outlet plenum for MF3 60, 73 and 90.

CZ-90DAF2

Air outlet plenum for MF3 112, 140 and 160.

CZ-106DAF2



Air outlet plenum for S-224ME1E5.

CZ-TREMIESPW705

Air outlet plenum for S-280ME1E5.

CZ-TREMIESPW706



External valve for MK3 15 to 73.

CZ-P73SVK3*

External valve for MK3 106.

CZ-P106SVK3

Rap valve kit.

CZ-P160RVK2

^{*} A 3/8" to 1/4" reducer is required when combining the S-73MK3E with ECOi EX R410A outdoor units [ME2 and MF3],

VRF Smart Connectivity+





Remote controller Panasonic Net Con, RH, No PIR, R1/R2.

SER8150R0B1194

Remote controller Panasonic Net Con, RH, PIR, R1/R2.

SER8150R5B1194



Wireless ZigBee® Pro module / Green Com card.

VCM8000V5094P



Door/window wireless sensor.

SED-WDC-G-5045



Wall/ceiling motion/temperature/humidity sensor.

SED-MTH-G-5045



CO₂ sensor.

SED-C02-G-5045



Sensor with room temperature and humidity.

SED-TRH-G-5045



Water leakage sensor.

SED-WLS-G-5045



Cover frame. Silver.

FAS-00



Cover frame. White.

FAS-01



Cover frame. Glossy translucent

white.

FAS-03



Cover frame. Light tan wood.

FAS-05



Cover frame. Dark brown wood.

FAS-06



Cover frame. Dark black wood.

FAS-07



Cover frame. Brushed steel finish.

FAS-10

Controller and touch controllers for hotels with dry contacts





Modbus RS-485 touch room controller with I/O, white.

PAW-RE2C4-MOD-WH

Touch display control with 2 digital inputs, white.

PAW-RE2D4-WH



Modbus RS-485 touch room controller with I/O, black.

PAW-RE2C4-MOD-BK

Touch display control with 2 digital inputs, black.

PAW-RE2D4-BK

Hotel sensors for dry contacts



Wall silent motion sensor 24 V.

PAW-WMS-DC

Wall silent motion sensor 240 V

PAW-WMS-AC



Ceiling silent motion sensor

24 V.

PAW-CMS-DC

Ceiling silent motion sensor 240 V AC.

PAW-CMS-AC

Power supply 24 V.

PAW-24DC



Door or window contact.

PAW-DWC

Centralised controls



System controller for 64 indoor units with weekly timer.

CZ-64ESMC3



Central ON / OFF controller, up to 16 groups, 64 indoor units.

CZ-ANC3



Intelligent controller (touch screen/web server) to control up to 256 indoors with included load distribution ratio (LDR).

CZ-256ESMC3

Centralised controls. BMS system. PC base





P-AIMS core software: Centralised software to control up to 1024 indoor units.

CZ-CSWKC2

P-AIMS communication adaptor.

CZ-CFUNC2

P-AIMS consumption calculation extension.

CZ-CSWAC2

P-AIMS layout display extension.

CZ-CSWGC2

P-AIMS BACnet extension.

CZ-CSWBC2

P-AIMS web application extension.

CZ-CSWWC2

Panasonic AC Smart Cloud





ALL REFERENCES RELATED TO AC SMART CLOUD IS IN THE DEDICATED PAGE

Panasonic AC Smart Cloud. Cloud internet control. Up to 128 groups. Controls 128 units.

CZ-CFUSCC1

BMS interface with S-Link





A unified interface supporting Modbus, BACnet, and KNX protocols for up to 16 indoor units.

PAW-AC2-BMS-16

A unified interface supporting Modbus, BACnet, and KNX protocols for up to 64 indoor units.

PAW-AC2-BMS-64

A unified interface supporting Modbus, BACnet, and KNX protocols for up to 128 indoor units.

PAW-AC2-BMS-128

Accessories interfaces





Commercial Wi-Fi Adaptor.





PAW-RC2-KNX-1i



Modbus RTU interface (Intesis).

PAW-RC2-MBS-1



Modbus RTU interface to control 4 indoor/groups (Intesis).

PAW-RC2-MBS-4



BACnet IP and MSTP (Intesis).

C7-CAPWFC2

PAW-RC2-BAC-1



KNX interface (Airzone).

PAW-AZRC-KNX-1



Modbus RTU interface (Airzone).

PAW-AZRC-MBS-1



BACnet IP and MSTP interface (Airzone).

PAW-AZRC-BAC-1



RAC interface adapter for integration into S-Link, plus external input and alarm/ status output.

CZ-CAPRA1



LonWorks® Interface controls up to 16 groups and 64 indoor units.

CZ-CLNC2

Panclima Air Conditioning & Heating Systems

Centralised controls. Connection with general equipment



Adaptor for ON / OFF control of external devices.

CZ-CAPC3



Demand control for Mini ECOi (LZ2, LE2).

CZ-CAPDC3



Mini series parallel device controlling indoor units. maximum 1 group and 8 indoor unit.

CZ-CAPBC2



Communication Adaptor. Up to 128 groups. Controls 128 units.

CZ-CFUNC2

Individual controls



CONEX wired remote controller (non-wireless), white.

CZ-RTC6W



CONEX wired remote controller with Bluetooth®, white.

CZ-RTC6WBL



CONEX wired remote controller with Wi-Fi and Bluetooth®, white.

CZ-RTC6WBLW2*



CONEX wired remote controller (non-wireless), black.

CZ-RTC6



CONEX wired remote controller with Bluetooth®, black.

CZ-RTC6BL



CONEX wired remote controller with Wi-Fi and Bluetooth®. black.

CZ-RTC6BLW2*



Design wired remote controller with Econavi function.

CZ-RTC5B



Infrared remote controller and receiver for 4 way 60x60 cassette - MY3 with panel.

CZ-RWS3 + CZ-RWRY3













Infrared remote controller and receiver for 4 way 90x90 cassette.

CZ-RWS3 + CZ-RWRU3



CZ-RWS3 + CZ-RWRL3



Infrared remote controller and receiver for 1 way cassette.

CZ-RWS3 + CZ-RWRD3



Infrared remote controller and receiver for ceiling.



Infrared remote controller for wall-mounted and floor console.

CZ-RWS3



Infrared remote controller and receiver for all indoor units.

CZ-RWS3 + CZ-RWRC3

* Available for indoor unit types MY3, MF3, MM2, and MK3.



CZ-RWS3 + CZ-RWRT3

Accessories PCB




T10 interface PCB with digital and relay connections.

PAW-T10

PCB for fan speed control of external EC Fan.

PAW-ECF

R-22 Replacement Kit




Replacement kit for R-22.

CZ-SLK2

Accessories cables





Cable for all the T10 functions.

CZ-T10



Cable to operate external EC fan.

PAW-FDC



Cable for all option monitoring signals.


PAW-OCT



Cable with force thermo OFF/ leakage detection.

PAW-EXCT

Water heat exchanger accessories



Stacking kit for vertically stacking up to 3 WHE (4 pieces per Kit).

PAW-3WSK

Advanced energy recovery ventilation - ZY Series accessories



Replacement high efficiency filter for FV-15ZY1G.

FV-FP15ZY1G

Replacement high efficiency filter for FV-35ZY1G.

FV-FP35ZY1G

Replacement high efficiency filter for FV-65ZY1G.

FV-FP65ZY1G

Replacement high efficiency filter for FV-1KZY1G and FV-2KZY1G 1)

FV-FP1KZY1G

Replacement high efficiency filter for FV-25ZY1G.

FV-FP25ZY1G

Replacement high efficiency filter for FV-50ZY1G.

FV-FP50ZY1G

Replacement high efficiency filter for FV-80ZY1G and FV-1HZY1G 1).

FV-FP80ZY1G

IAQ Controller.

PAW-ERV-IAQCT

1) 2 sets of filters required for those models.

